





TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: PBT
 FLAMABILITY RATING: UL94-V0
 COLOR: BLUE
 CONTACT MATERIAL: COPPER ALLOY
 CONTACT TYPE: STAMPED
 CONTACT PLATING: SELECTIVE GOLD
 SHIELDING: STEEL TIN PLATED
 QUALITY CLASS: 3 AS PER CECC 75 301-802

ENVIRONMENTAL
 OPERATING TEMPERATURE: -40 UP TO 85°C
 COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
 CURRENT RATING: 3A
 WORKING VOLTAGE: 250V AC
 INSULATOR RESISTANCE: >3000 MOHM
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC/MN
 CONTACT RESISTANCE: 30 mOHM MAX

PACKAGING
 TRAY + BAG*
 *Strain relief is always delivered in a separate bag for optional use


DIMENSION

PINS	A	B	C	D
9	16.30	25.00	30.80	22.40
15	24.60	33.30	39.20	30.80
25	38.30	47.10	53.10	44.50
37	54.80	63.50	69.40	61.40

NOTE
 Pre-crim position (can slightly vary because of not totally fixed part)
 After crimp position (can slightly vary depends on the tooling used)

RoHS Compliant

PROJECTION:



GENERAL TOLERANCE

.X = ± 0.2

.XX = ± 0.15



APPROVAL: RJ

UNIT: MM

SCALE:

SHEET: 1/1

DRAW: JOE

DESCRIPTION: FEMALE IDC WITH UNC 4-40 NUT D-SUB

WERI PART NO: 6180 xx 227 221

SIZE

A4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Wurth Electronics:](#)

[618009227221](#) [618025227221](#) [618015227221](#)