

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [0152660264](#)  
**Status:** **Active**  
**Overview:** Premo-Flex™ Cable Jumpers  
**Description:** 0.50mm Pitch Premo-Flex™ FFC Jumper, Opposite Side Contacts (Type D), 24 Circuits, 0.203m Cable Length, 0.27mm Cable Thickness, Tin (Sn) Plating

**Documents:**

|                                                              |                                                                |
|--------------------------------------------------------------|----------------------------------------------------------------|
| <a href="#">Drawing (PDF)</a>                                | <a href="#">Packaging Specification PK-15266-001-001 (PDF)</a> |
| <a href="#">Product Specification PS-15266-001-001 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>           |

**General**

|                         |                                           |
|-------------------------|-------------------------------------------|
| Product Family          | Cable                                     |
| Series                  | <a href="#">15266</a>                     |
| Comments                | Contacts on opposite sides, Type D        |
| Crimp Quality Equipment | Yes                                       |
| Overview                | <a href="#">Premo-Flex™ Cable Jumpers</a> |
| Product Name            | Premo-Flex™ FFC Jumper                    |
| UPC                     | 884982434684                              |

**Physical**

|                               |                 |
|-------------------------------|-----------------|
| Cable Length                  | 0.203m          |
| Circuits (Loaded)             | 24              |
| Circuits (maximum)            | 24              |
| Net Weight                    | 1.572/g         |
| Packaging Type                | Bag             |
| Pitch - Termination Interface | 0.50mm          |
| Temperature Range - Operating | -40°C to +105°C |
| Wire Size AWG                 | N/A             |
| Wire/Cable Type               | Flat Flex Cable |

**Electrical**

|                               |        |
|-------------------------------|--------|
| Current - Maximum per Contact | 0.5A   |
| Voltage - Maximum             | 60V AC |

**Material Info**

**Reference - Drawing Numbers**

|                         |                  |
|-------------------------|------------------|
| Packaging Specification | PK-15266-001-001 |
| Product Specification   | PS-15266-001-001 |
| Sales Drawing           | SD-15266-001     |



Series image - Reference only

**EU ELV**

**Not Reviewed**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

|                 |              |
|-----------------|--------------|
| China ROHS      | Not Reviewed |
| ELV             | Not Reviewed |
| RoHS Phthalates | Not Reviewed |

**Search Parts in this Series**

[15266](#) Series

**Use With**

<a href="http://www.molex.com/product/ffc">Molex FFC – FPC connector</a>. Be sure to match like plating.

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION