

RELAYS, CONTACTORS & SWITCHES

TACTILE SWITCHES





✓ Activ

<u>±</u>

PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

FSMRA4JH04=R/A,TACT PB SW,160G

Alcoswitch | FSMRAJ

1-1825027-1

TE Internal Number: 1-1825027-1 Alias ID: FSMRA4JH

Always EU RoHS/ELV Compliant

Actuator Style Round

Operating Function No

Contact Base Material Copper Alloy

Contact Plating Silver

Dust Proof No

Product Drawings

MICRO-MINIATURE PUSHBUTTON SWITCH

PDF **English**

CAD Files

Customer View Model

3D_IGS.ZIP

Customer View Model

3D_STP.ZIP English

Customer View Model

2D_DXF.ZIP English

3D PDF PDF English

Catalog Pages/Data Sheets

SWITCHES_CORE_PROGRAM_CATALOG

PDF **English**

Product Environmental Compliance

TE Material Declaration

MD_1-1825027-1_050420142244_dmtec

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Actuator Style

Round

Dust Proof

No

Illuminatoo

\A/:+L

| | mummated | VVICTI |
|------------------------|-----------------------------|----------------------------|
| | Leg Style | Kinked |
| | Product Type | Switch |
| | | |
| Configuration Features | Operating Function | No |
| | Support Bracket | With |
| | Configuration (Pole-Throw) | Single Pole - Single Throw |
| | Number of Actuators | 1 |
| | Ganged | With |
| | ESD Grounding Terminal | Without |
| | Tactile | Yes |
| | Snap Action | Without |
| | Tactile Feel | With |
| | | |
| Body Features | Actuator Color | Black |
| | Bushing Style | Unthreaded |
| | Actuator Material | PBT |
| | Actuator Force | 160 g [5.648 oz] |
| | Actuator Profile | Extended |
| | Case Material | Nylon |
| | Case Color | Black |
| | | |
| Contact Features | Contact Base Material | Copper Alloy |
| | Contact Plating | Silver |
| | Contact Current Rating (mA) | 50 |
| Termination Features | Termination Type | Printed Circuit Board |
| Mechanical Attachment | Mounting Type | Through Hole |
| | Mounting Angle | With |
| Housing Features | Low Profile | With |
| | Process Sealed | No |
| | | |
| Dimensions | Actuator Length | 5.74 mm [.226 in] |
| | Switch Height | 7 mm [.276 in] |
| | Button Width | 3.2 mm [.126 in] |
| | | |

| Usage Conditions | Temperature Rating (°C) | Standard |
|--------------------|--|------------------------------------|
| Packaging Features | Packaging Method | Loose Piece |
| Other | Comment | (On) indicates momentary position. |
| Product Compliance | Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE | |

CUSTOMERS ALSO BOUGHT

