

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 16_SMA-50-3-15/133_N

Rev.: E



Description

Right angle cable plug

Interface Standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	18 GHz		
Frequency range	DC to 1 GHz	1 to 2.5 GHz	2.5 to 5 GHz
Return loss	≥ 36 dB	≥ 32 dB	≥ 26 dB

Mechanical Data

Centre contact	soldered
Outer contact	crimped

Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	MVQ (Silicone Rubber)	

Related Documents

Outline drawing	DOU-00170266
Catalogue drawing	DCA-00183835
Assembly instruction	DOC-0000335678

Ordering Information

Bulk 500 pcs package	16_SMA-50-3-15/133_NP
Single package	16_SMA-50-3-15/133_NE

Additional Information

Suitable cables	RG_303_/U, RG_58_C/U, GX_03272
-----------------	--------------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions