Slide Switches

5-1571005-1

Active

Product Highlights:

- Number of Positions = 2
- Single Pole - Double Throw Configuration (Pole-Throw)
- Actuator Style = Top
- Actuator Color = Yellow
- S Series

View all Features | Find Similar Products

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector
- Compare Products
- Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- SWITCH, SLIDE S(**)GPC (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Additional Information:

- Product Line Information

Application Specifications:

- None Available

Related Products:

- Tooling

Instruction Sheets:

- None Available

CAD Files:

- None Available

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Number of Positions = 2
- Configuration (Pole-Throw) = Single Pole - Double Throw
- Actuator Style = Top
- Mount Angle = Vertical
- Grade = Consumer
- Termination Type = PC
- PCB Retention Feature = Yes

Electrical Characteristics:

- Contact Rating = 0.4VA

Body Related Features:

- Actuator Color = Yellow
- Series = S
- Mount Style = Through-Hole
- PCB Tail Length (mm [in]) = 3.30 [0.130]
- PCB Retention Method = Retention Solder Tails
- Actuator Material = Thermoplastic
- Flammability Rating = UL 94V-0
- Actuator Travel = 2.20 [.087]

Contact Related Features:

- Contact Plating = Gold

Configuration Related Features:

- Terminal Configuration = Standard
- Operating Function = On None On
- Number of Actuators = Single
- Terminals Connected = 1-2, 2-3

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Always was RoHS compliant

Identification Marking:

- Stamped Marking = With

Other:

- Brand = Tyco Electronics