

## Cable marker label - WML 6 (13X13)RL - 0830677

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable marker label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X, THERMOMARK S1.1, Mounting type: Adhesive, Cable diameter: ≤6 mm, Lettering field: 13 x 13 mm

The figure shows a version of the article



### Key commercial data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 046356 718523 |
| Weight per Piece (excluding packing) | 99.99 g                                                                                                 |
| Custom tariff number                 | 39269092                                                                                                |
| Country of origin                    | Germany                                                                                                 |
| Note                                 | Made to Order (non-returnable)                                                                          |

### Technical data

#### Dimensions

|            |          |
|------------|----------|
| Length (b) | 31.75 mm |
| Width (a)  | 12.7 mm  |

#### Ambient conditions

|                                 |                                                                                         |
|---------------------------------|-----------------------------------------------------------------------------------------|
| Ambient temperature (operation) | -50 °C ... 110 °C                                                                       |
| Recommended storage conditions  | 23 °C / 50% relative humidity. Storage in poly bags is recommended prior to processing. |

#### General

|                                     |                             |
|-------------------------------------|-----------------------------|
| Color                               | white                       |
| Base element material               | Vinyl film                  |
| Components                          | Silicone-free               |
| Material                            | PVC                         |
| Wipe resistance                     | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels         | 15000                       |
| Number of individual labels per row | 7                           |

## Cable marker label - WML 6 (13X13)RL - 0830677

### Technical data

#### General

|                                                                     |                                     |
|---------------------------------------------------------------------|-------------------------------------|
| Adhesive                                                            | Acrylic                             |
| Printability                                                        | Thermal transfer                    |
| Device                                                              | 5146477 THERMOMARK ROLL             |
|                                                                     | 5146723 THERMOMARK ROLL X1          |
|                                                                     | 5146257 THERMOMARK S1.1             |
|                                                                     | 5146231 THERMOMARK X1.2             |
| Ink ribbon                                                          | 5145384 THERMOMARK-RIBBON 110       |
|                                                                     | 0829544 THERMOMARK-RIBBON 110 BU    |
|                                                                     | 0829542 THERMOMARK-RIBBON 110 GN    |
|                                                                     | 0829543 THERMOMARK-RIBBON 110 RD    |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                |
| Result                                                              | Test passed                         |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03        |
| Test duration                                                       | 96 h                                |
| Wipe resistance test result                                         | Test passed                         |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02           |
| Test duration                                                       | 96 h                                |
| Salt spray testing result                                           | Test passed                         |
| Alternating condensation climate with SO2 test specification        | DIN 50018:2013-05                   |
| Climate level                                                       | AHT 1.0 S                           |
| Cycles                                                              | 2                                   |
| Condensation test result                                            | Test passed                         |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result                                                              | Test passed                         |
| Foil strength                                                       | 50 µm                               |
| Adhesive strength                                                   | 25 µm                               |
| Marking mounting type                                               | Adhesive                            |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27400401 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 7.0 | 27400401 |
| eCl@ss 8.0 | 27400401 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000761 |
|----------|----------|

## Cable marker label - WML 6 (13X13)RL - 0830677

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC001530 |
| ETIM 5.0 | EC001530 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Accessories

#### Accessories

##### Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 110 - 5145384



Ink ribbon, Length: 300000 mm, Width: 110 mm, Color: black