

NOTES:

I. MATERIALS AND FINISHES:

HD-BNC STR PLUG - BRASS, NICKEL PLATING
BNC STR PLUG - BRASS, NICKEL PLATING
CABLE - BELDEN 1855A

2. ELECTRICAL:

A. IMPEDANCE: 75 OHM

3. MECHANICAL:

A. TEMPERATURE RANGE : -30°C TO +75°C


4. PACKAGING:

A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 95-850-130-XXX AND DATE CODE"

THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
A	RELEASE TO MFG	10-Dec-12	49339	KR
E	24.00", 48.00", METRIC LENGTHS & HST LENGTHS ADDED IN LENGTH TABLE	12/7/16	2143	VK
F	METRIC PART NUMBERS UPDATED	2/28/17	3143	



LENGTH TABLE			
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH 'L' IN INCHES [METERS]	LENGTH 'X' IN INCHES [METERS] MIN
95-850-130-006	-	6.00 [0.152]	0.75 [0.019]
-	95-850-130M025	9.84 [0.250]	
-	95-850-130M030	11.81 [0.300]	
95-850-130-012	-	12.00 [0.305]	
95-850-130-018	-	18.00 [0.457]	
-	95-850-130M050	19.69 [0.500]	1.50 [0.038]
95-850-130-024	-	24.00 [0.610]	
-	95-850-130M075	29.53 [0.750]	
95-850-130-036	-	36.00 [0.914]	
-	95-850-130M100	39.37 [1.000]	
95-850-130-048	-	48.00 [1.219]	
-	95-850-130M125	49.21 [1.250]	
-	95-850-130M150	59.05 [1.500]	
95-850-130-072	-	72.00 [1.829]	
-	95-850-130M200	78.74 [2.000]	
-	95-850-130M300	118.11 [3.000]	
-	95-850-130M400	157.48 [4.000]	
-	95-850-130M500	196.85 [5.000]	

TOLERANCE TABLE	
LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

☒ FREQUENCY : DC TO 3 GHz	☒ CONTINUITY
☐ VSWR ---- : 1 MAX	☒ HI-POT: 750 VRMS
☐ INS. LOSS: ---- dB MAX	☐ OTHER

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:		
2 PLACE DECIMAL	3 PLACE DECIMAL	ANGLES
±.015 (0,381 mm)	±.005 (0,127 mm)	± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL

SEE NOTES

REFERENCE	EAR # 7307
-----------	------------

CONFIGURATION LEVEL: In Work

FINISH

DRAWN

ENGINEER

APPROVED
K. CADOTZ

CAD FILE

DATE _____

DATE _____

DATE
00-5

LE TON

T	I	T	L	E
---	---	---	---	---

HD-BNC STR PLUG TO
BNC STR CRIMP PLUG
USING BELDEN 1855A
CABLE, VARIOUS LENGTH

SCALE: 1.8:1.0	SHEET 2 OF 2
----------------	--------------

DWG SIZE
B

REV
F

Amphenol RF

www.amphenolrf.com

DRAWING NO. 95-850-130-XXX

ITEM NO. 95-850-130-XXX

PART NO. 95-850-130-XXX

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[95-850-130-006](#) [95-850-130-012](#) [95-850-130-018](#) [95-850-130-036](#) [95-850-130-018](#) [95-850-131-036](#) [95-850-131-012](#) [95-666-44882-1](#) [95-850-131-018](#) [95-850-130-012](#) [95-666-44883-1](#) [95-850-131-006](#) [95-850-130-006](#)
[95-850-130-036](#) [95-666-44883-2](#) [95-666-44882-2](#)