

D-Sub – Accessories for subminiature D connectors

Page

Accessories

07.02

Accessories

Identification	No. of contacts	Part No.	Drawing	Dimensions in mm															
Male screw locks for use without hood	9-37 50	09 67 001 9969 ¹⁾ 09 67 001 9970 ¹⁾																	
Female screw locks with nut Thread UNC/UNC Thread UNC/M3	9-50 9-50	09 67 000 9922 ¹⁾²⁾ 09 67 000 9924 ¹⁾²⁾																	
Female screw lock with nut Thread UNC/UNC	9-50	09 67 000 9973 ¹⁾																	
Female screw locks without nut Thread UNC/UNC Thread UNC/M3	9-50 9-50	09 67 000 9972 ¹⁾²⁾ 09 67 000 9974 ¹⁾²⁾																	
Female screw locks without nut for press-in connectors with grounding-pins or straight solder with grounding-clips. Thread UNC/UNC Thread UNC/M3	9-50 9-50	09 66 000 9972 ¹⁾ 09 66 000 9974 ¹⁾²⁾																	
Female screw lock with captive washer Thread UNC/UNC	9-50	09 67 001 9957 ¹⁾																	
U-Clip with thread 4-40 UNC	9-50	09 67 001 9928																	
Dust cap black thermoplastic for male connector	9 15 25 37	09 67 009 0611 09 67 015 0611 09 67 025 0611 09 67 037 0611		<table><tr><td></td><td>A</td><td>B</td></tr><tr><td>9</td><td>17.0</td><td>22.40</td></tr><tr><td>15</td><td>25.3</td><td>30.80</td></tr><tr><td>25</td><td>38.9</td><td>44.40</td></tr><tr><td>37</td><td>55.4</td><td>60.75</td></tr></table>		A	B	9	17.0	22.40	15	25.3	30.80	25	38.9	44.40	37	55.4	60.75
	A	B																	
9	17.0	22.40																	
15	25.3	30.80																	
25	38.9	44.40																	
37	55.4	60.75																	
for female connector	9 15 25 37	09 67 009 0711 09 67 015 0711 09 67 025 0711 09 67 037 0711		<table><tr><td></td><td>A</td><td>B</td></tr><tr><td>9</td><td>16.0</td><td>22.5</td></tr><tr><td>15</td><td>24.4</td><td>31.0</td></tr><tr><td>25</td><td>37.8</td><td>44.3</td></tr><tr><td>37</td><td>54.3</td><td>60.8</td></tr></table>		A	B	9	16.0	22.5	15	24.4	31.0	25	37.8	44.3	37	54.3	60.8
	A	B																	
9	16.0	22.5																	
15	24.4	31.0																	
25	37.8	44.3																	
37	54.3	60.8																	

¹⁾ Order 2 for each connector²⁾ M3 inner thread available on request