

General data

LUMOTAST 75 IP40 pushbutton range

Illuminated pushbuttons, signal lamps and keylock switches

- Mounting hole diameter 16.2 mm
- Degree of protection IP40
- Solder terminals for the following wire cross-sections:
 - Installed 0.5 mm² max.
 - Factory terminated 0.35 mm² max.
- 250 V/4 A max.
- 3 NC + 3 NO max.
- Lamp socket T 4.5

Content

LUMOTAST 75 illuminated pushbutton IP40

| | |
|---|--------|
| LUMOTAST 75 illuminated pushbutton IP40, protruding lens, round collar | 1 - 38 |
| LUMOTAST 75 illuminated pushbutton IP40, protruding lens, square collar | 1 - 40 |
| LUMOTAST 75 illuminated pushbutton IP40, flush lens, square collar | 1 - 41 |
| LUMOTAST 75 illuminated pushbutton IP40, flush lens, rectangular collar | 1 - 42 |
| LUMOTAST 75 illuminated pushbutton IP40, protruding lens, square collar | 1 - 43 |

LUMOTAST 75 keylock switch IP40


| | |
|---|--------|
| LUMOTAST 75 keylock switch IP40, round collar | 1 - 44 |
| LUMOTAST 75 keylock switch IP40, round collar | 1 - 45 |
| LUMOTAST 75 keylock switch IP40, rectangular collar | 1 - 46 |

LUMOTAST 75 IP40 signal lamp with lamp socket T 4.5

| | |
|--|--------|
| LUMOTAST 75 IP40 signal lamp with lamp socket T 4.5, round collar, protruding lens | 1 - 48 |
| LUMOTAST 75 IP40, signal lamp, square collar, protruding lens | 1 - 49 |
| LUMOTAST 75 IP40, signal lamp, square collar, flush lens | 1 - 50 |
| LUMOTAST 75 IP40 signal lamp, rectangular collar, flush lens | 1 - 50 |
| LUMOTAST 75 IP40 signal lamp, square collar, protruding lens | 1 - 51 |

1

LUMOTAST 75 illuminated pushbutton IP40



Technical data

General information

| | |
|------------------|-----------------|
| Form of lens | see order block |
| Form of collar | see order block |
| Colour of collar | see order block |

Dimensions

| | |
|--------------------|-------------------|
| Length of collar | see order block |
| Width of collar | see order block |
| Diameter of collar | see order block |
| Overall height | 7.5 mm |
| Mounting depth | 41,5/49,5/57,5 mm |
| Mounting hole | 16.2 mm |

Mechanical design

| | |
|---------------------|---------------------------------|
| Mounting | ring nut |
| Terminals | solder terminals, tin-plated |
| Contact system | snap-action bridge contact |
| Contact function | see order block |
| Contact arrangement | see order block |
| Contact materials | Ag |
| Illuminability | yes |
| Lamp socket | T 4.5 |

Mechanical characteristics

| | |
|----------------------|-------------|
| Operating force max. | 3 ... 6.5 N |
| Operating travel | 2.7 mm |
| Switching travel NC | 1.6 mm |
| Switching travel NO | 0.9 mm |
| Robustness min. | 100 N |

Electrical characteristics

| | |
|--------------------------|-------|
| Rated voltage AC max. | 250 V |
| Rated voltage DC max. | 220 V |
| Rated voltage AC/DC min. | 12 V |

| | |
|--------------------------------------|--------|
| Rated current AC max. | 4 A |
| Rated current DC max. | 0.2 A |
| Rated current AC/DC min. | 5 mA |
| Contact resistance acc. to life max. | 200 mΩ |
| Protection class | II |

Other specifications




| | |
|---|--|
| Operating life, at 250 V/2 A (operations) | 200000 (momentary) |
| Operating life, at 250 V/4 A (operations) | 60000 (momentary), 10000 (latching) |
| Degree of protection from front side | IP40 |
| Ambient temp. operating min. | -25 °C |
| Ambient temp. operating without lamp max. | +70 °C |
| Ambient temp. operating with lamp max. | +55 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +80 °C |
| Resistance to constant environment | according to IEC 600 68-2-3 and 2-30 |
| Resistance at variable environment | according to IEC 600 68-2-14 and 2-33 |
| Approvals | ENEC 25 T 55 (70), UL, CSA |
| Flame class acc. to UL 94 | V 1 |
| Hot wire ignition acc. to IEC 695-2-1 | yes |

Accessories LUMOTAST 75 illuminated pushbutton IP40

| Description | Photo | Order no. | Page |
|---------------------------------|-------|--------------------------|-------|
| Filament lamp, T 4.5 base, 12 V | | 1.90.100.022/0000 | 5 - 6 |
| Filament lamp, T 4.5 base, 24 V | | 1.90.100.023/0000 | 5 - 6 |

LUMOTAST 75 IP40

Accessories LUMOTAST 75 illuminated pushbutton IP40

| Description | Photo | Order no. | Page |
|--|--|--------------------------|--------|
| LED T 4.5 superbright, red, 24 V |  | 1.90.690.331/0000 | 5 - 20 |
| LED T 4.5 superbright, green, 24 V |  | 1.90.690.332/0000 | 5 - 20 |
| LED T 4.5 superbright, yellow, 24 V |  | 1.90.690.333/0000 | 5 - 20 |
| LED T 4.5 superbright, blue, 24 V |  | 1.90.690.334/0000 | 5 - 20 |
| LED T 4.5 superbright, white, 24 V |  | 1.90.690.335/0000 | 5 - 20 |
| LED T 4.5, red, 3 V |  | 1.90.692.001/0000 | 5 - 19 |
| LED T 4.5, green, 3 V |  | 1.90.692.002/0000 | 5 - 19 |
| LED T 4.5, yellow, 3 V |  | 1.90.692.003/0000 | 5 - 19 |
| Lamp extractor for T 4.5/5.5, lamp diameter 4 mm |  | 1.90.900.002/0000 | 5 - 24 |
| Lamp extractor for lamp diameter 5-6 mm |  | 1.90.900.004/0000 | 5 - 24 |
| Protective cap (for 18 x 24 collar) |  | 5.05.800.027/0000 | 5 - 30 |
| Blanking cap, black, to cover spare holes, dimensions 18 x 18 mm |  | 5.52.006.020/0103 | 5 - 33 |
| Blanking cap, black, to cover spare holes, dimensions 18 x 24 mm |  | 5.52.006.021/0100 | 5 - 33 |
| Blanking cap, black, to cover spare holes, round 18 mm |  | 5.52.006.022/0100 | 5 - 33 |
| Fixing spanner M 15, M 16 |  | 5.58.002.019/0105 | 5 - 25 |

1


LUMO
75 (40)

1

LUMOTAST 75 illuminated pushbutton IP40, protruding lens, round collar



Pict.: colourless



Mounting hole

| Contact arrangement | Contact function | Colour of collar | Order no. without lens | Note |
|---------------------|------------------|------------------|--------------------------|---|
| 1 NC + 1 NO | momentary | black | 1.15.108.451/0000 | Please include the desired lens and diffuser in your order. |
| 1 NC + 1 NO | latching | black | 1.15.108.551/0000 | Please include the desired lens and diffuser in your order. |
| 2 NC + 2 NO | momentary | black | 1.15.108.452/0000 | Please include the desired lens and diffuser in your order. |
| 2 NC + 2 NO | latching | black | 1.15.108.552/0000 | Please include the desired lens and diffuser in your order. |
| 3 NC + 3 NO | momentary | black | 1.15.108.453/0000 | Please include the desired lens and diffuser in your order. |
| 3 NC + 3 NO | latching | black | 1.15.108.553/0000 | Please include the desired lens and diffuser in your order. |

Technical data see page 1 - 38

Lens, round, transparent colourless, for filament lamp or LED: **5.49.257.011/1002**

Lens, round, transparent red, for LED: **5.49.257.011/1301**

Lens, round, transparent red, for filament lamp: **5.49.257.011/1303**

Lens, round, transparent yellow, for filament lamp or LED: **5.49.257.011/1402**

Lens, round, transparent green, for filament lamp: **5.49.257.011/1502**

Lens, round, transparent green, for LED: **5.49.257.011/1503**

Lens, round, transparent blue, for filament lamp: **5.49.257.011/1601**

Accessories:

Diffuser, round, for filament lamp, without legend: **5.72.050.000/0202**


Diffuser, round, for LED, without legend: **5.72.050.000/0214**

LUMOTAST 75 IP40

LUMOTAST 75 illuminated pushbutton IP40, flush lens, square collar



Pict.: red, without ring nut



Mounting hole

| Contact arrangement | Contact function | Colour of collar | Order no. without lens | Note |
|---------------------|------------------|------------------|--------------------------|---|
| 1 NC + 1 NO | momentary | black | 1.15.108.251/0000 | Please include the desired lens and diffuser in your order. |
| 1 NC + 1 NO | latching | black | 1.15.108.351/0000 | Please include the desired lens and diffuser in your order. |
| 2 NC + 2 NO | momentary | black | 1.15.108.252/0000 | Please include the desired lens and diffuser in your order. |
| 2 NC + 2 NO | latching | black | 1.15.108.352/0000 | Please include the desired lens and diffuser in your order. |
| 3 NC + 3 NO | momentary | black | 1.15.108.253/0000 | Please include the desired lens and diffuser in your order. |
| 3 NC + 3 NO | latching | black | 1.15.108.353/0000 | Please include the desired lens and diffuser in your order. |

Technical data see page 1 - 38

Lens, square, transparent colourless, for filament lamp or LED: **5.49.275.036/1002**

Lens, square, transparent red, for LED: **5.49.275.036/1301**

Lens, square, transparent red, for filament lamp: **5.49.275.036/1303**

Lens, square, transparent yellow, for filament lamp or LED: **5.49.275.036/1402**

Lens, square, transparent green, for filament lamp: **5.49.275.036/1502**

Lens, square, transparent green, for LED: **5.49.275.036/1503**

Lens, square, transparent blue, for filament lamp: **5.49.275.036/1601**

Accessories:

Sealing cap IP65 (for 18 x 18 collar): 5.05.200.009/0000

Protective cap (for 18 x 18 collar): 5.05.800.030/0000

Diffuser, square, for filament lamp, without legend: **5.73.013.000/0202**

Diffuser, square, for LED, without legend: **5.73.013.000/0214**

1



LUMO
75 (40)

1

LUMOTAST 75 illuminated pushbutton IP40, flush lens, rectangular collar



Pict.: green



| Contact arrangement | Contact function | Colour of collar | Order no. without lens | Note |
|---------------------|------------------|------------------|--------------------------|---|
| 1 NC + 1 NO | momentary | black | 1.15.108.051/0000 | Please include the desired lens and diffuser in your order. |
| 1 NC + 1 NO | latching | black | 1.15.108.151/0000 | Please include the desired lens and diffuser in your order. |
| 2 NC + 2 NO | momentary | black | 1.15.108.052/0000 | Please include the desired lens and diffuser in your order. |
| 2 NC + 2 NO | latching | black | 1.15.108.152/0000 | Please include the desired lens and diffuser in your order. |
| 3 NC + 3 NO | momentary | black | 1.15.108.053/0000 | Please include the desired lens and diffuser in your order. |
| 3 NC + 3 NO | latching | black | 1.15.108.153/0000 | Please include the desired lens and diffuser in your order. |

Technical data see page 1 - 38

Lens, rectangular, transparent colourless, for filament lamp or LED: **5.49.275.032/1002**

Lens, rectangular, transparent red, for LED: **5.49.275.032/1301**

Lens, rectangular, transparent red, for filament lamp: **5.49.275.032/1303**

Lens, rectangular, transparent yellow, for filament lamp or LED: **5.49.275.032/1402**

Lens, rectangular, transparent green, for filament lamp: **5.49.275.032/1502**

Lens, rectangular, transparent green, for LED: **5.49.275.032/1503**

Lens, rectangular, transparent blue, for filament lamp: **5.49.275.032/1601**

Accessories:


Sealing cap IP65 (for 18 x 24 collar): 5.05.200.008/0000

Protective cap (for 18 x 24 collar): 5.05.800.027/0000

Diffuser, rectangular, for filament lamp, without legend: **5.73.012.000/0202**

Diffuser, rectangular, for LED, without legend: **5.73.012.000/0214**

LUMOTAST 75 illuminated pushbutton IP40, protruding lens, square collar



| Contact arrangement | Contact function | Colour of collar | Order no. without lens | Note |
|---------------------|------------------|------------------|------------------------|---|
| 1 NC + 1 NO | momentary | black | 1.15.108.256/0000 | Please include the desired lens and diffuser in your order. |
| 1 NC + 1 NO | latching | black | 1.15.108.356/0000 | Please include the desired lens and diffuser in your order. |
| 2 NC + 2 NO | momentary | black | 1.15.108.257/0000 | Please include the desired lens and diffuser in your order. |
| 2 NC + 2 NO | latching | black | 1.15.108.357/0000 | Please include the desired lens and diffuser in your order. |
| 3 NC + 3 NO | momentary | black | 1.15.108.258/0000 | Please include the desired lens and diffuser in your order. |
| 3 NC + 3 NO | latching | black | 1.15.108.358/0000 | Please include the desired lens and diffuser in your order. |

Technical data see page 1 - 38

Lens, square, transparent colourless, for filament lamp or LED: **5.49.275.036/1002**

Lens, square, transparent red, for LED: **5.49.275.036/1301**

Lens, square, transparent red, for filament lamp: **5.49.275.036/1303**

Lens, square, transparent yellow, for filament lamp or LED: **5.49.275.036/1402**

Lens, square, transparent green, for filament lamp: **5.49.275.036/1502**

Lens, square, transparent green, for LED: **5.49.275.036/1503**

Lens, square, transparent blue, for filament lamp: **5.49.275.036/1601**

Accessories:

Sealing cap IP65 (for 18 x 18 collar): 5.05.200.009/0000

Protective cap (for 18 x 18 collar): 5.05.800.030/0000

Diffuser, square, for filament lamp, without legend: **5.73.013.000/0202**

Diffuser, square, for LED, without legend: **5.73.013.000/0214**

1

LUMO
75 (40)

LUMOTAST 75 keylock switch IP40



Technical data

General information

| | |
|------------------|-----------------|
| Form of lens | see order block |
| Colour of collar | see order block |
| Form of collar | see order block |

Dimensions

| | |
|------------------------------|-----------------|
| Length of collar | see order block |
| Diameter of collar | see order block |
| Width of collar | see order block |
| Overall height (without key) | 7.5 mm |
| Mounting depth | see order block |
| Mounting hole | 16.2 mm |

Mechanical design

| | |
|-----------------------------|------------------------------|
| Mounting | ring nut |
| Terminals | solder terminals, tin-plated |
| Contact system | snap-action bridge contact |
| Contact function | see order block |
| Contact arrangement | see order block |
| Contact materials | Ag |
| Illuminability | no |
| Lock | cylinder lock |
| Wafers | 4 pins |
| Lock type | 1D 21 |
| Number of locking positions | 45 |
| Main key | no |
| Symmetric key | no |
| Key removal position | see order block |

Mechanical characteristics

| | |
|----------------|-----------------|
| Rotating angle | see order block |
|----------------|-----------------|

Electrical characteristics

| | |
|--------------------------------------|--------|
| Rated voltage AC max. | 250 V |
| Rated voltage DC max. | 220 V |
| Rated voltage AC/DC min. | 12 V |
| Rated current AC max. | 4 A |
| Rated current DC max. | 0.02 A |
| Rated current AC/DC min. | 5 mA |
| Contact resistance acc. to life max. | 200 mΩ |
| Bouncing time max. | 10 ms |
| ESD-strength min. | 14 kV |

Other specifications

| | |
|---|---------------------------------------|
| Operating life, at 250 V/2 A (operations) | 50000 (momentary) |
| Operating life, at 250 V/4 A (operations) | 50000 (momentary) |
| Degree of protection from front side | IP40 |
| Ambient temp. operating min. | -25 °C |
| Ambient temp. operating max. | +70 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +80 °C |
| Resistance to constant environment | according to IEC 600 68-2-3 and 2-30 |
| Resistance at variable environment | according to IEC 600 68-2-14 and 2-33 |
| Weight max. | 35 g |
| Approvals | ENEC 25 T 55 (70), UL, CSA |
| Flame class acc. to UL 94 | V 1 |
| Hot wire ignition acc. to IEC 695-2-1 | yes |

Accessories LUMOTAST 75 keylock switch IP40


| Description | Photo | Order no. | Page |
|--|-------|-------------------|--------|
| Blanking cap, black, to cover spare holes, dimensions 18 x 24 mm | | 5.52.006.021/0100 | 5 - 33 |
| Blanking cap, black, to cover spare holes, round 18 mm | | 5.52.006.022/0100 | 5 - 33 |






LUMOTAST 75 IP40

Accessories LUMOTAST 75 keylock switch IP40

| Description | Photo | Order no. | Page |
|---------------------------|--|--------------------------|--------|
| Fixing spanner M 15, M 16 |  | 5.58.002.019/0105 | 5 - 25 |
| Spare key for LUMO 75 |  | 5.58.002.030/0000 | |
| Key cap for LUMO 75 |  | 5.58.004.721/0000 | |

LUMOTAST 75 keylock switch IP40, round collar



| Contact arrangement | Contact function | Rotating angle | Key removal position | Colour of collar | Order no. complete |
|---------------------|------------------|----------------|---|------------------|--------------------------|
| 1 NC + 1 NO | latching | 90° |  | black | 1.15.108.851/0000 |
| 1 NC + 1 NO | latching | 90° |  | black | 1.15.108.911/0000 |
| 1 NC + 1 NO | momentary | 45° |  | black | 1.15.108.941/0000 |
| 2 NC + 2 NO | latching | 90° |  | black | 1.15.108.852/0000 |
| 2 NC + 2 NO | latching | 90° |  | black | 1.15.108.912/0000 |


Technical data see page 1 - 44

Included: 2 keys.

Other lock variants and contacts available on request.

1

LUMOTAST 75 keylock switch IP40, rectangular collar



| Contact arrangement | Contact function | Rotating angle | Key removal position | Colour of collar | Order no. complete |
|---------------------|------------------|----------------|----------------------|------------------|--------------------------|
| 1 NC + 1 NO | latching | 90° | 0 | black | 1.15.108.571/0100 |
| 1 NC + 1 NO | latching | 90° | 0+1 | black | 1.15.108.631/0100 |
| 1 NC + 1 NO | momentary | 45° | 0 | black | 1.15.108.661/0100 |
| 2 NC + 2 NO | latching | 90° | 0 | black | 1.15.108.572/0100 |
| 2 NC + 2 NO | latching | 90° | 0+1 | black | 1.15.108.632/0100 |

Technical data see page 1 - 44

Included: 2 keys.
Other lock variants and contacts available on request.

LUMO
75 (40)

LUMOTAST 75 IP40 signal lamp with lamp socket T 4.5



Technical data

General information

| | |
|------------------|-----------------|
| Form of lens | see order block |
| Form of collar | see order block |
| Colour of collar | see order block |

Dimensions

| | |
|--------------------|-----------------|
| Length of collar | see order block |
| Width of collar | see order block |
| Diameter of collar | see order block |
| Overall height | 7.5 mm |
| Mounting depth | 33.5 mm |
| Mounting hole | 16.2 mm |

Mechanical design

| | |
|-------------|---------------------------------|
| Mounting | ring nut |
| Terminals | solder terminals, tin-plated |
| Lamp socket | T 4.5 |
| Lamp | filament lamp / LED |

Electrical characteristics

| | |
|--------------------|-------|
| Voltage limit max. | 42 V |
| Power limit max. | 1.2 W |

Other specifications

| | |
|--------------------------------------|---------------------------------------|
| Degree of protection from front side | IP40 |
| Weight | 5 g |
| Approvals | ENEC 25 T 55 (70), UL, CSA |
| Ambient temp. operating min. | -25 °C |
| Ambient temp. operating max. | +55 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +80 °C |
| Resistance to constant environment | according to IEC 600 68-2-3 and 2-30 |
| Resistance at variable environment | according to IEC 600 68-2-14 and 2-33 |

Accessories LUMOTAST 75 IP40 signal lamp with lamp socket T 4.5

| Description | Photo | Order no. | Page |
|-------------------------------------|-------|--------------------------|--------|
| Filament lamp, T 4.5 base, 12 V | | 1.90.100.022/0000 | 5 - 6 |
| Filament lamp, T 4.5 base, 24 V | | 1.90.100.023/0000 | 5 - 6 |
| LED T 4.5 superbright, red, 24 V | | 1.90.690.331/0000 | 5 - 20 |
| LED T 4.5 superbright, green, 24 V | | 1.90.690.332/0000 | 5 - 20 |
| LED T 4.5 superbright, yellow, 24 V | | 1.90.690.333/0000 | 5 - 20 |
| LED T 4.5 superbright, blue, 24 V | | 1.90.690.334/0000 | 5 - 20 |
| LED T 4.5 superbright, white, 24 V | | 1.90.690.335/0000 | 5 - 20 |


Accessories LUMOTAST 75 IP40 signal lamp with lamp socket T 4.5

| Description | Photo | Order no. | Page |
|--|---|-------------------|--------|
| LED T 4.5, red, 3 V |  | 1.90.692.001/0000 | 5 - 19 |
| LED T 4.5, green, 3 V |  | 1.90.692.002/0000 | 5 - 19 |
| LED T 4.5, yellow, 3 V |  | 1.90.692.003/0000 | 5 - 19 |
| Blanking cap, black, to cover spare holes, dimensions 18 x 18 mm |  | 5.52.006.020/0103 | 5 - 33 |
| Blanking cap, black, to cover spare holes, dimensions 18 x 24 mm |  | 5.52.006.021/0100 | 5 - 33 |
| Blanking cap, black, to cover spare holes, round 18 mm |  | 5.52.006.022/0100 | 5 - 33 |
| Fixing spanner M 15, M 16 |  | 5.58.002.019/0105 | 5 - 25 |

1

LUMO
75 (40)

LUMOTAST 75 IP40 signal lamp with lamp socket T 4.5, round collar, protruding lens



| Voltage limit max. | Power limit max. | Lamp socket | Colour of collar | Order no. without lens | Note |
|--------------------|------------------|-------------|------------------|--------------------------|---|
| 42 V | 1.2 W | T 4.5 | black | 1.65.111.071/0000 | Please include the desired lens and diffuser in your order. |

Technical data see page 1 - 48

Lens, round, transparent colourless, for filament lamp or LED: **5.49.257.011/1002**

Lens, round, transparent red, for LED: **5.49.257.011/1301**

Lens, round, transparent red, for filament lamp: **5.49.257.011/1303**

Lens, round, transparent yellow, for filament lamp or LED: **5.49.257.011/1402**

Lens, round, transparent green, for filament lamp: **5.49.257.011/1502**

Lens, round, transparent green, for LED: **5.49.257.011/1503**

Lens, round, transparent blue, for filament lamp: **5.49.257.011/1601**


Accessories:

Diffuser, round, for filament lamp, without legend: 5.72.050.000/0202

Diffuser, round, for LED, without legend: **5.72.050.000/0214**

1

LUMOTAST 75 IP40, signal lamp, square collar, flush lens



| Voltage limit max. | Power limit max. | Lamp socket | Colour of collar | Order no. without lens | Note |
|--------------------|------------------|-------------|------------------|------------------------|---|
| 42 V | 1.2 W | T 4.5 | black | 1.65.111.061/0000 | Please include the desired lens and diffuser in your order. |

Technical data see page 1 - 48

Lens, square, transparent colourless, for filament lamp or LED: **5.49.275.036/1002**

Lens, square, transparent red, for LED: **5.49.275.036/1301**

Lens, square, transparent red, for filament lamp: **5.49.275.036/1303**

Lens, square, transparent yellow, for filament lamp or LED: **5.49.275.036/1402**

Lens, square, transparent green, for filament lamp: **5.49.275.036/1502**

Lens, square, transparent green, for LED: **5.49.275.036/1503**

Lens, square, transparent blue, for filament lamp: **5.49.275.036/1601**


Accessories:

Diffuser, square, for filament lamp, without legend: **5.73.013.000/0202**

Diffuser, square, for LED, without legend: **5.73.013.000/0214**

LUMO
75 (40)

LUMOTAST 75 IP40 signal lamp, rectangular collar, flush lens



| Voltage limit max. | Power limit max. | Lamp socket | Colour of collar | Order no. without lens | Note |
|--------------------|------------------|-------------|------------------|------------------------|---|
| 42 V | 1.2 W | T 4.5 | black | 1.65.111.051/0000 | Please include the desired lens and diffuser in your order. |

Technical data see page 1 - 48

Lens, rectangular, transparent colourless, for filament lamp or LED: **5.49.275.032/1002**

Lens, rectangular, transparent red, for LED: **5.49.275.032/1301**

Lens, rectangular, transparent red, for filament lamp: **5.49.275.032/1303**

Lens, rectangular, transparent yellow, for filament lamp or LED: **5.49.275.032/1402**

Lens, rectangular, transparent green, for filament lamp: **5.49.275.032/1502**

Lens, rectangular, transparent green, for LED: **5.49.275.032/1503**

Lens, rectangular, transparent blue, for filament lamp: **5.49.275.032/1601**


Accessories:

Diffuser, rectangular, for filament lamp, without legend: **5.73.012.000/0202**

Diffuser, rectangular, for LED, without legend: **5.73.012.000/0214**

LUMOTAST 75 IP40

LUMOTAST 75 IP40 signal lamp, square collar, protruding lens



| Voltage limit max. | Power limit max. | Lamp socket | Colour of collar | Order no. without lens | Note |
|--------------------|------------------|-------------|------------------|------------------------|---|
| 42 V | 1.2 W | T 4.5 | black | 1.65.111.081/0000 | Please include the desired lens and diffuser in your order. |

Technical data see page 1 - 48

- Lens, square, transparent colourless, for filament lamp or LED: **5.49.275.036/1002**
- Lens, square, transparent red, for LED: **5.49.275.036/1301**
- Lens, square, transparent red, for filament lamp: **5.49.275.036/1303**
- Lens, square, transparent yellow, for filament lamp or LED: **5.49.275.036/1402**
- Lens, square, transparent green, for filament lamp: **5.49.275.036/1502**
- Lens, square, transparent green, for LED: **5.49.275.036/1503**
- Lens, square, transparent blue, for filament lamp: **5.49.275.036/1601**

Accessories:

- Diffuser, square, for filament lamp, without legend: **5.73.013.000/0202**
- Diffuser, square, for LED, without legend: **5.73.013.000/0214**

1

LUMO
75 (40)