

Conductor marker carrier - PATO 3/15 - 1013135

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 4.4 - 6.7 mm, lettering field size: 4 x 15 mm

Why buy this product

- ✓ Can be labeled using UC-WMT ... and US-WMT ... plastic labels or EMT insert strips
- ✓ These marking collars are used for subsequent labeling of systems that have already been wired

RoHS

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	500 STK
GTIN	 4 017918 013554
GTIN	4017918013554
Weight per Piece (excluding packing)	0.700 g
Custom tariff number	39269097
Country of origin	Germany

Technical data

Dimensions

Length (b)	15 mm
Width (a)	9 mm
Cable diameter	4.4 mm ... 6.7 mm

Ambient conditions

Ambient temperature (operation)	-50 °C ... 80 °C
---------------------------------	------------------

Conductor marker carrier - PATO 3/15 - 1013135

Technical data

General

Color	transparent
Type	Profile
Components	Silicone-free
Flammability rating according to UL 94	V0
Material	PVC
Marking mounting type	clip on

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 4.0	24190219
eCl@ss 4.1	24190219
eCl@ss 5.0	27149103
eCl@ss 5.1	27141137
eCl@ss 6.0	27141137
eCl@ss 7.0	27141137
eCl@ss 8.0	27400401
eCl@ss 9.0	27400401

ETIM

ETIM 2.0	EC000761
ETIM 3.0	EC000761
ETIM 4.0	EC001530
ETIM 5.0	EC002248

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121410
UNSPSC 11	39121410
UNSPSC 12.01	39121410
UNSPSC 13.2	39131504