

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0010181037

Status:

Active

Overview:

Standard .093" Pin and Socket Connectors

Description:

2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 2 Female Terminals, 1 Male Terminal

Documents:

3D Model

Packaging Specification PK-3099-002 (PDF)

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

LR19980

UL

E29179

General

Product Family

PCB Headers

Series

3099

Application

Power, Wire-to-Board

Comments

Solder Type|Round Pin

Overview

Standard .093" Pin and Socket Connectors

Product Name

Standard .093"

UPC

800754215244

Physical

Breakaway

No

Circuits (Loaded)

3

Circuits (maximum)

3

Color - Resin

Black

Durability (mating cycles max)

25

Flammability

94V-2

Glow-Wire Compliant

No

Lock to Mating Part

Yes

Material - Metal

Phosphor Bronze

Material - Plating Mating

Tin

Material - Plating Termination

Tin

Material - Resin

Polyester

Net Weight

1.322/g

Number of Rows

1

Orientation

Vertical

PC Tail Length

4.32mm

PCB Locator

Yes

PCB Retention

None

PCB Thickness - Recommended

1.60mm

Packaging Type

Bag

Pitch - Mating Interface

5.03mm

Plating min - Mating

1.270µm

Plating min - Termination

1.270µm

Polarized to PCB

Yes

Shrouded

Fully

Stackable

No

Surface Mount Compatible (SMC)

No

Temperature Range - Operating

-40°C to +105°C

Termination Interface: Style

Through Hole


Electrical

Current - Maximum per Contact

5.0A

Voltage - Maximum

250V



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Contains SVHC(2015 June 15): No

Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

Green Image

Not Relevant

Search Parts in this Series

3099 Series

Mates With

03-09-1081 , 03-09-1032

Solder Process Data

Duration at Max. Process Temperature (seconds)	005
Lead-freeProcess Capability	WAVE
Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	235

Material Info

Old Part Number	3099P3H
-----------------	---------

Reference - Drawing Numbers

Packaging Specification	PK-3099-002
Sales Drawing	SDA-3099-*3**

This document was generated on 01/27/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION