

**W-Series  
WDU 2.5 SW****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

www.weidmueller.com

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |                                                                      |
|------------|----------------------------------------------------------------------|
| Type       | WDU 2.5 SW                                                           |
| Order No.  | <a href="#">1020010000</a>                                           |
| Version    | Feed-through terminal, Screw connection, 2.5 mm², 800 V, 24 A, Black |
| GTIN (EAN) | 4008190297749                                                        |
| Qty.       | 100 pc(s).                                                           |

**W-Series**  
**WDU 2.5 SW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|        |         |                 |            |
|--------|---------|-----------------|------------|
| Width  | 5.1 mm  | Width (inches)  | 0.201 inch |
| Height | 60 mm   | Height (inches) | 2.362 inch |
| Depth  | 46.5 mm | Depth (inches)  | 1.831 inch |
| Weight | 7.94 g  | Net weight      | 7.47 g     |

**Temperatures**

|                                  |        |                                  |        |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -60 °C | Continuous operating temp., max. | 130 °C |
|----------------------------------|--------|----------------------------------|--------|

**Material data**

|                           |       |        |       |
|---------------------------|-------|--------|-------|
| Material                  | Wemid | Colour | Black |
| UL 94 flammability rating | V-0   |        |       |

**Rating data IECEx/ATEX**

|                                |                                                                                                   |                                 |                     |
|--------------------------------|---------------------------------------------------------------------------------------------------|---------------------------------|---------------------|
| Certificate No. (ATEX)         | DEMKO14ATEX1338U                                                                                  | Certificate No. (IECEX)         | IECEXULD14.0005U    |
| Max. voltage (ATEX)            | 690 V                                                                                             | Current (ATEX)                  | 24 A                |
| Wire cross section max. (ATEX) | 2.5 mm <sup>2</sup>                                                                               | Max. voltage (IECEX)            | 690 V               |
| Current (IECEX)                | 24 A                                                                                              | Wire cross section max. (IECEX) | 2.5 mm <sup>2</sup> |
| Operating temperature range    | For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity | Marking EN 60079-7              |                     |
| Ex 2014/34/EU label            | II 2 G D                                                                                          |                                 | Ex e II             |

**System specifications**

|                                   |                                                                                                          |                               |     |
|-----------------------------------|----------------------------------------------------------------------------------------------------------|-------------------------------|-----|
| Version                           | Screw connection, for plug-in cross-connector, for screwable cross-connection, One end without connector | End cover plate required      | Yes |
| Number of potentials              | 1                                                                                                        | Number of levels              | 1   |
| No. of clamping points per level  | 2                                                                                                        | Number of potentials per tier | 1   |
| Levels cross-connected internally | No                                                                                                       | PE connection                 | No  |
| Mounting rail                     | TS 35                                                                                                    | N-function                    | No  |
| PE function                       | No                                                                                                       | PEN function                  | No  |

**2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)**

|                                                                                                            |                     |                                                                                                            |                     |
|------------------------------------------------------------------------------------------------------------|---------------------|------------------------------------------------------------------------------------------------------------|---------------------|
| Cross-section for connected wire, solid, two clampable wires, min.                                         | 0.5 mm <sup>2</sup> | Cross-section for connected wire, solid, two clampable wires, max.                                         | 1.5 mm <sup>2</sup> |
| Wire connection cross section, finely stranded, two clampable wires, min.                                  | 0.5 mm <sup>2</sup> | Wire cross-section, finely stranded, two clampable wires, max.                                             | 1.5 mm <sup>2</sup> |
| Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, min. | 0.5 mm <sup>2</sup> | Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, max. | 1.5 mm <sup>2</sup> |

**Additional technical data**

|                          |       |                             |         |
|--------------------------|-------|-----------------------------|---------|
| Explosion-tested version | Yes   | Number of similar terminals | 1       |
| Open sides               | right | Type of mounting            | Snap-on |

**W-Series**  
**WDU 2.5 SW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Technical data**
**CSA rating data**

|                               |                |                               |        |
|-------------------------------|----------------|-------------------------------|--------|
| Certificate No. (CSA)         | 200039-1057876 | Current size C (CSA)          | 20 A   |
| Voltage size C (CSA)          | 600 V          | Wire cross section max. (CSA) | 12 AWG |
| Wire cross section min. (CSA) | 26 AWG         |                               |        |

**Conductors for clamping (rated connection)**

|                                                                                                                               |                      |                                                                                                                                       |                     |
|-------------------------------------------------------------------------------------------------------------------------------|----------------------|---------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| Blade size                                                                                                                    | 0.6 x 3.5 mm         | Clamping range, rated connection, max.                                                                                                | 4 mm <sup>2</sup>   |
| Clamping range, rated connection, min.                                                                                        | 0.05 mm <sup>2</sup> | Clamping screw                                                                                                                        | M 2.5               |
| Connection direction                                                                                                          |                      | Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min. | 0.5 mm <sup>2</sup> |
|                                                                                                                               | on side              | Number of connections                                                                                                                 | 2                   |
| Gauge to IEC 60947-1                                                                                                          | A3                   | Tightening torque, max.                                                                                                               | 0.8 Nm              |
| Stripping length                                                                                                              | 10 mm                | Torque level with DMS electric screwdriver                                                                                            | 1                   |
| Tightening torque, min.                                                                                                       | 0.4 Nm               | Twin wire-end ferrules, min.                                                                                                          | 0.5 mm <sup>2</sup> |
| Twin wire-end ferrules, max.                                                                                                  | 1.5 mm <sup>2</sup>  | Wire connection cross section AWG, max.                                                                                               | AWG 12              |
| Type of connection                                                                                                            | Screw connection     | Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, max.                             | 2.5 mm <sup>2</sup> |
| Wire connection cross section AWG, min.                                                                                       | AWG 30               | Wire connection cross section, finely stranded, max.                                                                                  | 4 mm <sup>2</sup>   |
| Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, min.                     | 0.5 mm <sup>2</sup>  | Wire connection cross section, solid core, min. rated connection                                                                      | 0.5 mm <sup>2</sup> |
| Wire connection cross section, solid core max. rated connection                                                               | 4 mm <sup>2</sup>    | Wire connection cross section, stranded, rated connection, min.                                                                       | 1.5 mm <sup>2</sup> |
| Wire connection cross section, stranded, rated connection, max.                                                               | 4 mm <sup>2</sup>    | Wire connection cross-section, finely stranded, min.                                                                                  | 0.5 mm <sup>2</sup> |
| Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max. | 2.5 mm <sup>2</sup>  |                                                                                                                                       |                     |

**Dimensions**

|              |       |
|--------------|-------|
| TS 35 offset | 29 mm |
|--------------|-------|

**Rating data**

|                                 |                     |                                              |         |
|---------------------------------|---------------------|----------------------------------------------|---------|
| Rated cross-section             | 2.5 mm <sup>2</sup> | Rated voltage                                | 800 V   |
| Rated current                   | 24 A                | Current at maximum wires                     | 32 A    |
| Standards                       | IEC 60947-7-1       | Volume resistance according to IEC 60947-7-x | 1.33 mΩ |
| Rated impulse withstand voltage | 8 kV                | Pollution severity                           | 3       |

**UL rating data**

|                                         |        |                                         |        |
|-----------------------------------------|--------|-----------------------------------------|--------|
| Certificate No. (UR)                    | E60693 | Conductor size Factory wiring max. (UR) | 12 AWG |
| Conductor size Factory wiring min. (UR) | 30 AWG | Conductor size Field wiring max. (UR)   | 12 AWG |
| Conductor size Field wiring min. (UR)   | 28 AWG | Current size B (UR)                     | 25 A   |
| Current size C (UR)                     | 25 A   | Voltage size B (UR)                     | 600 V  |
| Voltage size C (UR)                     | 600 V  |                                         |        |

**W-Series**  
**WDU 2.5 SW**
**Weidmüller Interface GmbH & Co. KG**

 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmüller.com

**Technical data**
**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000897    | ETIM 4.0   | EC000897    |
| ETIM 5.0   | EC000897    | ETIM 6.0   | EC000897    |
| UNSPSC     | 30-21-18-11 | eClass 5.1 | 27-14-11-20 |
| eClass 6.2 | 27-14-11-20 | eClass 7.1 | 27-14-11-20 |
| eClass 8.1 | 27-14-11-20 | eClass 9.0 | 27-14-11-20 |
| eClass 9.1 | 27-14-11-20 |            |             |

**Product information**

|                                 |                                                                                                                                                 |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Descriptive text ordering data  | Rated voltage 400V when using cross-connection ZQV. See section "W-series accessories" for colours available.                                   |
| Descriptive text technical data | 2.5 mm <sup>2</sup> conductor with wire end ferrule plus plastic collar only with collar optimised for diameter (order No. 1333100000, 500 pcs) |
| Descriptive text accessories    | Ensure 2.5 mm <sup>2</sup> max. when using the WQB. Only 400 V when using the shielding rail LS 2,8 1056400000.                                 |

**Approvals**

Approvals



ROHS Conform

**Downloads**

|                                             |                                                                                                                                                                                                                                                |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">CFAT_WDU 2.5.pdf</a><br><a href="#">IECEXULD14.0005U_e.pdf</a><br><a href="#">CB Test Zertifikat</a><br><a href="#">CB Zertifikat</a><br><a href="#">DE_PT1001_20160414_165_ISSUE01.pdf</a><br><a href="#">ACF-ATEX_4786180920</a> |
| Engineering Data                            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>                                                                                                                                                                                                       |
| User Documentation                          | <a href="#">NTI_IECEX_WDU-WPE 2.5.pdf</a>                                                                                                                                                                                                      |

**Safety note**

|               |                                    |
|---------------|------------------------------------|
| Safety notice | <a href="#">Safety Information</a> |
|---------------|------------------------------------|

### W-Series WDU 2.5 SW

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold


Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings



**W-Series**  
**WDU 2.5 SW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Accessories**
**Blank**


The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**General ordering data**

| Type       | Order No.                  | Version                    | GTIN (EAN)    | Qty.         |
|------------|----------------------------|----------------------------|---------------|--------------|
| DEK 5/5 MC | <a href="#">1609801044</a> | Dekafix, Terminal marker,  | 4008190397111 | 1,000 pc(s). |
| NE WS      |                            | 5 x 5 mm, Pitch in mm (P): |               |              |
|            |                            | 5.00 Weidmueller, White    |               |              |

**Shielding bus**

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

| Type      | Order No.                  | Version              | GTIN (EAN)    | Qty.       |
|-----------|----------------------------|----------------------|---------------|------------|
| LS 2.8    | <a href="#">1056400000</a> | W-Series, Shield bus | 4008190036454 | 100 pc(s). |
| WDU2.5-10 |                            |                      |               |            |

## W-Series WDU 2.5 SW

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

## Accessories

### Blank



The WAD connector marker is suitable for W-series terminals and for the WEW 35/2 and ZEW 35/2 end brackets. The markers are available as blank markers, with custom printing or standard print with lightning symbol. The WAD MultiCard markers are suitable for labelling with PrintJet ADVANCED printers.

- High-quality and resistant printing with PrintJet
- WAD marker and cover for the W-series terminals and the WEW 35/2 or ZEW 35/2 end brackets
- Available as blank markers, with custom printing or standard print with lightning symbol
- Quick and easy installation

### General ordering data

| Type              | Order No.                  | Version                                                                                       | GTIN (EAN) | Qty. |
|-------------------|----------------------------|-----------------------------------------------------------------------------------------------|------------|------|
| WAD 5 MC<br>NE GE | <a href="#">1112920000</a> | Group marker, Cover, 33.3 x 403224889 177 148 pc(s).<br>5 mm, Pitch in mm (P): 5.00<br>Yellow |            |      |
| WAD 5 MC<br>NE WS | <a href="#">1112910000</a> | Group marker, Cover, 33.3 x 403224889 1689 48 pc(s).<br>5 mm, Pitch in mm (P): 5.00<br>White  |            |      |

### Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

### General ordering data

| Type                | Order No.                  | Version                                                                                                                   | GTIN (EAN) | Qty. |
|---------------------|----------------------------|---------------------------------------------------------------------------------------------------------------------------|------------|------|
| WS 12/5 MC<br>NE WS | <a href="#">1609860000</a> | WS, Terminal marker, 12 x 4008190203481 720 pc(s).<br>5 mm, Pitch in mm (P): 5.00<br>Weidmueller, Allen-Bradley,<br>White |            |      |

**W-Series**  
**WDU 2.5 SW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Accessories**
**End plates**

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

| Type                          | Order No.                  | Version                                  | GTIN (EAN)             | Qty. |
|-------------------------------|----------------------------|------------------------------------------|------------------------|------|
| WAP 16+35<br>WTW 2.5-10       | <a href="#">1050100000</a> | W-Series, End plate,<br>Seperation plate | 400819007990120 pc(s). |      |
| WAP 2.5-10                    | <a href="#">1050000000</a> | W-Series, End plate                      | 400819010314950 pc(s). |      |
| WAP 2.5-10<br>BL              | <a href="#">1050080000</a> | W-Series, End plate                      | 400819013661150 pc(s). |      |
| WAP 16+35<br>WTW 2.5-10<br>BL | <a href="#">1050180000</a> | W-Series, End plate,<br>Seperation plate | 400819001389920 pc(s). |      |

**Test adapter**

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

| Type                  | Order No.                  | Version                | GTIN (EAN)             | Qty. |
|-----------------------|----------------------------|------------------------|------------------------|------|
| WTA 2/ZA<br>WDU2.5-10 | <a href="#">1632330000</a> | W-Series, Test adapter | 400819025733025 pc(s). |      |
| WTA 2<br>WDU2.5-10    | <a href="#">1632320000</a> | W-Series, Test adapter | 400819025734725 pc(s). |      |

## W-Series WDU 2.5 SW

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmüller.com

## Accessories

### ZGB pivotable group tag holder



The ZGB 15 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 15.

The ZGB 30 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 7.

Inlay tags and protective strips can be found under "Accessories".

### General ordering data

| Type   | Order No.                  | Version                                                                   | GTIN (EAN)    | Qty.      |
|--------|----------------------------|---------------------------------------------------------------------------|---------------|-----------|
| ZGB 15 | <a href="#">1636530000</a> | Terminal markers, Terminal marker, 15 x 7 mm, Pitch in mm (P): 5.00 White | 4008190297053 | 20 pc(s). |
| ZGB 30 | <a href="#">1611930000</a> | Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 5.00 White | 4008190002251 | 20 pc(s). |

### WQV 2.5



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### General ordering data

| Type       | Order No.                  | Version                                                        | GTIN (EAN)    | Qty.      |
|------------|----------------------------|----------------------------------------------------------------|---------------|-----------|
| WQV 2.5/3  | <a href="#">1053760000</a> | W-Series, Cross-connector, For the terminals, No. of poles: 3  | 4008190058999 | 50 pc(s). |
| WQV 2.5/4  | <a href="#">1053860000</a> | W-Series, Cross-connector, For the terminals, No. of poles: 4  | 4008190049706 | 50 pc(s). |
| WQV 2.5/10 | <a href="#">1054460000</a> | W-Series, Cross-connector, For the terminals, No. of poles: 10 | 4008190135089 | 20 pc(s). |
| WQV 2.5/2  | <a href="#">1053660000</a> | W-Series, Cross-connector, For the terminals, No. of poles: 2  | 4008190031121 | 50 pc(s). |

## W-Series WDU 2.5 SW

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

## Accessories

### End brackets




#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### General ordering data

| Type     | Order No.                  | Version               | GTIN (EAN)    | Qty.       |
|----------|----------------------------|-----------------------|---------------|------------|
| WEW 35/2 | <a href="#">1061200000</a> | W-Series, End bracket | 4008190030230 | 100 pc(s). |

### SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw.

The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

SchT 9/4 and SchT 14/6 are hinged group tag carriers for single dekafix and WS tags that enable easy access to the clamping screw.

SchT 9/4 and SchT 14/6 are fitted with WS or DEK.

Inlay tags and protective strips can be found under "Accessories".

### General ordering data

| Delivery status                                         | Available until            | Type                                                            | Order No.                  | Version                                                         | GTIN (EAN)    | Qty.      |
|---------------------------------------------------------|----------------------------|-----------------------------------------------------------------|----------------------------|-----------------------------------------------------------------|---------------|-----------|
| Discontinued                                            | 2015-07-31T00:00:00+02:00  | SCHT 9/4                                                        | <a href="#">1278460000</a> | SCHT, Terminal marker, 32 x 4 mm, Pitch in mm (P): 5.00 Beige   | 4008190086930 | 20 pc(s). |
| This article will no longer be available in the future. | 2017-06-30T00:00:00+02:00  | SCHT 14/6                                                       | <a href="#">1269060000</a> | SCHT, Terminal marker, 44.3 x 6 mm, Pitch in mm (P): 6.00 Beige | 4008190051396 | 20 pc(s). |
| SCHT 7                                                  | <a href="#">0517960000</a> | SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00 White | 4008190001742              | 20 pc(s).                                                       |               |           |

**W-Series**  
**WDU 2.5 SW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Accessories**
**Partition plates**

**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

| Type   | Order No.                  | Version                    | GTIN (EAN)    | Qty.      |
|--------|----------------------------|----------------------------|---------------|-----------|
| WTW EN | <a href="#">1058800000</a> | W-Series, Separation plate | 4008190140175 | 20 pc(s). |

**ZQV 2.5N**
**Spring connection with tension clamp Technology**

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

**General ordering data**

| Type              | Order No.                  | Version                            | GTIN (EAN)    | Qty.      |
|-------------------|----------------------------|------------------------------------|---------------|-----------|
| ZQV 2.5N/4<br>GE  | <a href="#">1693820000</a> | Z-series, Cross-connector,<br>24 A | 4008190883652 | 60 pc(s). |
| ZQV 2.5N/2<br>GE  | <a href="#">1693800000</a> | Z-series, Cross-connector,<br>24 A | 4008190883621 | 60 pc(s). |
| ZQV 2.5N/20<br>GE | <a href="#">1909000000</a> | Z-series, Cross-connector,<br>24 A | 4032248535613 | 20 pc(s). |
| ZQV 2.5N/10<br>GE | <a href="#">1693880000</a> | Z-series, Cross-connector,<br>24 A | 4008190883720 | 20 pc(s). |
| ZQV 2.5N/3<br>GE  | <a href="#">1693810000</a> | Z-series, Cross-connector,<br>24 A | 4008190883645 | 60 pc(s). |

**W-Series**  
**WDU 2.5 SW**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 1429-0  
 Fax: +49 5231 14292083  
 www.weidmueller.com

**Accessories**
**DEK 5/5**

**WS/ DEK**

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

**Your benefits with MultiMark**

- Compatible with W, Z, P and SAK series terminal blocks
- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Space for multi-line printing

**General ordering data**

| Type       | Order No.                  | Version                         | GTIN (EAN)    | Qty.       |
|------------|----------------------------|---------------------------------|---------------|------------|
| DEK 5/5 MM | <a href="#">2007110000</a> | Dekafix, Terminal marker,       | 4050118391862 | 800 pc(s). |
| WS         |                            | 5 x 5 mm, Weidmueller,<br>White |               |            |