



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

8X3 MTE RCPT SR LATCH .100CL

[AMPMODU](#) | [AMPMODU MTE](#)

103958-2

TE Internal Number: 103958-2

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Centerline **2.54 mm [.1 in]**

Number of Positions **3**

Number of Rows **1**

Row-to-Row Spacing **2.54 mm [.1 in]**

Mating Retention **With**

Product Drawings

[RCPT ASSY, AMPMODU MTE, SINGLE ROW, .100 C/L, LATCHED & POLARIZED, FOR NO 22-NO 26 AWG WIRE SIZE, STRIP FORM](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[AMPMODU_MTE_INTERCONNECT_SYSTEM_QRG_4-1773458-0](#)

PDF
English

Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[8X3 MTE RCPT SR LATCH .100CL](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[AMPMODU MTE CONNECTORS](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Row-to-Row Spacing	2.54 mm [.1 in]
	Glow Wire Rating	Standard Part - Not Glow Wire
	Applied Pressure	Standard
	Connector Type	Housing
	Applies To	Wire/Cable
	Connector Style	Receptacle
	Strain Relief	With
	Product Type	Connector
Configuration Features	Number of Positions	3
	Number of Rows	1
Electrical Characteristics	Dielectric Withstanding Voltage	600 VAC
	Operating Voltage	267 V
	Termination Resistance	15 mΩ
	Insulation Resistance (MΩ)	5000
Contact Features	Contact Type	Socket
	Solder Tail Contact Plating Material Finish	Bright
	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin-Lead
	Contact Current Rating (A)	3
	Contact Layout	Inline
Termination Features	Termination Method to Wire/Cable	Crimp, Insulation Displacement Crimp (IDC)
Mechanical Attachment	Mating Retention	With
	Mating Retention Type	Latch
	PCB Mount Retention	Without
	Mating Connector Lock	With
	Panel Mount Retention	Without
	Mating Connector Lock Type	Latch

	Mating Alignment	With
	Lock Type	Latch
	Mating Alignment Type	Latch
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	Thermoplastic
Dimensions	Height	5.08 mm [.2 in]
	Insulation Diameter	1.37 mm [.054 in]
	Length	60.96 mm [2.4 in]
	Wire/Cable Size (AWG)	26 – 22
	Wire/Cable Size (mm²)	.12 – .4
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Operation/Application	For Use With	Mates with Headers
Industry Standards	Approved Standards	CSA LR7189, UL E28476
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	72
	Packaging Method	Tube
Other	Comment	Maximum insulation diameter is 1.14 [.045] for Pneumatic Terminators., Ribbon Cable Notched handles 22-28 AWG
Product Compliance	Statement of Compliance	
	PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

RECTANGULAR POWER CONNECTORS



05P UMNL PIN HDR ASSY 94VO LF

WIRE-TO-BOARD HEADERS & RECEPTACLES



MINI DRAWER CONN FOR CT 22P

RIBBON CABLE CONNECTORS



A/L UNIV HDR 44P VERT 1-5102153-3

RECTANGULAR POWER CONNECTORS



08P UMNL HDR ASSY R/A 94VO LF

640900-3



Save to List



Find Similar Products

5-292178-1



Save to List



Find Similar Products



Save to List



Find Similar Products

640584-3



Save to List



Find Similar Products