


Technical Data Sheet		Rosenberger																																							
BNC 75 Ω	STRAIGHT PLUG	71S106-009N5																																							
 All dimensions are in mm; tolerances according to ISO 2768 m-H <table><tr><th colspan="2">Interface</th></tr><tr><td>Compatible to</td><td>IEC 61169-8, MIL-PRF-39012, CECC 22120</td></tr><tr><th colspan="2">Documents</th></tr><tr><td>Assembly instruction</td><td>51 E</td></tr><tr><th colspan="3">Material and plating</th></tr><tr><th colspan="2">Connector parts</th><th>Material</th><th>Plating</th></tr><tr><td>Center contact</td><td></td><td>Brass</td><td>AuroDur®, gold plated</td></tr><tr><td>Outer contact</td><td></td><td>Brass</td><td>Flash white bronze over silver(e.g. Optargen®)</td></tr><tr><td>Body</td><td></td><td>Brass</td><td>Flash white bronze over silver(e.g. Optargen®)</td></tr><tr><td>Dielectric</td><td></td><td>PTFE</td><td></td></tr><tr><td>Gasket</td><td></td><td>NeopreneCR 50C6</td><td></td></tr><tr><td>Gasket</td><td></td><td>Silicone</td><td></td></tr></table>			Interface		Compatible to	IEC 61169-8, MIL-PRF-39012, CECC 22120	Documents		Assembly instruction	51 E	Material and plating			Connector parts		Material	Plating	Center contact		Brass	AuroDur®, gold plated	Outer contact		Brass	Flash white bronze over silver(e.g. Optargen®)	Body		Brass	Flash white bronze over silver(e.g. Optargen®)	Dielectric		PTFE		Gasket		NeopreneCR 50C6		Gasket		Silicone	
Interface																																									
Compatible to	IEC 61169-8, MIL-PRF-39012, CECC 22120																																								
Documents																																									
Assembly instruction	51 E																																								
Material and plating																																									
Connector parts		Material	Plating																																						
Center contact		Brass	AuroDur®, gold plated																																						
Outer contact		Brass	Flash white bronze over silver(e.g. Optargen®)																																						
Body		Brass	Flash white bronze over silver(e.g. Optargen®)																																						
Dielectric		PTFE																																							
Gasket		NeopreneCR 50C6																																							
Gasket		Silicone																																							
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de		Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : info@rosenberger.de	Page 1 / 2																																						

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG
RF_35/08.13/6.1

Technical Data Sheet				Rosenberger			
BNC 75 Ω		STRAIGHT PLUG		71S106-009N5			
Electrical data Impedance75 Ω FrequencyDC to 4 GHz Return loss≥ 33 dB @ DC to 1 GHz ≥ 30 dB @ 1 GHz to 2 GHz ≥ 28 dB @ 2 GHz to 4 GHz Insertion loss≤ 0.05 x √ f [GHz] dB Insulation resistance≥ 5 GΩ Center contact resistance≤ 1.5 mΩ Outer contact resistance≤ 1 mΩ Test voltage (at sea level)1500 V rms Working voltage (at sea level)400 V rms Power handling (at 20 °C, sea level, VSWR 1.0)80 W @ 2 GHz - Limitations are possible due to the used cable type - Mechanical data Mating cycles≥ 500 Center contact captivation: axial≥ 15 N Environmental data Temperature range-65 °C to +165 °C Thermal shockMIL-STD-202, Method 107, Condition B Corrosion resistanceMIL-STD-202, Method 101, Condition B VibrationMIL-STD-202, Method 204, Condition B ShockMIL-STD-202, Method 213, Condition G Moisture resistanceMIL-STD-202, Method 106 RoHScompliant Tooling N/A Suitable cables RG 59 B/U Packing Standard1 pce in bag Weight16.0 g/pce							
While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.							
Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	03.08.04	A. Gasteiger	06.08.13	c00	07-0154	J. Krautenbacher	06.08.13
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : info@rosenberger.de			Page 2 / 2