

Pro-H
CP T RM 10
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16


D-32758 Detmold

Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

www.weidmuller.com



The powerful new line of PRO-H power supplies – with ATEX and Class I Div. 2 approvals – is designed for use in Ex zones and the high-performance sector. High power reserves, a wide operating temperature range of -25 °C to +70 °C and high MTBF values (mean time between failures) of up to 1.8 million hours: these features ensure that the power supplies are suitable for all applications that require superior reliability (for example in the processing industry, power engineering, and in demanding machine construction applications).

Solutions are available to fit control voltages from 12V/24V to 48V. The product can be wired in parallel in order to increase the power capacity. A two-channel set-up with 100% load sharing can also be implemented with an optional redundancy module. This serves to increase your operational reliability. The Remote On/Off function allow you to switch the device on and off remotely. The output status can be signalled over a voltage-free relay or transistor output. The devices are equipped with pluggable connection terminals which allow them to be easily tested.

Product solutions can be custom-fit for use in different types of one-phase, and three-phase systems.

General ordering data

Delivery status	This article will no longer be available in the future.
Available until	2019-06-30
Type	CP T RM 10
Order No.	1105880000
Version	Power supply, switch-mode power supply unit
GTIN (EAN)	4032248881253
Qty.	1 pc(s).
Alternative product	2486090000

Pro-H
CPT RM 10
Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 1429-0

Fax: +49 5231 14292083

www.weidmueller.com

Technical data
Dimensions and weights

Width	35 mm	Width (inches)	1.378 inch
Height	110 mm	Height (inches)	4.331 inch
Depth	110 mm	Depth (inches)	4.331 inch
Net weight	467 g		

Temperatures

Humidity	0...95 % (no condensation)	Operating temperature	-25 °C...70 °C
Storage temperature	-25 °C...85 °C		

Input

Rated input voltage	24 V DC
---------------------	---------

output

Connection system	Screw connection	Output voltage	24...28 V (adjustable via potentiometer on front)
Output voltage type	DC	Rated (nominal) output current @ U_{Nom}	15 A @ 40 °C
Rated output voltage	24 V DC $\pm$ 1 %	Residual ripple, breaking spikes	100 mV _{pp} @ 24 V DC, I_{nenn}

General data

Housing version	Metal, corrosion resistant	Humidity	0...95 % (no condensation)
Operating temperature	-25 °C...70 °C	Protection degree	IP20

Insulation coordination

Class of protection	I, with PE connection	Pollution severity	2
---------------------	-----------------------	--------------------	---

Connection data (input)

Conductor cross-section, AWG/kcmil , max.	10	Conductor cross-section, AWG/kcmil , min.	18
Conductor cross-section, flexible , min.	1 mm ²	Conductor cross-section, rigid , max.	4 mm ²
Conductor cross-section, rigid , min.	1 mm ²	Number of terminals	4 (++-)
Tightening torque, max.	0.6 Nm	Tightening torque, min.	0.5 Nm
Wire connection cross section, flexible (input), max.	4 mm ²		

Connection data (output)

Conductor cross-section, AWG/kcmil , max.	10	Conductor cross-section, AWG/kcmil , min.	12
Conductor cross-section, flexible , max.	4 mm ²	Conductor cross-section, flexible , min.	2.5 mm ²
Conductor cross-section, rigid , max.	4 mm ²	Conductor cross-section, rigid , min.	2.5 mm ²
Connection system	Screw connection	Number of terminals	4 (++ / -)
Tightening torque, max.	0.6 Nm	Tightening torque, min.	0.5 Nm

Connection data (signal)

Wire connection method	Screw connection	Wire cross-section, AWG/kcmil , max.	12
Wire cross-section, AWG/kcmil , min.	32	Wire cross-section, solid , max.	2.5 mm ²
Wire cross-section, solid , min.	0.2 mm ²		

**Pro-H
CPT RM 10**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data**Approvals**

Institute (CSA)



Certificate No. (CSA)

246286-2148800

Institute (cURus)



Certificate No. (cURus)

E258476

Classifications

ETIM 4.0	EC002541	ETIM 5.0	EC002541
ETIM 6.0	EC002850	eClass 6.2	27-04-90-04
eClass 7.1	27-04-90-04	eClass 8.1	27-04-90-04
eClass 9.0	27-04-07-03	eClass 9.1	27-04-92-90

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	DE_PA5200_160422_002.pdf
Brochure/Catalogue	CAT 4.3 ELECTR 15/16 EN
Engineering Data	EPLAN, WSCAD
User Documentation	Information zur Gewährleistung