

STANDARD RECTANGULAR CONNECTORS



✓ Active

[PRODUCT DRAWING](#)

English

[3D PDF](#)

TE CONNECTIVITY (TE) DYNAMIC S/ROW HDR 5P V ASSY

Dynamic Series | Dynamic 3000 Series

1-178315-3

TE Internal Number: 1-178315-3

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type **Polarization**

Mating Retention **With**

Mating Retention Type **Latch**

Product Drawings

5 POS SINGLE ROW VERTICAL HDR ASS'Y FOR DYNAMIC D-3100

PDF ([TIFF AVAILABLE](#))

English

5 POS SINGLE ROW VERTICAL HDR ASS'Y FOR DYNAMIC D-3100

PDF ([TIFF AVAILABLE](#))

English

CAD Files

Customer View Model

3D_IGS.ZIP

English

3D PDF

PDF

English

Customer View Model

3D_STP.ZIP

English

Customer View Model

2D_DXF.ZIP

English

Catalog Pages/Data Sheets

D3000 Series Dynamic Connectors

PDF

English

1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH

PDF

English

Product Specifications

Product Specification

Dynamic Connector D-3000 Series

TIF

Japanese

Dynamic Connector D-3000 Series

PDF

Japanese

DYNAMIC D-3000 SERIES CONNECTOR

PDF

Japanese

Qualification Test Report

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Connector
	PCB Mounting Orientation	Vertical
	Sealed	No
	Connector System	Wire-to-Board
	Shielded	No
	Insertion Force	Standard
	Connector Style	Plug
	Glow Wire Rating	Standard Part - Not Glow Wire
	Strain Relief	Without
	Series Number	3000
	Shrouded	Yes
	Connector Type	Header
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	5
	Number of Rows	1
	Preloaded	Yes
	Selectively Loaded	No
Electrical Characteristics	Operating Voltage	250 VAC [250 VDC]
	UL Voltage Rating	250 VAC [250 VDC]
Body Features	Header Type	Shrouded
	Sealable	No
Contact Features	Contact Plating Material	Gold
	Contact Current Rating (A)	15
	Tail Plating Thickness	2 μm [78.74 μin]
	Multiple Contact Types	Without
	Contact Style	Straight
	Contact Type	Tab
	Tail Plating Material	Tin
	Contact Transmits (Typical)	Power, Signal (Data)

Termination Features	Termination Method to PC Board	Through Hole - Solder
Mechanical Attachment	Mating Alignment	With
	Mating Alignment Type	Polarization
	Mating Retention	With
	Mating Retention Type	Latch
	PCB Mount Retention	With
	PCB Mount Retention Type	Retention Leg
	Contact Retention	Without
	PCB Mount Alignment	Without
	Lock Type	Latch
Housing Features	Centerline	3.81 mm [.149 in]
	Housing Material	Polyester GF
	Housing Color	Black
Dimensions	PCB Thickness (Recommended)	1.6 mm [.063 in]
	Tail Length	3.8 mm [.149 in]
	Height	21.6 mm [.85 in]
	Width	9.35 mm [.368 in]
	Length	29.24 mm [1.15 in]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	For Use With	Receptacle Housing
	Assembly Integration Feature	Without
	Halogen Free	Yes
Industry Standards	UL Flammability Rating	UL 94V-0
	CSA File Number	LR7189
	VDE Tested	No
	CSA Rating	Certified
	UL Rating	Recognized

Agency/Standard

CSA, UL

UL File Number

E28476

Packaging Features	Packaging Quantity	17
	Packaging Method	Tube, Tube/Box
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

STANDARD RECTANGULAR CONNECTORS	STANDARD RECTANGULAR CONNECTORS	STANDARD RECTANGULAR CONNECTORS	STANDARD RECTANGULAR CONNECTORS
			
DYNAMIC 3200 HDR H 3P ASSY 1-178138-3	6-P POST HDR D-3100D VERT .76 178323-3	DYNAMIC S/ROW HDR 8P V ASSY 1-178317-3	DYNAMIC 3100 HDR ASSY 6P V K/X 1-178316-3
 Save to List	 Save to List	 Save to List	 Save to List
 Find Similar Products	 Find Similar Products	 Find Similar Products	 Find Similar Products