

REV.			DATE			DESCRIPTION		
A			04/31/03			UPDATE DRAWING FORMAT		
B			03/01/04			MODIFY DESCRIPTION - RG-179/U		

RECOMMENDED
CABLE STRIPPING DIM'S

2.70 [.106]
1.70 [.067]
4.16 [.164]
8.60 [.339]
6.10 [.240]
4.40 [.173]
2.00 [.079]
5.00 [.197] SQ.
2.40 [.094]
2.80 [.110]
.80 [.032]
4.05 [.160]
9.52 [.375]

NOTE:

- CRIMPED FERRULE
HEX CRIMP SIZE .151"
- CONTACT PIN TO SOLDER

8													
7													
6	FERRULE	COPPER	GOLD	1									
5	COVER	BRASS	GOLD	1									
4	INSULATOR	DELRIIN	NATURAL	1									
3	CONTACT PIN	BRASS	GOLD	1									
2	INSULATOR	TEFLON	NATURAL	1									
1	BODY	BRASS	GOLD	1									
DESCRIPTION		MATERIAL	FINISH	QTY	DO NOT SCALE DRAWING		CAD FILE	C:/252/252119-75.DWG	DWG. NO.	252119-75.DWG	REV. B	SIZE A	SCALE NA

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:

0.5 - 8mm ± 0.20mm

8 - 30mm ± 0.40mm

30 - 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:

.020 - .315 = ± 0.007"

.315 - 1.180 = ± 0.015"

1.180 - 4.724 = ± 0.020"

APPROVALS

DRAWN G.R.S.

CHECKED

ISSUED

SHEET 1 OF 1

PART NO.

252119-75

MCX R/A CRIMP PLUG
(FOR RG-179/U DOUBLE BRAID)

Amphenol Connex