

## DIN rail perforated - NS 35/ 7,5 PERF 755MM - 1207640

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail, material: steel galvanized and passivated with a thick layer, perforated, height 7.5 mm, width 35 mm, length: 755 mm

### Why buy this product



### Key commercial data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 10 pc                                                                                                   |
| Minimum order quantity               | 10 pc                                                                                                   |
| GTIN                                 | <br>4 017918 932640 |
| Weight per Piece (excluding packing) | 240.0 g                                                                                                 |
| Custom tariff number                 | 72166190                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|        |        |
|--------|--------|
| Height | 7.5 mm |
| Length | 755 mm |
| Width  | 35 mm  |

#### General

|                       |                                           |
|-----------------------|-------------------------------------------|
| Material              | Steel                                     |
| Coating               | Galvanized, passivated with a thick layer |
| Color                 | silver                                    |
| Test standard         | In acc. with EN 60715: 2001               |
| Nominal current $I_N$ | 1920 A                                    |

## DIN rail perforated - NS 35/ 7,5 PERF 755MM - 1207640

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 23150301 |
| eCl@ss 4.1 | 23150301 |
| eCl@ss 5.0 | 27141143 |
| eCl@ss 5.1 | 27141143 |
| eCl@ss 6.0 | 27141143 |
| eCl@ss 7.0 | 27141143 |
| eCl@ss 8.0 | 27400602 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001285 |
| ETIM 3.0 | EC001285 |
| ETIM 4.0 | EC000212 |
| ETIM 5.0 | EC000212 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212109 |
| UNSPSC 7.0901 | 39121708 |
| UNSPSC 11     | 39121708 |
| UNSPSC 12.01  | 39121708 |
| UNSPSC 13.2   | 39121708 |

### Drawings

## DIN rail perforated - NS 35/ 7,5 PERF 755MM - 1207640

Dimensional drawing

