


Non-Insulated Wire Ferrules DIN 46228 Part 1



			Dimensions (mm)				Recommended Crimping Tools	
Size mm2	AWG	Part Number	Pieces per bag	L	D-1	D-2	S	
0.25	24	12510025 12710025	1000 1000	5 7	0.8	1.7 1.7	0.15 0.15	SQ28-10 or TRAP24-10
0.34	22	12510034 12710034	1000	5 7	0.9	1.8 1.8	0.15 0.15	
0.5	20	12610050 12810050 121010050	1000 1000 1000	6 8 10	1 1 1	2.1 2.1 2.1	0.15 0.15 0.15	
0.75	20	12610050 12610075 12810075	1000	6 8	1.2	2.3	0.15 0.15 0.15	
		121010075 121210075	1000 1000	10 12	1.2	2.3	0.15 0.15	
1	18	12610100 12810100 121010100 121210100	1000 1000 1000 1000	6 8 10 12	1.4 1.4 1.4 1.4	2.52.52.52.5	0.15 0.15 0.15 0.15	
1.5	16	12710150 121010150 121210150 121510150 121810150 122010150	1000 1000 1000 1000 1000	7 10 12 15 18 20	1.7 1.7 1.7 1.7 1.7	2.8 2.8 2.8 2.8 2.8 2.8	0.15 0.15 0.15 0.15 0.15 0.15	
2.5	14	12710250	1000	7	2.2	3.4	0.15	

				D	imensio	Recommended Crimping Tools		
Size mm2	AWG	Part Number	Pieces per bag	L	D-1	D-2	S	
10	8	1212110	500	12	4.5	5.8	0.2	TRAP8-1 or
		1215110	500	15	4.5	5.8	0.2	TRAP8-4
		1218110	500	18	4.5	5.8	0.2	
		1220110	500	20	4.5	5.8	0.2	
		1225110	500	25	4.5	5.8	0.2	
16	6	1212116	250	12	5.8	7.5	0.2	
		1215116	250	15	5.8	7.5	0.2	
		1218116	250	18	5.8	7.5	0.2	
		1220116	250	20	5.8	7.5	0.2	
		1225116	250	25	5.8	7.5	0.2	
		1232116	250	32	5.8	7.5	0.2	
25	4	1212125	100	12	7.3	9.5	0.2	
		1215125	100	15	7.3	9.5	0.2	
		1218125	100	18	7.3	9.5	0.2	
		1225125	100	25	7.3	9.5	0.2	
		1232125	100	32	7.3	9.5	0.2	
35	2	1218135	100	18	8.3	11	0.2	TRAP8-1
		1220135	100	20	8.3	11	0.2	
		1225135 1232135	100 100	25 32	8.3 8.3	11 11	0.2	
50	1	1218150	100	18	10.3	13	0.3	
		1222150	100	22	10.3	13	0.3	

		121010250	1000	10	2.2	3.4	0.15
		121210250	1000	12	2.2	3.4	0.15
		121510250	1000	15	2.2	3.4	0.15
		121810250	1000	18	2.2	3.4	0.15
		122010250	1000	20	2.2	3.4	0.15
4	12	12910400	1000	9	2.8	4	0.2
		121010400	1000	10	2.8	4	0.2
		121210400	1000	12	2.8	4	0.2
		121510400	1000	15	2.8	4	0.2
		121810400	1000	18	2.8	4	0.2
		122010400	1000	20	2.8	4	0.2
6	10	121010600	1000	10	3.5	4.7	0.2
		121210600	1000	12	3.5	4.7	0.2
		121210600	1000	12	3.5	4.7	0.2
		121510600	1000	15	3.5	4.7	0.2

		1225150	100	25	10.3	13	0.3	
		1232150	100	32	10.3	13	0.3	
70	2/0	1225170	100	25	12.5	15	0.4	VICE70150
		1232170	100	32	12.5	15	0.4	
95	3/0	1225195	100	25	14.5	17	0.4	
		1230195	100	30	14.5	17	0.4	
		1232195	100	32	14.5	17	0.4	
120	4/0	12321120	100	32	16.5	19	0.5	
		12401120	100	40	16.5	19	0.5	
150	300 MCM	123211500	100	32	18.5	21	0.5	
		123811500	100	38	18.5	21	0.5	
185	350 MCM	123211850	100	32	20	23.5	0.6	
		124011850	100	40	20	23.5	0.6	