

Tool - SAC BIT HOOD-W 24 - 1212486


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Nut for assembling pressure nuts with 24 mm wrench size, for 4 mm hexagonal drive



RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 478502
GTIN	4046356478502
Weight per Piece (excluding packing)	40.000 g
Custom tariff number	82079030
Country of origin	Germany

Technical data

Dimensions

Length (b)	41.5 mm
Width (a)	31.5 mm
Height	6 mm

General

Base element material	Steel
Coating	nickel-plated

Classifications

eCl@ss

eCl@ss 4.0	21043074
------------	----------

Tool - SAC BIT HOOD-W 24 - 1212486

Classifications

eCl@ss

eCl@ss 4.1	21043074
eCl@ss 5.0	21040290
eCl@ss 5.1	21040290
eCl@ss 6.0	21040290
eCl@ss 7.0	21040290
eCl@ss 8.0	21045003
eCl@ss 9.0	21044290

ETIM

ETIM 3.0	EC000149
ETIM 4.0	EC000149
ETIM 5.0	EC000149
ETIM 6.0	EC000149

UNSPSC

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27113201

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
-----	---	---------------

Tool - SAC BIT HOOD-W 24 - 1212486

Accessories

Additional products

Torque screwdriver - TSD 25 SAC - 1212315



Torque screwdriver, with preset torque of 2.5 Nm and 4 mm hexagonal drive for the pressure nut of the connector hood

Torque screwdriver - TSD-M 3NM - 1212225



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 1.2 - 3 Nm

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits