

1213F Multi-Conductor - Enhanced Category 5e Nonbonded-Pair Cable



For more Information
please call

1-800-Belden1

**Description:**

24 AWG solid bare copper conductors, plenum, FEP Teflon® insulation, twisted pairs, overall Beldfoil® shield, drain wire, RJ-45 compatible, see color code chart (below), Flamarrest® jacket (red, orange, yellow, green, blue, gray or natural).

Usage (Overall)**Suitable Applications:**

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG
 ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video,
 AES/EBU, Digital Video, RS-422, Noisy Environments, 100MHz Category 5e

Physical Characteristics (Overall)**Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material
4	24	Solid	BC - Bare Copper

Total Number of Conductors:

8

Insulation**Insulation Material:**

Insulation Material
FEP - Fluorinated Ethylene Propylene

Outer Shield**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

Outer Jacket**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride

Overall Cable**Overall Nominal Diameter:**

0.235 in.

Pair**Pair Color Code Chart:**

Number	Color
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Mechanical Characteristics (Overall)**Operating Temperature Range:**

0°C To +75°C

Bulk Cable Weight:

34 lbs/1000 ft.

1213F Multi-Conductor - Enhanced Category 5e Nonbonded-Pair Cable

Max. Recommended Pulling Tension:	25 lbs.
Min. Bend Radius/Minor Axis:	1 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

CEC/C(UL) Specification:	CMP
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	12/09/2011
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	NEMA WC-63.1 Category 5e, UL Verified to Category 5e

Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	1212F

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/ft)
15

Maximum Capacitance Unbalance (pF/100 m):	330
---	-----

Nominal Velocity of Propagation:

VP (%)
70

Maximum Delay:

Delay (ns/100 m)
538 @ 100MHz

Max. Delay Skew:

Delay Skew (ns/100 m)
45

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
9.38

Max. Operating Voltage - UL:

Voltage
300 V RMS

Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)
3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min RL (dB)	Min. SRL (dB)
-------------	-----------------------------	----------------	------------------	---------------	-----------------	-------------	---------------

1213F Multi-Conductor - Enhanced Category 5e Nonbonded-Pair Cable

.772	1.800	72.0	70	72.2	68.2	19.400	
1	2.000	70.3	68.3	70.3	66.3	20.000	23.0
4	4.000	61.3	59.3	59.3	55.3	23.000	23.0
8	5.700	56.8	54.8	53.1	49.1	24.500	24.5
10	6.400	55.3	53.3	50.9	46.9	25.000	25.0
16	8.100	52.2	50.2	46.1	42.1	25.000	25.0
20	9.100	50.8	48.8	43.7	39.7	25.000	25.0
25	10.200	49.3	47.3	41.1	37.1	24.300	24.3
31.25	11.400	47.9	45.9	38.5	34.5	23.600	23.6
62.5	16.400	43.4	41.4	29.0	25.0	21.500	21.5
100	21.000	40.3	38.3	21.3	17.3	20.100	20.1
155	26.600	37.4	35.4	12.8	8.9	18.800	
200	30.500	35.8	33.8	7.3	3.3	18.000	
250	34.400	34.3	32.3	1.9		17.300	
300	38.000	33.1	28.2			16.800	
350	41.400	32.1	27.2			16.300	
400	44.500	31.3	26.3			15.900	
450	47.600	30.5	25.6			15.500	

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	67.8	64.8
4	100 ± 15	100 ± 15	55.8	52.8
8	100 ± 15	100 ± 15	49.7	46.7
10	100 ± 15	100 ± 15	47.8	44.8
16	100 ± 15	100 ± 15	43.7	40.7
20	100 ± 15	100 ± 15	41.8	38.8
25	100 ± 15	100 ± 15	39.8	36.8
31.25	100 ± 15	100 ± 15	37.9	34.9
62.5	100 ± 15	100 ± 15	31.9	28.9
100	100 ± 15	100 ± 15	27.8	24.8
155	100 ± 22	100 ± 15	24.0	21.0
200	100 ± 22	100 ± 15	21.8	18.8
250	100 ± 32	100 ± 15	19.8	16.8
300	100 ± 32	100 ± 15	18.2	15.2
350	100 ± 32	100 ± 15	16.9	13.9

Notes (Overall)

Notes: Shield is bonded to jacket inner wall for electrical stability. RJ-45 Compatible. Jacket sequentially marked at 2 ft. intervals.
 Third party verified to TIA/EIA-568-B.2, Category 5e.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1213F D15A1000	1,000 FT	36.000 LB	BLUE		CAT5E+ 4PR F/UTP CMP RIB
1213F D15I1000	1,000 FT	32.000 LB	BLUE		CAT5E+ 4PR F/UTP CMP REEL
1213F D15500	500 FT	17.500 LB	BLUE		CAT5E+ 4PR F/UTP CMP REEL
1213F 002A1000	1,000 FT	36.000 LB	RED		CAT5E+ 4PR F/UTP CMP RIB
1213F 002I1000	1,000 FT	32.000 LB	RED		CAT5E+ 4PR F/UTP CMP REEL
1213F 003A1000	1,000 FT	36.000 LB	ORANGE		CAT5E+ 4PR F/UTP CMP RIB
1213F 003I1000	1,000 FT	32.000 LB	ORANGE		CAT5E+ 4PR F/UTP CMP REEL
1213F 004A1000	1,000 FT	36.000 LB	YELLOW		CAT5E+ 4PR F/UTP CMP RIB
1213F 004I1000	1,000 FT	32.000 LB	YELLOW		CAT5E+ 4PR F/UTP CMP REEL
1213F 005A1000	1,000 FT	36.000 LB	GREEN, DARK		CAT5E+ 4PR F/UTP CMP RIB
1213F 005I1000	1,000 FT	32.000 LB	GREEN, DARK		CAT5E+ 4PR F/UTP CMP REEL
1213F 008A1000	1,000 FT	36.000 LB	GRAY		CAT5E+ 4PR F/UTP CMP RIB
1213F 008I1000	1,000 FT	32.000 LB	GRAY		CAT5E+ 4PR F/UTP CMP REEL
1213F 009A1000	1,000 FT	36.000 LB	WHITE		CAT5E+ 4PR F/UTP CMP RIB
1213F 009I1000	1,000 FT	32.000 LB	WHITE		CAT5E+ 4PR F/UTP CMP REEL
1213F 010A1000	1,000 FT	36.000 LB	BLACK		CAT5E+ 4PR F/UTP CMP RIB
1213F 010I1000	1,000 FT	32.000 LB	BLACK		CAT5E+ 4PR F/UTP CMP REEL

1213F Multi-Conductor - Enhanced Category 5e Nonbonded-Pair Cable

Revision Number: 1 Revision Date: 10-01-2012

© 2012 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.