


SPECIFICATIONS							
CONTACT CARRIER MATERIAL	NYLON						
MOLDED MATERIAL/COLOR	POLYAMIDE/BLACK						
CONTACT MATERIAL/PLATING	BRASS/GOLD						
COUPLING NUT MATERIAL/PLATING	ZINC/NICKEL						
RATED CURRENT [A]	35.0 A (8 AWG)						
RATED VOLTAGE [V]	600 V (8 AWG)						
CABLE JACKET MATERIAL/COLOR	TPE/BLACK						
CONDUCTOR INSULATION MATERIAL	PVC/NYLON						
NUMBERS OF CONDUCTORS [AWG]	4x8 AWG						
TEMPERATURE RATING	-40°C to +90°C (-40°F to +194°F)						
PROTECTION CLASS	MEETS IEC IP67						
APPROVALS AND CERTIFICATIONS	UL 2237						



CABLE LENGTH	TOLERANCE*					
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER					
STRIP LENGTH	TOLERANCE *					
0-7mm	±0.5mm					
8-29mm	±1.0mm					
30-49mm	±2.0mm					
50-69mm	±3.0mm					
70-100mm	±4.0mm					
OVER 100mm	±5.0mm					
* UNLESS OTHERWISE SPECIFIED						

NOTES:

REV DESCRIPTION

1. "*" INDICATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.

TV 06/15/16

UPDATED MATERIAL INSULATION PER ECO

CAUTION: RISK OF ELECTRICAL SHOCK DO NOT DISCONNECT UNDER LOAD

SOURCE DRAWING - FOR REFERENCE ONLY

		1. 2. 3. 4.		3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.		MINNEAPOLIS, 1 1–800–544 (763) 553- (763) 553- turck.cc					55441 769 300 708 fax
		MATERIAL		ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY	DRFT	RDS	DATE 08/14/13	DESCRIPTION HSM HKM 4800-1279-			70 *	
CIFIC	SEE SPECIFICATIONS	APVD	J.B.		SCALE 1=2.7	ПЭМ	+000-12,	00-12/9-*				
					UNIT OF MEASUREMENT		EASUREMENT	IDENTIFICATION NO.				
		FINISH CONTACT TURCK			MILLIMETER [INCH]			IDENTIFICATION NO.				
55	092	SEE	SPECIFICATIONS	FOR MORE INFORMATION			-					
ECC	NO.				DO NOT SCALE THIS DRAWING			FILE: 777032149	9		SHEET	1 OF 1