

## 9497 Multi-Conductor - High-Conductivity Copper Speaker Cable Open Twisted Const

For more Information  
please call

1-800-Belden1

**General Description:**

16 AWG stranded (19x29) ETP high-conductivity tinned copper conductors, PVC insulation, cabled.

**Physical Characteristics (Overall)****Conductor**

AWG:

| # Conductors | AWG | Stranding | Conductor Material                   |
|--------------|-----|-----------|--------------------------------------|
| 2            | 16  | 19x29     | High Conductivity TC - Tinned Copper |

Total Number of Conductors: 2

**Insulation**

Insulation Material:

| Insulation Material      | Wall Thickness (in.) |
|--------------------------|----------------------|
| PVC - Polyvinyl Chloride | .023                 |

Insulation Color Code Chart:

| Number | Color  |
|--------|--------|
| 1      | Black  |
| 2      | Orange |

**Outer Shield**

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded            |

**Outer Jacket**

Outer Jacket Material:

| Outer Jacket Material |
|-----------------------|
| Unjacketed            |

**Overall Cable**

Overall Nominal Diameter: 0.210 in.

**Mechanical Characteristics (Overall)**

|                                   |                          |
|-----------------------------------|--------------------------|
| Operating Temperature Range:      | -30°C To +80°C           |
| UL Temperature Rating:            | 80°C (UL AWM Style 1007) |
| Bulk Cable Weight:                | 28 lbs/1000 ft.          |
| Max. Recommended Pulling Tension: | 84 lbs.                  |
| Min. Bend Radius/Minor Axis:      | 2.250 in.                |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                    |                            |
|------------------------------------|----------------------------|
| AWM Specification:                 | UL Style 1007 (300 V 80°C) |
| EU Directive 2011/65/EU (ROHS II): | Yes                        |
| EU CE Mark:                        | Yes                        |
| EU Directive 2000/53/EC (ELV):     | Yes                        |

**9497 Multi-Conductor - High-Conductivity Copper Speaker Cable Open Twisted Const**

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire &amp; Cable): Yes

MII Order #39 (China RoHS): Yes

**Flame Test**

UL Flame Test: VW-1

**Plenum/Non-Plenum**

Plenum (Y/N): No

**Electrical Characteristics (Overall)****Nom. Inductance:**

Inductance (μH/ft)

.19

**Nom. Conductor DC Resistance:**

DCR @ 20°C (Ohm/1000 ft)

4.27

**Max. Operating Voltage - UL:**

Voltage

300 V RMS (UL AWM Style 1007)

**Max. Recommended Current:**

Current

7.1 Amps per conductor @ 25°C

**Put Ups and Colors:**

| Item #       | Putup    | Ship Weight | Color | Notes | Item Desc       |
|--------------|----------|-------------|-------|-------|-----------------|
| 9497 0001000 | 1,000 FT | 30.000 LB   | NONE  | C     | TW PR BLK & ORG |

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 08-23-2012

© 2013 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.