



✓ Active

[PRODUCT DRAWING](#)  
English

TE CONNECTIVITY (TE)

### 05P.DIP SWITCH ASSY

[Alcoswitch](#) | [SBP](#) , [Standard](#)

5161390-5

TE Internal Number: 5161390-5

[Always EU RoHS/ELV Compliant](#)

Product Type **Switch**

Contact Mating Area Plating Material **Tin**

Housing Color **Natural**

Housing Material **Nylon - GF**

Auto-Insertable **No**

#### Product Drawings

[DIP SWITCH SOLDER LEGS 3,2mm LONG](#)

PDF  
**English**

#### Catalog Pages/Data Sheets

[SWITCHES\\_CORE\\_PROGRAM\\_CATALOG](#)

PDF  
**English**

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

#### Product Type Features

Product Type	<b>Switch</b>
Sealed	<b>No</b>
Switch Type	<b>DIP</b>
Actuator Style	<b>Slide</b>

#### Configuration Features

Number of Switches	<b>5</b>
Configuration (Pole-Throw)	<b>Single Pole - Single Throw</b>
Number of Positions	<b>5</b>

#### Body Features

Actuator Color	<b>Red</b>
----------------	------------

#### Contact Features

Contact Mating Area Plating Material	<b>Tin</b>
Auto-Insertable	<b>No</b>
Contact Base Material	<b>Phosphor Bronze</b>

	Contact Mating Area Plating Thickness (µin)	98.42
	Solder Tail Contact Plating	Tin
Termination Features	Termination Post Length	3.2 mm [ .1259 in ]
Mechanical Attachment	Mounting Type	Through Hole
	Mounting Angle	Vertical
Housing Features	Housing Color	Natural
	Housing Material	Nylon - GF
	Centerline	2.54 mm [ .1 in ]
Dimensions	Length	15.24 mm [ .599 in ]
	Height	8.5 mm [ .334 in ]
Usage Conditions	Operating Temperature Range (°C)	-25 – 70
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Box/Carton
	Packaging Quantity	500
Other	Comment	Soldering in "off" position only
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	