

## **CIRCULAR POWER CONNECTORS**



✓ Active

### TE CONNECTIVITY (TE)

## LGH-4 SGL MOLDED END LEAD

LGH | LGH , SBL

#### 445058-1

TE Internal Number: 445058-1

Not Yet Reviewed for EU RoHS Not Yet Reviewed for EU ELV

Pigtail Length 9.65 mm [.38 in]

**Product Type** Lead Assembly

**Operating Voltage (VDC)** 50000

Wire/Cable Size (AWG) 16

**Contact Type** Socket



## **PRODUCT DRAWING**

± English




**→** 3D PDF

**Customer View Model** 

2D\_DXF.ZIP

**English** 



English	
Customer View Model	
3D_STP.ZIP	
English	
Product Specifications	
Product Specification	
Standard LGH Connectors, Series 1/2I, 1/2LI, 1I, 1LI, 2I, 3I And 4I	
PDF	
English	
FEATURES	+
	•
Please review product documents or contact us for the latest agency approval information.	
Please Note: Use the Product Drawing for all design activity.	
Draduct Tura Fasturas	
Product Type Features	
Product Type Lead Assembly  Contact Type Socket	
Contact Type Socket	
Electrical Characteristics	
Operating Voltage (VDC) 50000	
Body Features	
Positive Stop Ferrule Without	
Termination Features	
Wire/Cable Size (AWG) 16  Termination Method to Wire/Cable Pre-Terminated to Cable	
Termination Metriod to Vine, easie 116 ferminated to Casie	
Mechanical Attachment	
Mating Alignment Type Voyed	
Mating Alignment Type Keyed	
Dimensions	
Pigtail Length 9.65 mm [.38 in]	
Assembly Length 990.6 mm [ 39 in ]	
Usage Conditions	
Operating Temperature Range (°C) -55 – 125	
Shielded No	

**Customer View Model** 

3D\_IGS.ZIP

Packaging Features	
Packaging Quantity 1	
PRODUCT COMPLIANCE	+

Statement of Compliance

# **Statement of Compliance**

PDF