

SAC-3P-20,0-534/AD 180 BM - 1403217

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

RoHS

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	50 STK
GTIN	 4 046356 643443
GTIN	4046356643443
Weight per Piece (excluding packing)	920.000 g
Custom tariff number	85444290
Country of origin	Poland

Technical data

General

Standards/regulations	Valve connector EN 175301-803
-----------------------	-------------------------------

Standards and Regulations

Standard designation	Valve connector
Standards/regulations	EN 175301-803

Classifications

eCl@ss

eCl@ss 4.0	27060306
eCl@ss 4.1	27060306
eCl@ss 5.0	27060300
eCl@ss 5.1	27061804
eCl@ss 6.0	27061801
eCl@ss 7.0	27061801
eCl@ss 8.0	27279218
eCl@ss 9.0	27060311

SAC-3P-20,0-534/AD 180 BM - 1403217

Classifications

ETIM

ETIM 4.0	EC001855
ETIM 5.0	EC001855
ETIM 6.0	EC001855

UNSPSC

UNSPSC 6.01	31251501
UNSPSC 7.0901	31251501
UNSPSC 11	31251501
UNSPSC 12.01	31251501
UNSPSC 13.2	31251501

Approvals

Approvals

Approvals

CSAus

Ex Approvals

Approval details

CSAus		http://www.csagroup.org/services/testing-and-certification/certified-product-listing/	13631
Nominal current I _N		6 A	
Nominal voltage U _N		24 V	

Accessories

Accessories

Mounting material

SAC-3P-20,0-534/AD 180 BM - 1403217

Accessories

Screw - SAC-V-SCREW-M3-29 KNURL - 1403779



Fillister head screw with plastic knurl, M3 x 40