

QUICK DISCONNECTS



✓ Active

PRODUCT DRAWING

English

TE CONNECTIVITY (TE) TERMINAL FASTON 2,8 L P FASTON | 110

140852-2

TE Internal Number: 140852-2

Always EU RoHS/ELV Compliant

Mating Tab Width **2.79 mm [.11 in]**

Mating Tab Thickness **.79 mm [.031 in]**

Wire Insulation Diameter **1.19 – 2.49 mm [.047 – .098 in]**

Wire Size (AWG) **22 – 17**

Wire Size (mm²) **.3 – 1**

Product Drawings

.110 SERIES RECEPTACLE, FASTON

PDF

English

Product Environmental Compliance

TE Material Declaration

[MD_140852-2_122020152355_dmtec](#)

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Wire Stop	No
Disconnect Type	Quick Disconnect
Insertion Force	Normal
FASTON	Yes
Wire/Cable Composition	Stranded
Insulated	No
Support Style	Insulation Support
Applies To	Wire/Cable

Configuration Features

Terminal Angle	Straight
Connection Capacity	Single

Body Features

Plating Material	Brass, Tin
------------------	-------------------

Contact Features	Terminal Orientation	Straight
Termination Features	Crimp Type	F-Crimp
Mechanical Attachment	Mating Retention Type	Dimple
Dimensions	Mating Tab Width	2.79 mm [.11 in]
	Mating Tab Thickness	.79 mm [.031 in]
	Wire Insulation Diameter	1.19 – 2.49 mm [.047 – .098 in]
	Wire Size (AWG)	22 – 17
	Wire Size (mm ²)	.3 – 1
	Overall Length	16.1 mm [.634 in]
Industry Standards	UL Rating	Listed
	CSA Certified	Yes
Packaging Features	Packaging Method	Bag
	Packaging Quantity	500
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	
