

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON ADVANCE B10 coupling housing, for M6 screw locking, salt-water-resistant aluminum, with 1 x M20 thread, straight cable outlet, without surface coating



Key commercial data

| Packing unit | 1 pc |
|--------------------------------------|-----------------|
| GTIN | 4 046356 583398 |
| Weight per Piece (excluding packing) | 452.4 g |
| Custom tariff number | 85389099 |
| Country of origin | China |

Technical data

Dimensions

| Height | 68 mm |
|--------|--------|
| Width | 45 mm |
| Length | 105 mm |

Ambient conditions

| Degree of protection of housing (IP) | IP66 |
|----------------------------------------|-----------------------|
| | IP68 (0.2 bar/24 h) |
| | IP69K |
| Degree of protection of housing (NEMA) | 4 (UL50e / NEMA 250) |
| | 4X (UL50e / NEMA 250) |
| | 6P (UL50e / NEMA 250) |
| | 12 (UL50e / NEMA 250) |
| Ambient temperature (operation) | -40 °C 125 °C |

General

| Note | For contact inserts HC-B10, BB18, DD42, M, K8/24 |
|--------------|--------------------------------------------------|
| Туре | B10 |
| Housing type | Coupling housings |



Technical data

General

| Locking type | Screw locking |
|------------------------------|----------------------------------------|
| Fixing screws | M6 |
| No. of cable outlets | 1 |
| Cable exit | Straight |
| Screw connection | none |
| Type of the screw connection | 1x M20 |
| Housing material | Die-cast aluminum, corrosion resistant |
| Housing surface material | Uncoated |

Classifications

eCl@ss

| eCl@ss 4.0 | 27140816 |
|------------|----------|
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27261203 |
| eCl@ss 7.0 | 27440202 |
| eCl@ss 8.0 | 27440202 |

ETIM

| ETIM 4.0 | EC000437 |
|----------|----------|
| ETIM 5.0 | EC000437 |

UNSPSC

| UNSPSC 6.01 | 31261502 |
|---------------|----------|
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11 | 31261502 |
| UNSPSC 12.01 | 31261502 |
| UNSPSC 13.2 | 31261502 |

Approvals

Approvals

Approvals

EAC

Ex Approvals



Approvals

Approvals submitted

Approval details

EAC

Accessories

Accessories

Extension adapter

Extension adapter - ENLAR-M-KV-M20/M25 - 1647666



Step-up adapter, M20 to M25, including O-ring

Full screw connection

Cable gland - G-INS-M20-S68N-PNES-GY - 1411125



Cable gland, Cable gland material: Polyamide 6, External cable diameter 6 mm ... 12 mm, Shielding: No, Connecting thread: M20, Color: silver grey

Cable gland - G-INS-M20-S68N-PNES-BK - 1411133



Cable gland, Cable gland material: Polyamide 6, External cable diameter 6 mm ... 12 mm, Shielding: No, Connecting thread: M20, Color: jet black

Cable gland - G-INS-M20-S68N-NNES-S - 1411163



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 6 mm ... 12 mm, Shielding: No, Connecting thread: M20, Color: silver



Accessories

Cable gland - HC-M-KV-M20(11-16) - 1645998



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20

Cable gland - G-INSEC-M20-S68N-NCRS-S - 1411189



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 9 mm ... 13 mm, Shielding: Yes, Connecting thread: M20, Color: silver

Cable gland - HC-M-KV-Z-M20 - 1646146



Metal screw connection with strain relief clamp, thread length: 6 mm, cable sealing area: 7.5 - 15 mm, clamping area: 11 - 17 mm, SW 24, screw connection: M20

Cable gland - HC-M-KV-T-M20 - 1646188



Metal screw connection with cable bend protection and strain relief, thread length: 6 mm, cable sealing area: 7.5 - 15 mm, clamping area: 10 - 16 mm, SW 24, screw connection: M20

Plug for cable screw gland

Filler plugs - HC-M-BS-M20 - 1645846



Filler plug, metal, size: M20

Protective cover



Accessories

Protective covers - HC-B 10-TMS-SD-IP50 - 1690749



HEAVYCON ADVANCE IP50 protective cover B10, for panel mounting side, with clip locking, with retaining cord, diameter of retaining cord eyelet 3 mm

Protective covers - HC-B 10-TMS-SD-IP65 - 1690781



HEAVYCON ADVANCE IP65 protective cover B10, for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet 3 mm

Reducing adapter


Reducing adapter - REDUC-M-KV-M20/M16 - 1647611




Step-down adapter, M20 to M16, including O-ring

Drawings

Dimensioned drawing





Dimensional drawing

Phoenix Contact 2015 @ - all rights reserved http://www.phoenixcontact.com