



- △ HOUSING: LCP, UL94V-0, BLACK.
CONTACT: PHOSPHOR BRONZE
- △ 1.27µm GOLD PER ASTM B 488 IN CONTACT AREA, 1.27µm MIN TIN-LEAD
ON PCB TAIL, OVER 3.81µm MIN NICKEL PER SAE AMS-QQ-N-290 OVER ALL.
- △ MANUFACTURING TOLERANCE FOR Ø.056 ±0.05 DIAMETER FINISHED HOLE:
DRILLED HOLE: Ø.05 ±0.02
COPPER PLATING: 0.050 ± 0.025
TIN-LEAD PLATING: 0.0124 ± 0.0038.
- △ 1.27 µm GOLD PER ASTM B 488 IN CONTACT AREA, 1.27 µm MIN MATTE TIN
PER ASTM B 545 ON PCB TAIL, OVER 3.81 µm MIN NICKEL PER SAE AMS-QQ-N-290 OVER ALL.
- △ MANUFACTURING TOLERANCE FOR A Ø.0575 ±0.045 FINISHED HOLE WITHOUT TIN LEAD PLATING:
DRILLED HOLE: Ø.065 ±0.02
COPPER PLATING: 0.025 ± 0.050
- △ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

6	OBSOLETE	4	5	1410212-2
		2	3	1410212-1
		CONTACT TAIL/ VOLT. FINISH		PART NO

[illegible]