

## Reducing adapter - A-INR-PG16/13-N-NS-S - 1415216

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Reducing adapter, Nickel-plated brass, Connecting thread: Pg16


The figure shows version A-INR-PG21/16-N-NS-S

### Product Description

Reduced Pg16 to Pg13,5

RoHS

### Key Commercial Data

Packing unit	10 STK
GTIN	 4 055626 038599
GTIN	4055626038599
Custom tariff number	74153900

### Technical data

#### Dimensions

Length	11.5 mm
Length without connecting thread	3.5 mm
Connecting thread diameter	37.5 mm
Hexagon angular dimension	44 mm
Length of the connecting thread	8 mm

#### Ambient conditions

Degree of protection	IP68 (Depends on the screw connection used)
----------------------	---


#### General

Material	Nickel-plated brass
O-ring material	NBR
Outer thread	Pg16
Internal thread	Pg13,5

## Reducing adapter - A-INR-PG16/13-N-NS-S - 1415216

### Drawings

Dimensional drawing



Dimensional drawing

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[1415216](#)