

Power cable - SAC-5P-MINMR/10,0-547 - 1416643

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Power cable, 5-position, PVC, yellow, Plug angled 7/8"-16UNF, on free cable end, Cable length: 10 m

Why buy this product

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ High-performance: connectors and cables with a large conductor cross section for power supply

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 221854
GTIN	4055626221854

Technical data

Dimensions

Length of cable	10 m
-----------------	------

Ambient conditions

Ambient temperature (operation)	-20 °C ... 105 °C (Plug / socket)
Degree of protection	IP68

General

Rated current at 40°C	8 A
Rated voltage	300 V
Number of positions	5
Coding	A - standard
Status display	No
Protective circuit/component	Unwired
Insertion/withdrawal cycles	100
Torque	10 lb _r -in.

Power cable - SAC-5P-MINMR/10,0-547 - 1416643

Technical data

General

	1.12 Nm
--	---------

Material

Contact material	CuZn
Contact surface material	AU
Contact carrier material	PVC
Material of grip body	PVC
Material, knurls	Anodized aluminum

Cable


Cable type	ITC/PLTC
Cable abbreviation	547
AWG signal line	18
Conductor cross section signal conductor	5 x AWG 18
Conductor cross section voltage supply	41 x AWG 34
Wire colors	Black 1, blue 2, gray 3, brown 4, white 5
External sheath, color	yellow
External cable diameter	6.60 mm
Outer sheath, material	PVC
Conductor material	Bare Cu litz wires
Nominal voltage, cable	300 V
Flame resistance	UL 1581, FT4
Other resistance	UV resistant (720 h) UL 2556

Standards and Regulations


Flame resistance	UL 1581, FT4
Other resistance	UV resistant (720 h) UL 2556

Drawings

Dimensional drawing



Circuit diagram




Contact assignment of 7/8" plug

7/8"-16UNF plug, angled

Power cable - SAC-5P-MINMR/10,0-547 - 1416643

Schematic diagram



Pin assignment, plug, 7/8"-16UNF, 5-pos., view of male side

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>