




MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

15P AMPMODU II PIN HEADER

[AMPMODU](#) | [AMPMODU Headers](#)

1-826631-5

TE Internal Number: 1-826631-5

[Always EU RoHS/ELV Compliant](#)

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **15**

Header Type **Breakaway**

Product Drawings

[AMPMODU II STIFTLISTE 90DEG EINREIHIG](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Right Angle

Connector Type

Header

Row-to-Row Spacing

2.54 mm [.1 in]

Stabilizers

Without

Strain Relief

Without

	Board Standoff	Without
	Profile	Standard
	Product Type	Connector
	Gasket	Without
Configuration Features	Number of Positions	15
	Number of Rows	1
	Keyed	No
	Selectively Loaded	No
Body Features	Header Type	Breakaway
	Post Size (mm)	.63
Contact Features	Contact Protection	Without
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Solder Tail Contact Plating Material	Tin
	Contact Mating Area Plating Material	Gold
Termination Features	Termination Post Length	3.2 mm [.1259 in]
	Termination End Plating Material	Tin Over Nickel
	Termination End Plating Thickness (µm)	3
	Termination Method to PC Board	Through Hole
Mechanical Attachment	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
	Mating Connector Lock	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Green
	Housing Material	Thermoplastic
Dimensions	PCB Thickness (Recommended) (in)	.062
	Mating Post Length	6.7 mm [.264 in]

Usage Conditions	High Temperature Housing	No
Operation/Application	High Speed Serial Data Connector	No
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, CUL E28476
Packaging Features	Packaging Quantity	300
	Packaging Method	Box
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	