





No. OF PINS	DIMENSIONS		
	A	B	C
9	1.213	0.984	0.642
	30.81	24.99	16.30
15	1.541	1.312	0.971
	39.14	33.32	24.65
25	2.088	1.852	1.512
	53.04	47.04	38.40
37	2.729	2.500	2.157
	69.32	63.50	54.80

MATERIALS:


SHELL: SPCC, NICKEL PLATED
INSULATOR: BLACK PA9T NYLON, UL 94-O
CONTACTS: BRASS, GOLD PLATED
RIVET: COPPER ALLOY, NICKEL PLATED
SCREWLOCK: ZINC ALLOY, NICKEL PLATED
BOARDLOCK: SPCC, TIN PLATED

ELECTRICAL:

CURRENT RATING: 5 AMPS
INSULATOR RESISTANCE: 1,000 MEGOHMS Min.
DIELECTRIC WITHSTANDING: 1,000VAC RMS
TEMPERATURE: -55° C to +105° C

183-YYY-2 1 3 R YY 1

SERIES
POSITIONS
009
015
025
037
GENDER
2 = FEMALE
TERMINATION
1 = DIP SOLDER
SHELL PLATING
3 = NICKEL PLATED
RoHS COMPLIANT
HARDWARE OPTIONS
SEE SHEET 2
PLATING OPTIONS
1 = GOLD FLASH











BOTTOM VIEW

RoHS COMPLIANT

DO NOT SCALE FROM DRAWING

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.		DRAWN: PAM JENKINS		DATE: 4-28-05			
			CHECKED:		DATE:			
NorComp			SCALE: 1 : 1	SHEET 1 OF 2	REV 10			
			DWG NO. 183-YYY-213RYY1					

	 METAL SHELL WITH INSIDE GROUND STRAPS	 METAL SHELL	 METAL SHELL FORK BOARD LOCKS	 METAL SHELL FORK BOARD LOCKS
 0.120" DIA. HOLE	16	N/A	N/A	55
 4-40 FLUSH INSERT	17	45	57 BOARD LOCKS IN REAR HOLE (0.590")	53 BOARD LOCKS IN FRONT HOLE (0.590")
 4-40 HEX STANDOFF FEMALE SCREWLOCK	18	48	54 BOARD LOCKS IN REAR HOLE	56 BOARD LOCKS IN FRONT HOLE
 4-40 ROUND STANDOFF FEMALE SCREWLOCK	N/A	N/A	N/A	N/A

DO NOT SCALE FROM DRAWING

RoHS COMPLIANT

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.		DRAWN: WAYNE ROBBINS		DATE: 8-23-98		
			CHECKED:		DATE:		
	NorComp		SCALE:		SHEET OF 2 2		REV 10
DWG NO. 183-YYY-213RYY1							

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

NorComp:

<u>183-009-213R161</u>	<u>183-009-213R171</u>	<u>183-009-213R181</u>	<u>183-015-213R161</u>	<u>183-015-213R171</u>	<u>183-025-213R161</u>
<u>183-025-213R171</u>	<u>183-025-213R181</u>	<u>183-037-213R161</u>	<u>183-037-213R171</u>	<u>183-037-213R181</u>	<u>183-015-213R181</u>
<u>183-009-213R431</u>	<u>183-009-213R451</u>	<u>183-009-213R481</u>	<u>183-009-213R541</u>	<u>183-009-213R571</u>	<u>183-015-213R431</u>
<u>183-015-213R451</u>	<u>183-015-213R481</u>	<u>183-015-213R541</u>	<u>183-025-213R431</u>	<u>183-025-213R451</u>	<u>183-025-213R481</u>
<u>183-025-213R541</u>	<u>183-025-213R571</u>	<u>183-037-213R431</u>	<u>183-037-213R451</u>	<u>183-037-213R481</u>	<u>183-037-213R541</u>
<u>183-037-213R571</u>	<u>183-009-212-531</u>	<u>183-015-112-531</u>	<u>183-037-212-531</u>	<u>183-025-212-531</u>	<u>183-015-212-531</u>
<u>183-037-112-531</u>	<u>183-025-112-531</u>	<u>183-009-112-531</u>			