

10987654321

MATERIAL NUMBER	ENGINEERING NUMBER NON-PLATED	MATERIAL NUMBER	ENGINEERING NUMBER TIN PLATED	AWG WIRE RANGE	FITS MALE TAB SIZE	"L" .031/0.79	"B" ±.015/0.38	"H" ±.010	REF. WIRE INSULATION DIAMETER
190210031	MZ-0186	190180076	MZ-4186	26-20	.110x.020	.690/17.50	.32/8.1	.078/1.98	.040-.095
190210032	MZ-0186-032	190180077	MZ-4186-032	26-20	.110x.032	.690/17.50	.32/8.1	.094/2.38	.040-.095
190210004	AAZ-0187	190210011	AAZ-4187	22-16	.110x.020	.717/18.20	.34/8.6	.078/1.98	.060-.125
190210005	AAZ-0187-032	190210036	AAZ-4187-032	22-16	.110x.032	.717/18.20	.34/8.6	.094/2.38	.060-.125
190210018	BBZ-0188	190210025	BBZ-4188	18-12	.110x.020	.717/18.20	.34/8.6	.078/1.98	.085-.145
190210019	BBZ-0188-032	190210026	BBZ-4188-032	18-12	.110x.032	.717/18.20	.34/8.6	.094/2.38	.085-.145

22

WIRE RANGE

WIRE INSULATION DIA.

B

L

.25 ± 0.10

6.4 ± 0.26

.23 ± 0.10

5.8 ± 0.26

METAL CARRIER STRIP

H

.163 MAX

4.10

"VIBRAKRIMP"

OPEN ELECTRICAL BARREL W/OPEN VIBRATION SUPPORT

METAL STRIP QUICK DISCONNECTS

SALES DRAWING

NOTES:

1. MATERIAL: BRASS, .016 THK.

2. PLATING: SEE CHART.

WAS CD-51003	EC NO. ETC2002-0287	DRWN: BRE	CHK: HEB	APPR: RWD	DESCRIPTION	REV
A	02/04/10	02/04/10	02/04/10	02/04/10		

QUALITY SYMBOLS	GENERAL TOLERANCES: (UNLESS SPECIFIED)	SCALE NO: NE	DESIGN UNITS	THIRD ANGLE PROJECTION	DIMENSIONS:	SHT	REV
MAJOR = 0	4 PLACES ±0. mm ±. INCH	DRAWN BY & DATE BRE 02/04/09	mm INCH	THIRD ANGLE PROJECTION	mm INCH mm ONLY		
CRITICAL = 0	3 PLACES ±0. mm ±. INCH	CHECKED BY & DATE HEB 02/04/09					
	2 PLACES ±0. mm ±. INCH	APPROVED BY & DATE RWD 02/04/09					
	1 PLACE ±0. mm ±. INCH	CAD FILENAME SD-19021-007 .DGN					
	ANGULAR: ± 1/2 °	MATERIAL NO. SEE CHART		DRAWING NO. SD-19021-007		SHEET NO. 1 OF 1	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.					SIZE B

LBORD.DGN REV A 96/06/12 LEVEL 4

987654321