

PCB terminal block - ZFKDSA 1,5-W-7,62- 2 - 1906158

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Pitch: 7.62 mm, Number of positions: 2, Connection method: Spring-cage connection, Mounting: Soldering, Color: green



The illustration shows the 10-position version



Key commercial data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	 4 017918 467708
Weight per Piece (excluding packing)	2.9 g
Custom tariff number	85369010
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Dimensions

Pitch	7.62 mm
Dimension a	7.62 mm

General

Range of articles	ZFKDS(A) 1,5-W
Nominal cross section	1.5 mm ²
Solder pin surface	Sn
Number of positions	2

Classifications

eCl@ss

eCl@ss 4.0	27141109
eCl@ss 4.1	27141109

PCB terminal block - ZFKDSA 1,5-W-7,62- 2 - 1906158

Classifications

eCl@ss

eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401
eCl@ss 8.0	27440401

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

Approvals

Approvals

Approvals

CSA / KEMA-KEUR / CCA / IECCEB Scheme / EAC

Ex Approvals

Approvals submitted

Approval details

CSA 		
	B	D
mm ² /AWG/kcmil	28-12	28-12
Nominal current I _N	10 A	10 A
Nominal voltage U _N	300 V	300 V

PCB terminal block - ZFKDSA 1,5-W-7,62- 2 - 1906158

Approvals

KEMA-KEUR 	
mm²/AWG/kcmil	1.5
Nominal voltage UN	250 V

CCA	
mm²/AWG/kcmil	1.5
Nominal voltage UN	250 V

IECEE CB Scheme 	
mm²/AWG/kcmil	1.5
Nominal voltage UN	250 V

EAC	
-----	--