

# Printed-circuit board connector - MCC 1/18-STZ-3,81 BK - 1971769

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Plug component, Nominal current: 8 A, Number of positions: 18, Pitch: 3.81 mm, Connection method: Crimp connection, Color: black, Contact surface: Tin









# **Key Commercial Data**

Packing unit	1 pc
Minimum order quantity	50 pc
Weight per Piece (excluding packing)	5.33 g
Custom tariff number	85366990
Country of origin	Poland

### Technical data

#### **Dimensions**

Pitch	3.81 mm
Dimension a	64.77 mm

#### General

Range of articles	MCC 1/STZ
Rated voltage (III/3)	160 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	8 A
Nominal cross section	1 mm <sup>2</sup>
Number of positions	18

#### Connection data

Conductor cross section flexible min.	0.2 mm <sup>2</sup>
Conductor cross section flexible max.	1 mm²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	18
Minimum AWG according to UL/CUL	20
Maximum AWG according to UL/CUL	18

#### Standards and Regulations



# Printed-circuit board connector - MCC 1/18-STZ-3,81 BK - 1971769

# Technical data

## Standards and Regulations

Connection in acc. with standard	EN-VDE
	CUL

## Classifications

## eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27141190
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440309
eCl@ss 9.0	27440309

#### **ETIM**

ETIM 3.0	EC001121
ETIM 4.0	EC002638
ETIM 5.0	EC002638

### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

# Approvals

## Approvals

Approvals

cULus Recognized / EAC

Ex Approvals



# Printed-circuit board connector - MCC 1/18-STZ-3,81 BK - 1971769

# Approvals

Approvals submitted

## Approval details

cULus Recognized		
	В	D
mm²/AWG/kcmil	24-22	24-22
Nominal current IN	5 A	5 A
Nominal voltage UN	300 V	300 V

LEAC		
27.0		
		1

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: