

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The **ASI 2SC1972** is Designed for RF power amplifiers on VHF band mobile radio applications.

FEATURES INCLUDE:

- Replaces Original **2SC1972** in Most Applications
- High Gain Reduces Drive Requirements
- Economical **TO-220CE** Package

MAXIMUM RATINGS

I_C	3.5 A
V_{CBO}	35 V
P_{DISS}	25 W @ $T_C = 25^\circ C$
T_{STG}	$-55^\circ C$ to $+175^\circ C$
θ_{JC}	6.0 $^\circ C/W$

PACKAGE STYLE TO-220AB (COMMON EMITTER)

The image shows two views of a TO-220AB package. The left view is a top-down perspective showing the package body with dimensions A (width), B (height), C (total height including leads), D (lead thickness), E (lead width), F (lead length), G (lead pitch), H (lead length), L (lead thickness), M (lead width), N (lead pitch), P (lead length), R (lead length), S (lead length), T (lead length), and U (lead length). The right view is a side profile showing the package body with dimensions A (width), B (height), C (total height including leads), D (lead thickness), E (lead width), F (lead length), G (lead pitch), H (lead length), L (lead thickness), M (lead width), N (lead pitch), P (lead length), R (lead length), S (lead length), T (lead length), and U (lead length). The package has three pins: 1 (base), 2 (emitter), and 3 (collector). A tab is also shown, which is the emitter.

1 = BASE 2 = EMITTER
3 = COLLECTOR TAB = EMITTER

DIMENSIONS				
	mm		inches	
	min	max	min	max
A	10	10.4	0.393	0.409
B	15.2	15.9	0.598	0.626
C	12.7	13.7	0.500	0.539
D	6.2	6.6	0.244	0.260
E	4.4	4.6	0.173	0.181
F	3.5	5.5	0.137	0.216
G	2.65	2.95	0.104	0.116
H	17.6 typ.		0.692 typ.	
L	1.14	1.7	0.044	0.067
M	3.75	3.85	0.147	0.151
N	1.23	1.32	0.048	0.051
P	0.41	0.64	0.016	0.025
R	2.4	2.72	0.094	0.107
S	4.95	5.15	0.194	0.203
T	2.4	2.7	0.094	0.106
U	0.61	0.94	0.024	0.037

CHARACTERISTICS $T_C = 25^\circ C$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	$I_C = 50$ mA	17			V
BV_{CBO}	$I_C = 10$ mA	35			V
BV_{EBO}	$I_E = 10$ mA	4.0			V
I_{CBO}	$V_{CES} = 25$ V			100	μA
I_{EBO}	$V_{EB} = 3.0$ V			500	μA
h_{FE}	$V_{CE} = 10$ V $I_C = 100$ mA	10	50	180	---
η_c	$V_{CC} = 13.5$ V $P_{IN} = 2.5$ W $f = 175$ MHz	60	70		%
P_{OUT}		14	15		W