


## Zener Diodes

### Features

- Silicon planar power Zener diodes
- For use in stabilizing and clipping circuits with high power rating
- Standard Zener voltage tolerance is  $\pm 5\%$
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**



17173

### Applications

- Voltage stabilization

### Mechanical Data

**Case:** DO-41

**Weight:** approx. 310 mg

**Packaging codes/options:**

TR/5K per 13" reel, 25K/box

TAP/5K per Ammo pack (52 mm tape), 25K/box

### Absolute Maximum Ratings

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

| Parameter         | Test condition | Symbol    | Value             | Unit |
|-------------------|----------------|-----------|-------------------|------|
| Power dissipation |                | $P_{tot}$ | 1.3 <sup>1)</sup> | W    |
| Z-current         |                | $I_Z$     | $P_V/V_Z$         | mA   |

<sup>1)</sup> Valid provided that leads at a distance of 4 mm from case are kept at ambient temperature.

### Thermal Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

| Parameter                                  | Test condition | Symbol     | Value             | Unit               |
|--------------------------------------------|----------------|------------|-------------------|--------------------|
| Thermal resistance junction to ambient air |                | $R_{thJA}$ | 110 <sup>1)</sup> | K/W                |
| Junction temperature                       |                | $T_j$      | 175               | $^{\circ}\text{C}$ |
| Storage temperature range                  |                | $T_{stg}$  | - 65 to + 175     | $^{\circ}\text{C}$ |

<sup>1)</sup> Valid provided that leads at a distance of 4 mm from case are kept at ambient temperature.

### Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified

| Parameter       | Test condition        | Symbol | Min. | Typ. | Max. | Unit |
|-----------------|-----------------------|--------|------|------|------|------|
| Forward voltage | $I_F = 200\text{ mA}$ | $V_F$  |      |      | 1.2  | V    |

# 1N4728A to 1N4764A



Vishay Semiconductors

## Electrical Characteristics

1N4728A...1N4764A

| Part number | Nominal Zener voltage <sup>1)</sup> | Test current | Maximum dynamic impedance |                      |          | Maximum reverse leakage current |                    | Surge current <sup>3)</sup>      | Maximum regulator current <sup>2)</sup> |
|-------------|-------------------------------------|--------------|---------------------------|----------------------|----------|---------------------------------|--------------------|----------------------------------|-----------------------------------------|
|             | $V_Z$ at $I_{ZT}$                   | $I_{ZT}$     | $Z_{ZT}$ at $I_{ZT}$      | $Z_{ZK}$ at $I_{ZK}$ | $I_{ZK}$ | $I_R$                           | Test voltage $V_R$ | at $T_A = 25\text{ °C}$<br>$I_R$ | $I_{ZM}$                                |
|             | V                                   | mA           | $\Omega$                  | $\Omega$             | mA       | $\mu\text{A}$                   | V                  | mA                               | mA                                      |
| 1N4728A     | 3.3                                 | 76           | 10                        | 400                  | 1        | 100                             | 1                  | 1380                             | 276                                     |
| 1N4729A     | 3.6                                 | 69           | 10                        | 400                  | 1        | 100                             | 1                  | 1260                             | 252                                     |
| 1N4730A     | 3.9                                 | 64           | 9                         | 400                  | 1        | 50                              | 1                  | 1190                             | 234                                     |
| 1N4731A     | 4.3                                 | 58           | 9                         | 400                  | 1        | 10                              | 1                  | 1070                             | 217                                     |
| 1N4732A     | 4.7                                 | 53           | 8                         | 500                  | 1        | 10                              | 1                  | 970                              | 193                                     |
| 1N4733A     | 5.1                                 | 49           | 7                         | 550                  | 1        | 10                              | 1                  | 890                              | 178                                     |
| 1N4734A     | 5.6                                 | 45           | 5                         | 600                  | 1        | 10                              | 2                  | 810                              | 162                                     |
| 1N4735A     | 6.2                                 | 41           | 2                         | 700                  | 1        | 10                              | 3                  | 730                              | 146                                     |
| 1N4736A     | 6.8                                 | 37           | 3.5                       | 700                  | 1        | 10                              | 4                  | 660                              | 133                                     |
| 1N4737A     | 7.5                                 | 34           | 4                         | 700                  | 0.5      | 10                              | 5                  | 605                              | 121                                     |
| 1N4738A     | 8.2                                 | 31           | 4.5                       | 700                  | 0.5      | 10                              | 6                  | 550                              | 110                                     |
| 1N4739A     | 9.1                                 | 28           | 5                         | 700                  | 0.5      | 10                              | 7                  | 500                              | 100                                     |
| 1N4740A     | 10                                  | 25           | 7                         | 700                  | 0.25     | 10                              | 7.6                | 454                              | 91                                      |
| 1N4741A     | 11                                  | 23           | 8                         | 700                  | 0.25     | 5                               | 8.4                | 414                              | 83                                      |
| 1N4742A     | 12                                  | 21           | 9                         | 700                  | 0.25     | 5                               | 9.1                | 380                              | 76                                      |
| 1N4743A     | 13                                  | 19           | 10                        | 700                  | 0.25     | 5                               | 9.9                | 344                              | 69                                      |
| 1N4744A     | 15                                  | 17           | 14                        | 700                  | 0.25     | 5                               | 11.4               | 304                              | 61                                      |
| 1N4745A     | 16                                  | 15.5         | 16                        | 700                  | 0.25     | 5                               | 12.2               | 285                              | 57                                      |
| 1N4746A     | 18                                  | 14           | 20                        | 750                  | 0.25     | 5                               | 13.7               | 250                              | 50                                      |
| 1N4747A     | 20                                  | 12.5         | 22                        | 750                  | 0.25     | 5                               | 15.2               | 225                              | 45                                      |
| 1N4748A     | 22                                  | 11.5         | 23                        | 750                  | 0.25     | 5                               | 16.7               | 205                              | 41                                      |
| 1N4749A     | 24                                  | 10.5         | 25                        | 750                  | 0.25     | 5                               | 18.2               | 190                              | 38                                      |
| 1N4750A     | 27                                  | 9.5          | 35                        | 750                  | 0.25     | 5                               | 20.6               | 170                              | 34                                      |
| 1N4751A     | 30                                  | 8.5          | 40                        | 1000                 | 0.25     | 5                               | 22.8               | 150                              | 30                                      |
| 1N4752A     | 33                                  | 7.5          | 45                        | 1000                 | 0.25     | 5                               | 25.1               | 135                              | 27                                      |
| 1N4753A     | 36                                  | 7            | 50                        | 1000                 | 0.25     | 5                               | 27.4               | 125                              | 25                                      |
| 1N4754A     | 39                                  | 6.5          | 60                        | 1000                 | 0.25     | 5                               | 29.7               | 115                              | 23                                      |
| 1N4755A     | 43                                  | 6            | 70                        | 1500                 | 0.25     | 5                               | 32.7               | 110                              | 22                                      |
| 1N4756A     | 47                                  | 5.5          | 80                        | 1500                 | 0.25     | 5                               | 35.8               | 95                               | 19                                      |
| 1N4757A     | 51                                  | 5            | 95                        | 1500                 | 0.25     | 5                               | 38.8               | 90                               | 18                                      |
| 1N4758A     | 56                                  | 4.5          | 110                       | 2000                 | 0.25     | 5                               | 42.6               | 80                               | 16                                      |
| 1N4759A     | 62                                  | 4            | 125                       | 2000                 | 0.25     | 5                               | 47.1               | 70                               | 14                                      |
| 1N4760A     | 68                                  | 3.7          | 150                       | 2000                 | 0.25     | 5                               | 51.7               | 65                               | 13                                      |
| 1N4761A     | 75                                  | 3.3          | 175                       | 2000                 | 0.25     | 5                               | 56                 | 60                               | 12                                      |
| 1N4762A     | 82                                  | 3.0          | 200                       | 3000                 | 0.25     | 5                               | 62.2               | 55                               | 11                                      |
| 1N4763A     | 91                                  | 2.8          | 250                       | 3000                 | 0.25     | 5                               | 69.2               | 50                               | 10                                      |
| 1N4764A     | 100                                 | 2.5          | 350                       | 3000                 | 0.25     | 5                               | 76.0               | 45                               | 9                                       |

<sup>1)</sup> Based on dc-measurement at thermal equilibrium while maintaining the lead temperature ( $T_L$ ) at  $30\text{ °C} + 1\text{ °C}$ , 9.5 mm (3/8") from the diode body.

<sup>2)</sup> Valid provided that electrodes at a distance of 4 mm from case are kept at ambient temperature.

<sup>3)</sup>  $t_p = 10\text{ ms}$ .

## Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified





Figure 1. Admissible Power Dissipation vs. Ambient Temperature

## Package Dimensions in millimeters (inches): DO-41



Document no.: 6.561-5001.02-4  
Rev. 3 - Date: 09 February 2005  
94 9368



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.