


1N6263WT

SILICON SCHOTTKY BARRIER DIODE

for general purpose applications

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode




Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Peak Reverse Voltage	V_{RRM}	40	V
Power Dissipation	P_{tot}	400	mW
Max. Single Cycle Surge Forward Current (10 s Square wave)	I_{FSM}	2	A
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_S	- 55 to + 150	$^\circ\text{C}$

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Max.	Unit
Reverse Breakdown Voltage at $I_R = 10\ \mu\text{A}$	$V_{(BR)R}$	40	-	V
Forward Voltage at $I_F = 1\ \text{mA}$ at $I_F = 15\ \text{mA}$	V_F	- -	0.39 0.9	V
Reverse Leakage Current at $V_R = 30\ \text{V}$	I_R	-	200	nA
Junction Capacitance at $V_R = 0\ \text{V}$, $f = 1\ \text{MHz}$	C_{tot}	-	2.2	pF
Reverse Recovery Time at $I_F = I_R = 5\ \text{mA}$, recover to $0.1\ I_R$	t_{rr}	-	1	ns



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)




Dated : 23/11/2006

1N6263WT


PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SOD-523



UNIT	A	b _p	C	D	E	H _E	V	∠
mm	0.70 0.60	0.4 0.3	0.135 0.127	1.25 1.15	0.85 0.75	1.7 1.5	0.1	5°



SEMTECH ELECTRONICS LTD.
(Subsidiary of Sino-Tech International Holdings Limited, a company
listed on the Hong Kong Stock Exchange, Stock Code: 724)



Dated : 23/11/2006