




CentralTM
Semiconductor Corp.

DESCRIPTION

The CENTRAL SEMICONDUCTOR 1SMB5.0CA Series types are Surface Mount Bi-Directional Glass Passivated Junction Transient Voltage Suppressors designed to protect voltage sensitive components from high voltage transients. **THIS DEVICE IS MANUFACTURED WITH A GLASS PASSIVATED CHIP FOR OPTIMUM RELIABILITY.**

Note: For Uni-directional devices, please refer to the 1SMB5.0A Series data sheet.

Specified by
STAND-OFF VOLTAGE

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

	SYMBOL	UNITS
Peak Power Dissipation	P_{DM}	600 W
Peak Forward Surge Current (JEDEC Method)	I_{FSM}	100 A
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150 $^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$)

TYPE NO.	REVERSE STAND-OFF VOLTAGE	BREAKDOWN VOLTAGE			MAXIMUM REVERSE LEAKAGE ● V_{RWM}	MAXIMUM CLAMPING VOLTAGE ● I_{PPM}	MAXIMUM PEAK PULSE CURRENT	MARKING CODE		
		V_{BR}	ϕI_T	ϕV_{RWM}						
	V_{RWM}				VOLTS		I_R		V_C	I_{PPM}
	VOLTS				MIN	MAX	mA		μA	VOLTS
1SMB5.0CA	5.0	6.40	7.25	10	1600	9.2	65.2	CKEC		
1SMB6.0CA	6.0	6.67	7.67	10	1600	10.3	58.3	CKGC		
1SMB6.5CA	6.5	7.22	8.30	10	1000	11.2	53.6	CKKC		
1SMB7.0CA	7.0	7.78	8.95	10	400	12.0	50.0	CKMC		
1SMB7.5CA	7.5	8.33	9.58	1.0	200	12.9	46.5	CKPC		
1SMB8.0CA	8.0	8.89	10.23	1.0	100	13.6	44.1	CKRC		
1SMB8.5CA	8.5	9.44	10.82	1.0	20	14.4	41.7	CKTC		
1SMB9.0CA	9.0	10.0	11.5	1.0	10	15.4	39.0	CKVC		
1SMB10CA	10	11.1	12.8	1.0	5.0	17.0	35.3	CKXC		
1SMB11CA	11	12.2	14.0	1.0	5.0	18.2	33.0	CKZC		
1SMB12CA	12	13.3	15.3	1.0	5.0	19.9	30.2	CLEC		
1SMB13CA	13	14.4	16.5	1.0	5.0	21.5	27.9	CLGC		

TYPE NO.	REVERSE STAND-OFF VOLTAGE	BREAKDOWN VOLTAGE			MAXIMUM REVERSE LEAKAGE ②V _{RWM} I _R	MAXIMUM CLAMPING VOLTAGE ③V _C	MAXIMUM PEAK PULSE CURRENT ④I _{PPM}	MARKING CODE
		V _{BR}		①I _T				
		VOLTS						
		V _{RWM}	MIN					
1SMB14CA	14	15.6	17.9	1.0	5.0	23.2	25.8	CLKC
1SMB15CA	15	16.7	19.2	1.0	5.0	24.4	24.0	CLMC
1SMB16CA	16	17.8	20.5	1.0	5.0	26.0	23.1	CLPC
1SMB17CA	17	18.9	21.7	1.0	5.0	27.6	21.7	CLRC
1SMB18CA	18	20.0	23.3	1.0	5.0	29.2	20.5	CLTC
1SMB20CA	20	22.2	25.5	1.0	5.0	32.4	18.5	CLVC
1SMB22CA	22	24.4	28.0	1.0	5.0	35.5	16.9	CLXC
1SMB24CA	24	26.7	30.7	1.0	5.0	38.9	15.4	CLZC
1SMB26CA	26	28.9	33.2	1.0	5.0	42.1	14.2	CMEC
1SMB28CA	28	31.1	35.8	1.0	5.0	45.4	13.2	CMGC
1SMB30CA	30	33.3	38.3	1.0	5.0	48.4	12.4	CMKC
1SMB33CA	33	36.7	42.2	1.0	5.0	53.3	11.3	CMMC
1SMB36CA	36	40.0	46.0	1.0	5.0	58.1	10.3	CMPC
1SMB40CA	40	44.4	51.1	1.0	5.0	64.5	9.3	CMRC
1SMB43CA	43	47.8	54.9	1.0	5.0	69.4	8.6	CMTC
1SMB45CA	45	50.0	57.5	1.0	5.0	72.7	8.3	CMVC
1SMB48CA	48	53.3	61.3	1.0	5.0	77.4	7.7	CMXC
1SMB51CA	51	56.7	65.2	1.0	5.0	82.4	7.3	CMZC
1SMB54CA	54	60.0	69.0	1.0	5.0	87.1	6.9	CNEC
1SMB58CA	58	64.4	74.1	1.0	5.0	93.6	6.4	CNGC
1SMB60CA	60	66.7	76.7	1.0	5.0	96.8	6.2	CNKC
1SMB64CA	64	71.1	81.8	1.0	5.0	103	5.8	CNMC
1SMB70CA	70	77.8	89.5	1.0	5.0	113	5.3	CNPC
1SMB75CA	75	83.3	95.8	1.0	5.0	121	4.9	CNRC
1SMB78CA	78	86.7	99.7	1.0	5.0	126	4.7	CNTC
1SMB85CA	85	94.4	108.2	1.0	5.0	137	4.4	CNVC
1SMB90CA	90	100.0	115.5	1.0	5.0	146	4.1	CNXC
1SMB100CA	100	111.0	128.0	1.0	5.0	162	3.7	CNZC
1SMB110CA	110	122.0	140.5	1.0	5.0	177	3.4	CPEC
1SMB120CA	120	133.0	153.0	1.0	5.0	193	3.1	CPGC
1SMB130CA	130	144.0	165.5	1.0	5.0	209	2.9	CPKC
1SMB150CA	150	167.0	192.5	1.0	5.0	243	2.5	CPMC
1SMB160CA	160	178.0	205.0	1.0	5.0	259	2.3	CPPC
1SMB170CA	170	189.0	217.5	1.0	5.0	275	2.2	CPRC

DATA
SHEET

All Dimensions in Inches (mm).

