

ZS4-T3-R1



Products Low Voltage Products and Systems Connection Devices Terminal Blocks SNK Series

General Information

Extended Product Type:	ZS4-T3-R1
Product ID:	1SNK506213R0000
EAN:	3472595062133
Catalog Description:	ZS4-T3-R1 Screw Clamp Terminal Block - Feed-through - Grey
Long Description:	Unique triple deck solution combining increased connecting capacity (up to 4 mm ² with ferrule) and jumper channel available on each deck, - Fit many applications: space constraints , multiple signals distribution, sensors distribution, - Closed terminal block: no end section needed, optimized rigidity.

Additional Information

ABB Industrial IT Suite:	Control IT
Ambient Air Temperature:	Operation -55 ... +110 °C Storage -55 ... +110 °C
Ambient Temperature:	-5 ... +40 °C
BV Certificate:	1SND161073A0204
CB Certificate:	1SND161095A0200
CSA Certificate:	1SND161070A0209
Color:	Grey
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Rigid 1x 24 ... 10 AWG Screw Clamp / Rigid 2x 24 ... 16 AWG Screw Clamp / With Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 12 AWG Screw Clamp / With Twin Ferrule 2x 24 ... 16 AWG
Connecting Capacity UL/CSA:	Stranded 10 AWG
Connecting Capacity Main Circuit:	Screw Clamp / Flexible 1x 0.22 ... 4 mm ² Screw Clamp / Flexible 2x 0.2 ... 1.5 mm ² Screw Clamp / Rigid 1x 0.2 ... 4 mm ² Screw Clamp / Rigid 2x 0.2 ... 1.5 mm ² Screw Clamp / With Insulated Ferrule 1x 0.22 ... 4 mm ² Screw Clamp / Without Insulated Ferrule 1x 0.22 ... 4 mm ² Screw Clamp / With Twin Ferrule 2x 0.22 ... 1.5 mm ²
Connection Type:	Screw clamp
Country of Origin:	France (FR)
Customs Tariff Number:	85369010
DNV Certificate:	1SND161087A0202
Data Sheet, Technical Information:	1SNK161079D0201
Declaration of Conformity - CE:	1SND225100U1000
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Dielectric Test Voltage:	2000 V
EAC Certificate:	1SND161009A1100
EAN:	3472595062133
ETIM 4:	EC000897 - Feed-through terminal block
ETIM 5:	EC000897 - Feed-through terminal block
ETIM 6:	EC000897 - Feed-through terminal block
Environmental Information:	1SND220178E0200
Flammability According to UL94:	V0
Function:	Feed-through
Gauge Type:	A3-B3

III Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SNK160027C0201
Insulation Material:	Polyamide
Invoice Description:	ZS4-T3-R1 Screw Clamp Terminal Block - Feed-through - Grey
Maximum Operating Voltage UL/CSA:	Main Circuit 300 V
Minimum Order Quantity:	25 piece
Mounting on DIN Rail:	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Connections:	6
Number of Levels:	3
Object Classification Code:	X
Order Multiple:	25 piece
Package Level 1 EAN:	3472595062133
Package Level 1 Gross Weight:	0.732 kg
Package Level 1 Height:	97 mm
Package Level 1 Length:	117 mm
Package Level 1 Units:	25 piece
Package Level 1 Width:	147 mm
Package Level 2 Gross Weight:	10.255 kg
Package Level 2 Height:	300 mm
Package Level 2 Length:	500 mm
Package Level 2 Units:	350 piece
Package Level 2 Width:	300 mm
Package Level 3 Units:	8400 piece
Packing Type:	Box
Pollution Degree:	3
Power Loss:	3 W
Product Main Type:	ZS4-T3-R1
Product Name:	Terminal Block
Product Net Depth:	78.4 mm
Product Net Height:	100.1 mm
Product Net Length:	78.4 mm
Product Net Weight:	28.3 g
Product Net Width:	6 mm
Product Packing Type:	Box
RMRS Certificate:	1SND161008A1101
Rated Cross-Section:	4 mm ²
Rated Current (I _n):	Main Circuit 32 A Tap 32 A
Rated Impulse Withstand Voltage (U _{imp}):	8000 V
Rated Short-time Withstand Current (I _{cw}):	for 1 s 480 A
Rated Voltage (U _r):	800 V
Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
RoHS Information:	1SND230491F0206
RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Spacing:	6 mm
Sub-Function:	6 connections

Sub-Function:	3 connections
Sub-Function 3:	3 feed-through circuits
Sub-Function 4:	Closed block
Wire Stripping Length:	10.5 mm
cUL Certificate:	1SND161041A0210
Number of Potentials:	3

