





4 mm<sup>2</sup>  
10 AWG

## ZS4-SF1-R Screw Clamp Terminal Block

for 5x20 and 5x25 Fuses - with Blown Fuse Indicator and Test Socket Screws

8 mm 0.315 in spacing



### Features and Benefits

- Protect your circuit with 5x25 and 5x20 fuse terminal blocks (fuse not supplied with the terminal blocks),
- Compliant with IEC 60947-7-3 standard,
- Ease the test with built-in test socket screws,
- Quickly identify the defective circuit thanks to the blown fuse indicator with leakage current < 0.5 mA.

### Main Technical Data

Connecting capacity		IEC	cULus - CSA
with 1 conductor per clamp	Rigid	0.2-4 mm <sup>2</sup>	24-10 AWG
	Flexible	0.22-4 mm <sup>2</sup>	24-10 AWG
	with ferrule	0.22-4 mm <sup>2</sup>	24-12 AWG
		Gauge	A3-B3
with 2 conductors per clamp	Rigid	0.2-1 mm <sup>2</sup>	24-18 AWG
	Flexible	0.22-1 mm <sup>2</sup>	24-18 AWG
	with twin ferrule	0.22-1.5 mm <sup>2</sup>	24-16 AWG
Rated cross section		4 mm <sup>2</sup>	10 AWG
Rated current		6.3 A	6.3 A
Rated short-time withstand current (1s)		480 A	
Rated voltage		250 V	300 V
Impulse withstand voltage		8000 V	
Protection		IP 20	NEMA 1

### Rated power

Separate arrangement/Overload and short-circuit arrangement	2.5 W
Separate arrangement/Exclusive short-circuit arrangement	4 W
Compound arrangement/Overload and short-circuit arrangement	1.6 W
Compound arrangement/Exclusive short-circuit arrangement	4 W

CE	CB	RoHS	cUL	CSA	Gost	BV	Gost and BV: Pending - 2009
----	----	------	-----	-----	------	----	-----------------------------

### Mounting Instructions

Rail		DIN3-TH35
Wire stripping length		11 mm 0.433 in
Tool		Flat screwdriver Ø 3.5 mm Ø 0.138 in
Torque		0.6 Nm ± 0.1 5.31 lb.in ± 0.885

### Ordering Details

#### ZS4-SF1-R Fuse Screw Clamp Terminal Block

Description	Type	Part Number	Pack <sup>(ing)</sup> pieces	Weight g (1 pce)
With blown fuse indicator by red LED 24-60V and 2 test socket screws Dia 2 mm 0.079 in	Grey-Dark Grey	<b>ZS4-SF1-R2</b> 1SNK 508 413 R0000	50	13.30
With blown fuse indicator by red LED 115-250V and 2 test socket screws Dia 2 mm 0.079 in	Grey-Dark Grey	<b>ZS4-SF1-R4</b> 1SNK 508 415 R0000	50	13.30

#### ZS4-SF1-R Terminal Block Accessories

Description	Type	Part Number	Pack <sup>(ing)</sup> pieces	Weight g (1 pce)
1 End Stops	10 mm 0.394 in Dark Grey	<b>BAM3</b> 1SNK 900 001 R0000	50	13.80
2 End Sections	1.5 mm 0.059 in Dark Grey	<b>ES4-SF</b> 1SNK 508 960 R0000	20	1.82
3 Terminal Block Markers	Blank card White	<b>MC812</b> 1SNK 160 000 R0000	22	0.09
	Universal wire markers holder Grey	<b>UMH</b> 1SNK 900 611 R0000	10	0.20
	Self adhesive strip White	<b>SAT8</b> 1SNK 900 616 R0000	5	6.00

Some accessories may modify the terminal block's ratings. See complete information in "Technical Datasheet".