

SNK Terminal Blocks T&B Catalog Number:

1SNK506211R0000

UPC Number: 80432548888

Status: Active

Description:

Gray feed through double deck terminal block with 6 mm spacing, 30 amp UL current with screw clamp connection

| Features | |
|---------------------------------------|---|
| | |
| | Easy and ergonomic mounting thanks to the unique profile |
| | Marking surfaces can be read clearly from any angle in an enclosure and are larger than standard markers |
| | One unique end section and circuit separator fits all feed-through terminal blocks, reducing the use of accessories |
| Application | |
| | For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc. |
| General | |
| Style | Double Deck Feed Through |
| Color | Gray |
| Mounting | DIN 3 |
| Series | ZS6-D1 |
| Connection Technology | Screw Clamp |
| UL Wire Range (AWG) | 24-10 |
| Rated IEC Wire Range (Solid) (mm2) | 0.2-6 |
| Rated IEC Wire Range (Stranded) (mm2) | 0.22-6 |
| Dimension Information | |
| L x W x H (mm) | 70.4 x 6 x 67 |
| Spacing (mm) | 6 |
| L x W x H (in) | 2.77 x .236 x 2.64 |
| Spacing (inches) | 0.236 |
| Specifications | |
| UL Current (Amps) | 30 |
| UL Voltage (VAC) | 300 |
| Packaging | |
| T&B Order Multiple | 50 |
| T&B Inner Pack | 50 |
| Package in Units | 400 |
| T&B Sold in UOM | Each |
| T&B Weight Per UOM | 0.04 lbs. Each |
| Certifications | |
| Approvals | USR, CSA, CE |

For further technical assistance, please contact us...



Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com