




Brochure

SNK series Terminal blocks Screw clamp technology


SNK series, terminal blocks

Screw clamp technology



Rely on our expertise

ABB screw clamp technology benefits from 50 years of experience. Billions of our screw clamps have been manufactured and are used worldwide every day.



Qualified for worldwide markets and applications
Eco-designed according to international environmental standards in sustainable development.



A smart design to support your daily connection challenges

Revitalise your electrical installations

Modern. High quality finishing.

Improve marking visibility from any direction

Asymmetrical design offers the best visibility from any direction, +20% marking surface.

Facilitate your rail assembly process

Asymmetrical shape: easy to handle, prevents risk of short-circuit. Stiffness: improved holding adherence to the rail, low deflection when tightening. Locking pin: quick and easy to lock up to ten blocks in position at a time.

Smooth your connecting process


Engineered conductor entry: optimized conductor guiding, easier connection. One or two conductors. Conductors with or without ferrules.

Facilitate maintenance operations

Terminals can be individually removed from a terminal assembly equipped with markers: ABB markers become independent after strip mounting, ABB markers remain on terminal in any situation. Handwriting possible.



Best marking visibility from any direction



Asymmetrical design offers the best visibility



Engineered conductor entry



Maintenance operations facilitated

"Simply SNK"

Find your preferred marking solution from our universal range



ABB automatic printing solutions

ABB marking systems with blank marker cards (2) and self adhesive strips (1).

ABB pre-marking solutions

Pre-printed marker cards (2).



Manual marking solutions

Universal marker holder (UMH), compatible with most of the wire markers available on the market (3).

Patented "flat marking area", compatible with self-adhesive strips and can be written on with a marker pen (4).


Make savings where it counts

Reduce your stock value

Significant reduction of part numbers to manage. Less terminal blocks and accessories needed to do your electrical installation, number of units per pack suited to the usage.

Reduce marking cost

With pre-printed marker cards and strip mounting. Zero investment needed using your current tools: adhesive hand label printer, desktop printers, pen.



SNK series, terminal blocks

PI-Spring and Screw common features

Common Accessories



Compact and screw end stops




Plug-in insulated jumpers



Cross spacing jumpers

PI-Spring and Screw tech

Common smart Design



Asymmetrical Design
avoid mounting errors



Engineered conductor entry
for ease of wiring



Fewer parts to stock
with common end sections



Testing devices



Screwless
component plugs



Blank and pre-marked
markers

Technologies terminal blocks



Disconnect blocks
operated by hand or screwdriver



Convenient jumpering system
up to 50 poles, divisible





Clear terminal block identification
Top large marker. Hand pre-marking
before final marker installation

SNK series, terminal blocks

Applications

Qualified for worldwide markets, applications
and for severe environments: vibration, shock, corrosion...



Industry and Commercial



SNK series terminal blocks can be used worldwide in all types of industrial and commercial applications. All our products have CB, UL and CSA third party certificates delivered by independent laboratories. SNK series products are developed and qualified in accordance with the following international standards: IEC 60947-1, IEC 60947-7-1, IEC 60947-7-2, IEC 60947-7-3, UL 1059, CSA C22.2 n°158-10.



Solar



Thanks to their 1000 V rating per IEC 60947-7-1, SNK terminal blocks are ideally suited for use in solar equipment.

Railways



All SNK series products are suited to trackside fixed equipment. For the more demanding environment of rolling stock applications, PI-Spring has been successfully tested in accordance with IEC 61373 requirements to resist high vibration and shock conditions (multi-axial waves, acceleration...).

The plastic material used is compliant with the flammability, smoke toxicity and opacity severe requirements of the traction segment and can be classified I2F2 per NF F 16-101 and NF F 16-102 standards; HL3 per EN 45 545 standard and V0 per UL94 standard. It complies with NFPA 130 per ASTM E 162 and ASTM E 662 standards tests and with FR238.103 and BSS 7239 standards. The IRIS certificate guarantees the respect of international railway industry requirements.

Hazardous locations



SNK series is certified IEC Ex in accordance with IEC 60079-0 and IEC 60079-7 (increased safety "Exe") world international standards for products used in explosive atmospheres.

In order to serve specific local market requirements, some SNK products have additional local certifications such as: ATEX, UL hazardous Locations or BR-Ex...

SNK products have successfully passed toughest tests like the thermal endurance test: 2 weeks in hot environment (95 °C + 90% RH) followed by 2 weeks (125 °C) and one day cold environment test (-65 °C).

This proves the high mechanical performances of the SNK products.

Marine



SNK products have proven their performance by successfully passing tests required for the most extreme conditions. (eg: salt mist, damp or dry heat and cold environments) per IEC 60068... standards.

In order to serve the worldwide marine markets requirements, SNK products have the following Marine certifications, in particular: BV Marine, DNV, RINA, RMRS.

SNK series, terminal blocks

Screw clamp technology

						Terminal blocks		End sections	Jumper bars		Marking
Type	Function	Cross section	Spacing	Maximum current	Color	Order code		Order code	Nb of poles	Order code	
		IEC UL/CSA									
Feed-through and ground terminal blocks											
 ZS4		 4 mm ² 12 AWG	5.2 mm <i>0.205 in</i>	32 A 20 A	Grey Blue	1SNK505010R0000 1SNK505020R0000			2	1SNK905302R0000	MC512 MC512PA MG-CPM-13
		 2.5 mm ² 14 AWG							3	1SNK905303R0000	
		 4 mm ² 12 AWG							4	1SNK905304R0000	
		 4 mm ² 12 AWG							5	1SNK905305R0000	
 ZS4-PE		 4 mm ² 12 AWG		480 A / 1s 396 A / 1s	Green-yellow	1SNK505150R0000					
		 2.5 mm ² 14 AWG									
		 4 mm ² 12 AWG									
		 4 mm ² 12 AWG									
 ZS6		 6 mm ² 10 AWG	6 mm <i>0.236 in</i>	41 A 30 A	Grey Blue	1SNK506010R0000 1SNK506020R0000			2	1SNK906302R0000	MC612 MC612PA MG-CPM-13
		 4 mm ² 12 AWG							3	1SNK906303R0000	
		 6 mm ² 10 AWG							4	1SNK906304R0000	
		 6 mm ² 10 AWG							5	1SNK906305R0000	
 ZS6-PE		 6 mm ² 10 AWG		720 A / 1s 636 A / 1s	Green-yellow	1SNK506150R0000					
		 4 mm ² 12 AWG									
		 6 mm ² 10 AWG									
		 6 mm ² 10 AWG									
 ZS10		 10 mm ² 6 AWG	8 mm <i>0.315 in</i>	57 A 42 A	Grey Blue	1SNK508010R0000 1SNK508020R0000		1SNK505910R0000 	2	1SNK908302R0000	
		 6 mm ² 10 AWG							3	1SNK908303R0000	
		 10 mm ² 6 AWG							4	1SNK908304R0000	
		 10 mm ² 6 AWG							5	1SNK908305R0000	
 ZS10-PE		 10 mm ² 6 AWG		1200 A / 1s 1596 A / 1s	Green-yellow	1SNK508150R0000		ES4			
		 6 mm ² 10 AWG									
		 10 mm ² 6 AWG									
		 10 mm ² 6 AWG									
 ZS16		 16 mm ² 4 AWG	10 mm <i>0.394 in</i>	76 A 67 A	Grey Blue	1SNK510010R0000 1SNK510020R0000			2	1SNK910302R0000	MC812 MC812PA MG-CPM-13
		 10 mm ² 8 AWG							3	1SNK910303R0000	
		 16 mm ² 4 AWG							4	1SNK910304R0000	
		 16 mm ² 4 AWG							5	1SNK910305R0000	
 ZS16-PE		 16 mm ² 4 AWG		1920 A / 1s 2544 A / 1s	Green-yellow	1SNK510150R0000					
		 10 mm ² 8 AWG									
		 16 mm ² 4 AWG									
		 16 mm ² 4 AWG									
 ZS25		 25 mm ² 3 AWG	12 mm <i>0.472 in</i>	101 A 100 A	Grey Blue	1SNK512010R0000 1SNK512020R0000			2	1SNK912302R0000	
		 16 mm ² 8 AWG							3	1SNK912303R0000	
		 25 mm ² 3 AWG							5	1SNK912305R0000	
		 25 mm ² 3 AWG									
 ZS25-PE		 25 mm ² 3 AWG		1920 A / 1s 3204 A / 1s	Green-yellow	1SNK512150R0000					
		 16 mm ² 8 AWG									
		 25 mm ² 3 AWG									
		 25 mm ² 3 AWG									

All technical data for UL/CSA standards and dimensions in inches are shown in *italics*.

 Flexible (IEC) stranded (UL/CSA) conductor –  Flexible with insulated ferrule –  Rigid conductor

SNK series, terminal blocks

Screw clamp technology

					Terminal blocks		End sections	Jumper bars		Marking					
Type	Function	Cross section	Spacing	Maximum current	Color	Order code	Order code	Nb of poles	Order code						
		IEC	UL/CSA												
Feed-through and ground terminal blocks, closed															
			35 mm ² 0 AWG	16 mm 0.630 in	125 A 150 A	Grey Blue	1SNK516010R0000 1SNK516020R0000	Closed	2	1SNK916302R0000	MC812 MC812PA MG-CPM-13				
			35 mm ² 2 AWG						3	1SNK916303R0000					
			35 mm ² 0 AWG						4	1SNK916304R0000					
	35 mm ² 2 AWG	5	1SNK916305R0000												
			35 mm ² 2 AWG		4200 A / 1s 4032 A / 1s	Green-yellow	1SNK516150R0000		10	1SNK916310R0000					
			35 mm ² 2 AWG												
			35 mm ² 2 AWG												
			70 mm ² 00 AWG						22 mm 0.866 in	192 A 159 A		Grey Blue	1SNK522010R0000 1SNK522020R0000		2
			50 mm ²	3	1SNK922303R0000										
			95 mm ² 00 AWG	5	1SNK922305R0000										
	70 mm ² 00 AWG	10	1SNK922310R0000												
			70 mm ² 00 AWG	8400 A / 1s 8088 A / 1s	Green-yellow	1SNK522150R0000									
			50 mm ²												
			95 mm ² 00 AWG												
			95 mm ² 0000 AWG							26 mm 1.024 in		232 A 230 A	Grey Blue	1SNK526010R0000 1SNK526020R0000	
			50 mm ²	3	1SNK926303R0000										
			120 mm ² 0000 AWG	5	1SNK926305R0000										
	50 mm ²	10	1SNK926310R0000												
			95 mm ² 0000 AWG	11400 A / 1s 12840 A / 1s	Green-yellow	1SNK526150R0000									
			50 mm ²												
			120 mm ² 0000 AWG												
Feed-through and ground terminal blocks - 3 and 4 connections															
			6 mm ² 10 AWG	6 mm 0.236 in	39 A 30 A	Grey Blue	1SNK506011R0000 1SNK506021R0000		 ES6-3S	2		1SNK906302R0000	MC612 MC612PA MG-CPM-13		
			4 mm ² 12 AWG							3		1SNK906303R0000			
			6 mm ² 10 AWG							4		1SNK906304R0000			
	6 mm ² 10 AWG	5	1SNK906305R0000												
			6 mm ² 10 AWG		480 A / 1s 636 A / 1s	Green-yellow	1SNK506151R0000			10	1SNK906310R0000				
			4 mm ² 12 AWG							50	1SNK906350R0000				
			6 mm ² 10 AWG												
			6 mm ² 10 AWG							6 mm 0.236 in	39 A 30 A	Grey Blue		1SNK506012R0000 1SNK506022R0000	 ES6-4S
			4 mm ² 12 AWG	3	1SNK906303R0000										
			6 mm ² 10 AWG	4	1SNK906304R0000										
	6 mm ² 10 AWG	5	1SNK906305R0000												
			6 mm ² 10 AWG	480 A / 1s 636 A / 1s	Green-yellow	1SNK506152R0000		10	1SNK906310R0000						
			4 mm ² 12 AWG					50	1SNK906350R0000						
			6 mm ² 10 AWG												

All technical data for UL/CSA standards and dimensions in inches are shown in *italic*.

 Flexible (IEC) stranded (UL/CSA) conductor –  Flexible with insulated ferrule –  Rigid conductor

SNK series, terminal blocks

Screw clamp technology

						Terminal blocks		End sections		Jumper bars		Marking	
Type	Function	Cross section		Spacing	Maximum current	Color	Order code	Order code	Nb of poles	Order code			
		IEC	UL/CSA										
Double deck terminal blocks													
			4 mm² 12 AWG	5.2 mm 0.205 in	29 A 20 A	Grey	1SNK505210R0000		2	1SNK905302R0000	MC512 MC512PA MG-CPM-13		
			2.5 mm² 14 AWG						3	1SNK905303R0000			
			4 mm² 12 AWG						4	1SNK905304R0000			
			4 mm² 12 AWG				1SNK505211R0000		5	1SNK905305R0000			
			2.5 mm² 14 AWG						10	1SNK905310R0000			
			4 mm² 12 AWG						50	1SNK905350R0000			
			6 mm² 10 AWG		40 A 30 A		1SNK506210R0000						
			4 mm² 12 AWG										
			6 mm² 10 AWG										
			4 mm² 12 AWG	6 mm 0.236 in		Grey	1SNK506211R0000	1SNK505960R0000 	2	1SNK906302R0000	MC612 MC612PA MG-CPM-13		
			6 mm² 10 AWG						3	1SNK906303R0000			
			4 mm² 12 AWG						4	1SNK906304R0000			
			6 mm² 10 AWG		41 A 30 A		1SNK506212R0000	ES4-D2	5	1SNK906305R0000			
			4 mm² 12 AWG						10	1SNK906310R0000			
			6 mm² 10 AWG						50	1SNK906350R0000			
			6 mm² 10 AWG		720 A / 1s 636 A / 1s	Green-yellow	1SNK506250R0000						
			4 mm² 12 AWG										
			6 mm² 10 AWG										
			4 mm² 10 AWG	5.2 mm 0.205 in	25 / 29 A 27 / 27 A	Grey	1SNK505315R0000		2	1SNK905302R0000	MC512 MC512PA MG-CPM-13		
			2.5 mm² 14 AWG						3	1SNK905303R0000			
			4 mm² 10 AWG						4	1SNK905304R0000			
			4 mm² 10 AWG				1SNK505316R0000		5	1SNK905305R0000			
			2.5 mm² 14 AWG						10	1SNK905310R0000			
			4 mm² 10 AWG						50	1SNK905350R0000			
			4 mm² 10 AWG	8 mm 0.315 in	6.3 / 32 A 12 / 30 A	Grey	1SNK508425R0000	1SNK508911R0000 	2	1SNK908302R0000	MC812 MC812PA MG-CPM-13		
			4 mm² 12 AWG						3	1SNK908303R0000			
			6 mm² 10 AWG						4	1SNK908304R0000			
			4 mm² 10 AWG			Grey, dark grey	1SNK508423R0000 1SNK508424R0000	ES4-D2-SF1	5	1SNK908305R0000			
			4 mm² 12 AWG						10	1SNK908310R0000			
			6 mm² 10 AWG										

All technical data for UL/CSA standards and dimensions in inches are shown in italic.

 Flexible (IEC) stranded (UL/CSA) conductor –  Flexible with insulated ferrule –  Rigid conductor

SNK series, terminal blocks

Screw clamp technology

					Terminal blocks		End sections	Jumper bars		Marking
Type	Function	Cross section	Spacing	Maximum current	Color	Order code	Order code	Nb of poles	Order code	
		IEC UL/CSA								
Triple deck terminal blocks										
 ZS4-T3		 4 mm² 12 AWG	5.2 mm 0.205 in	32 A 20 A	Grey	1SNK505212R0000	 ES4-T3	2	1SNK905302R0000	MC512 MC512PA MG-CPM-13
		 2.5 mm² 14 AWG						3	1SNK905303R0000	
		 4 mm² 12 AWG						4	1SNK905304R0000	
 ZS4-T3-R1		 4 mm² 10 AWG	6 mm 0.236 in	32 A 30 A	Grey	1SNK506213R0000	Closed	5	1SNK905310R0000	
		 4 mm² 14 AWG						10	1SNK905350R0000	
		 4 mm² 10 AWG						2	1SNK906302R0000	
		 4 mm² 14 AWG						3	1SNK906303R0000	
		 4 mm² 10 AWG						4	1SNK906304R0000	
								5	1SNK906305R0000	
								10	1SNK906310R0000	
Disconnect terminal blocks, with orange blade										
 ZS4-S		 4 mm² 10 AWG	5.2 mm 0.205 in	25 A 25 A	Grey Blue Orange	1SNK505310R0000 1SNK505320R0000 1SNK505330R0000				MC512 MC512PA MG-CPM-13
		 2.5 mm² 14 AWG								
		 4 mm² 10 AWG								
 ZS4-S-T		 4 mm² 10 AWG			Grey	1SNK505311R0000	 ES4			
		 2.5 mm² 14 AWG								
		 4 mm² 10 AWG								
 ZS6-S		 6 mm² 10 AWG	6 mm 0.236 in	30 A 25 A	Grey Blue	1SNK506315R0000 1SNK506322R0000				MC612 MC612PA MG-CPM-13
		 4 mm² 12 AWG								
		 6 mm² 10 AWG								
 ZS10-S		 10 mm² 6 AWG	8 mm 0.315 in	42 A 25 A	Grey Blue	1SNK508315R0000 1SNK508320R0000				MC812 MC812PA MG-CPM-13
		 6 mm² 12 AWG								
		 10 mm² 6 AWG								
 ZS4-S-R1...		 4 mm² 10 AWG	6 mm 0.236 in	26 A 26 A	Grey Blue Orange	1SNK506310R0000 1SNK506320R0000 1SNK506330R0000	Closed			
		 4 mm² 12 AWG								
		 4 mm² 10 AWG								
 ZS4-S-T2-R1		 4 mm² 12 AWG			Grey	1SNK506311R0000				MC612 MC612PA MG-CPM-13
		 4 mm² 10 AWG								
		 4 mm² 10 AWG								
 ZS6-S-4S-T2		 6 mm² 10 AWG	6 mm 0.236 in	27 A 28 A	Grey	1SNK506316R0000	 ES6-4S			
		 4 mm² 12 AWG								
		 6 mm² 10 AWG								

All technical data for UL/CSA standards and dimensions in inches are shown in *italic*.

 Flexible (IEC) stranded (UL/CSA) conductor –  Flexible with insulated ferrule –  Rigid conductor

SNK series, terminal blocks

Screw clamp technology

					Terminal blocks		End sections	Jumper bars		Marking
Type	Function	Cross section	Spacing	Maximum current	Color	Order code	Order code	Nb of poles	Order code	
		IEC UL/CSA								
Disconnect terminal blocks, with plug										
 ZS4-SP		 4 mm² 10 AWG	5.2 mm 0.205 in	18 A 18 A	Grey	1SNK505313R0000	1SNK505910R0000			MC512 MC512PA MG-CPM-13
		 2.5 mm² 14 AWG								
		 4 mm² 10 AWG								
 ZS4-SP-T2		 4 mm² 10 AWG				1SNK505314R0000	 ES4			
		 2.5 mm² 14 AWG								
		 4 mm² 10 AWG								
 ZS10-SP		 10 mm² 6 AWG	8 mm 0.315 in	18 A 18 A	Grey	1SNK508316R0000				MC812 MC812PA MG-CPM-13
		 6 mm² 8 AWG								
		 10 mm² 6 AWG								
 ZS4-SP-R1		 4 mm² 10 AWG	6 mm 0.236 in	18 A 20 A	Grey	1SNK506313R0000	Closed	2 3 4 5 10	1SNK906302R0000 1SNK906303R0000 1SNK906304R0000 1SNK906305R0000 1SNK906310R0000	MC612 MC612PA MG-CPM-13
		 4 mm² 10 AWG								
		 4 mm² 10 AWG								
 ZS4-SP-T2-R1		 4 mm² 10 AWG				1SNK506314R0000				
		 4 mm² 10 AWG								
		 4 mm² 10 AWG								
 PG5...	Component insertion in series with circuit		5.2 mm 0.205 in		Dark grey	1SNK900401R0000				MC512 MC512PA MG-CPM-13
	Equipped with linking bar			Orange	1SNK900402R0000					
Disconnect terminal blocks, with orange lever										
 ZS4-S-R3		 4 mm² 10 AWG	8 mm 0.315 in	18 A 18 A	Grey, orange	1SNK508416R0000	1SNK508960R0000			MC812 MC812PA MG-CPM-13
		 4 mm² 12 AWG								
		 4 mm² 10 AWG								
 ZS4-S-R2		 4 mm² 10 AWG	6 mm 0.236 in	18 A 13 A	Grey, orange	1SNK506414R0000	Closed	2 3 4 5 10	1SNK906302R0000 1SNK906303R0000 1SNK906304R0000 1SNK906305R0000 1SNK906310R0000	MC612 MC612PA MG-CPM-13
		 4 mm² 12 AWG								
		 4 mm² 10 AWG								
 ZS10-S-R2		 10 mm² 6 AWG	8 mm 0.315 in	10 A 22 A	Grey, orange	1SNK508417R0000		2 3 4 5 10	1SNK908302R0000 1SNK908303R0000 1SNK908304R0000 1SNK908305R0000 1SNK908310R0000	MC812 MC812PA MG-CPM-13
		 6 mm² 10 AWG								
		 10 mm² 6 AWG								
Fuse holder terminal blocks - For 5x20 mm 0.197x0.787 in and 5x25 mm 0.197x0.984 in fuses										
 ZS4-SF1...		 4 mm² 10 AWG	8 mm 0.315 in	6.3 A 10 A	Grey, dark grey	1SNK508410R0000	1SNK508960R0000			MC812 MC812PA MG-CPM-13
		 4 mm² 12 AWG				1SNK508411R0000				
		 4 mm² 10 AWG				1SNK508412R0000				
		 4 mm² 10 AWG				1SNK508413R0000 1SNK508414R0000 1SNK508415R0000				
						ES4-SF				

All technical data for UL/CSA standards and dimensions in inches are shown in italic.

 Flexible (IEC) stranded (UL/CSA) conductor –  Flexible with insulated ferrule –  Rigid conductor

SNK series, terminal blocks

Screw clamp technology

					Terminal blocks		End sections	Jumper bars		Marking
Type	Function	Cross section	Spacing	Maximum current	Color	Order code	Order code	Nb of poles	Order code	
		IEC <i>UL/CSA</i>								
Fuse holder terminal blocks - For 5x20 mm 0.197x0.787 in fuses and marshalling cabinets applications										
 ZS4-SF...		 4 mm ² 10 AWG	6 mm 0.236 in	6.3 A 10 A	Grey, dark grey	1SNK506410R0000 1SNK506411R0000 1SNK506412R0000 1SNK506413R0000 1SNK506415R0000 1SNK506416R0000	Closed	2 3 4 5 10	1SNK906302R0000 1SNK906303R0000 1SNK906304R0000 1SNK906305R0000 1SNK906310R0000	MC612 MC612PA MG-CPM-13
		 4 mm ² 12 AWG								
		 4 mm ² 10 AWG								
		 4 mm ² 12 AWG								
		 4 mm ² 10 AWG								
 ZS4-R2		 4 mm ² 10 AWG	6 mm 0.236 in	32 A 30 A	Grey	1SNK506013R0000	Closed	2 3 4 5 10	1SNK906302R0000 1SNK906303R0000 1SNK906304R0000 1SNK906305R0000 1SNK906310R0000	MC612 MC612PA MG-CPM-13
		 4 mm ² 12 AWG								
		 4 mm ² 10 AWG								
 ZS4-PE-R2		 4 mm ² 10 AWG	6 mm 0.236 in	480 A / 1s 396 A / 1s	Green- Yellow	1SNK506153R0000	1SNK505911R0000  ES6-4S			
		 4 mm ² 12 AWG								
		 4 mm ² 10 AWG								
 4 mm ² 10 AWG										
Fuse holder terminal blocks - For 6.3x32 mm 1/4 x 1 1/4 in fuses										
 ZS10-SF		 10 mm ² 6 AWG	8 mm 0.315 in	10 A 22 A	Grey, dark grey	1SNK508418R0000	Closed	2 3 4 5 10	1SNK908302R0000 1SNK908303R0000 1SNK908304R0000 1SNK908305R0000 1SNK908310R0000	MC812 MC812PA MG-CPM-13
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								
 ZS10-SF-R		 10 mm ² 6 AWG	8 mm 0.315 in	10 A 22 A	Grey, dark grey	1SNK508421R0000 1SNK508422R0000	Closed	2 3 4 5 10	1SNK908302R0000 1SNK908303R0000 1SNK908304R0000 1SNK908305R0000 1SNK908310R0000	MC812 MC812PA MG-CPM-13
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								
 10 mm ² 6 AWG										
Test and measurement										
 ZS10-ST		 10 mm ² 6 AWG	8 mm 0.315 in	50 A 53 A	Grey	1SNK508310R0000	Closed	2 3 4 5 10	1SNK908902R0000 1SNK908903R0000 1SNK908904R0000 1SNK908905R0000 1SNK908910R0000	MC812 MC812PA MG-CPM-13
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								
 ZS10-ST-1		 10 mm ² 6 AWG	8 mm 0.315 in	50 A 53 A	Grey	1SNK508312R0000	1SNK508910R0000  ES10-ST	2 3 4 5 10	1SNK908902R0000 1SNK908903R0000 1SNK908904R0000 1SNK908905R0000 1SNK908910R0000	MC812 MC812PA MG-CPM-13
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								
 ZS10-ST-T4		 10 mm ² 6 AWG	8 mm 0.315 in	50 A 53 A	Grey	1SNK508311R0000	Closed	2 3 4 5 10	1SNK908902R0000 1SNK908903R0000 1SNK908904R0000 1SNK908905R0000 1SNK908910R0000	MC812 MC812PA MG-CPM-13
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								
 ZS10-R1		 10 mm ² 6 AWG	8 mm 0.315 in	57 A 62 A	Grey	1SNK508011R0000	Closed	2 3 4 5 10	1SNK908902R0000 1SNK908903R0000 1SNK908904R0000 1SNK908905R0000 1SNK908910R0000	MC812 MC812PA MG-CPM-13
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								
 ZS10-PE-R1		 10 mm ² 6 AWG	8 mm 0.315 in	1200 A / 1s 1596 A / 1s	Green- Yellow	1SNK508151R0000	Closed	2 3 4 5 10	1SNK908902R0000 1SNK908903R0000 1SNK908904R0000 1SNK908905R0000 1SNK908910R0000	MC812 MC812PA MG-CPM-13
		 6 mm ² 10 AWG								
		 10 mm ² 6 AWG								

All technical data for UL/CSA standards and dimensions in inches are shown in *italic*.

 Flexible (IEC) stranded (UL/CSA) conductor –  Flexible with insulated ferrule –  Rigid conductor

SNK series, terminal blocks

Accessories

Type	Rail	Description	Spacing	Rated current	Color	Order code	Color	Order code				
End stops							Label holders					
 BAM3	TH 35-7.5 TH 35-15	Screw end stop	10 mm 0.394 in		Dark grey	1SNK900001R0000	Dark grey	10 mm 0.394 in width 1SNK900605R0000				
 BAZ1	TH 35-7.5 TH 35-15	Screwless end stop	5.2 mm 0.205 in		Dark grey	1SNK900002R0000		LH				
 BAZH1	TH 35-7.5 TH 35-15	High end stop for double deck or power terminal blocks	10 mm 0.394 in		Dark grey	1SNK900102R0000		19.5 mm 0.768 in width 1SNK900607R0000				
									 LH-R1			
Circuit separators												
 CS	TH 35-7.5 TH 35-15	Compatible with feed-through terminal blocks up to 16 mm² 4 AWG	0 mm 0 in		Dark grey	1SNK900101R0000						
 CS-R1	TH 35-7.5 TH 35-15	Compatible with feed-through terminal blocks up to 35 mm² 0 AWG	3 mm 0.118 in		Dark grey	1SNK900103R0000						
Test adaptors												
	TP2	Test adaptor for test plug Ø 2 or 2.3 mm (0.079 in or 0.091 in)			Dark grey	1SNK900203R0000						
	TP4	Test adaptor for test plug Ø 4 mm (0.157 in)			Dark grey	1SNK900205R0000						
Test connectors												
	TC5	Test connector	5.2 mm 0.205 in	1.5 mm² 16 AWG	Dark grey	1SNK900200R0000						
	TC5-R1	End module for test connector	5.2 mm 0.205 in	1.5 mm² 16 AWG	Dark grey	1SNK900201R0000						
Component plugs												
 PG5-R2		Component plug-in (between 2 blocks with 5.2 mm 0.205 in spacing)	2 x 5.2 mm 2 x 0.205 in		Dark grey	1SNK900403R0000						
Shield connectors												
		Compatible with ZS feed-through and double deck terminal blocks				1SNK900600R0000						
						1SNK900602R0000						
SHBS / SHB												
Protecting covers												
 CO		1 m 39.4 in length spacing			Trans-parent	1SNK900604R0000						
 PL		5.2 mm 0.205 in spacing			Trans-parent	1SNK900618R0000						
		6 mm 0.236 in spacing				1SNK900619R0000						
		8 mm 0.315 in spacing				1SNK900620R0000						
		10 mm 0.394 in spacing				1SNK900621R0000						
		16 mm 0.630 in spacing				1SNK900622R0000						

SNK series, terminal blocks

Markers and marking systems

Markers for terminal blocks

Type	Nb of markers per card	Terminal block spacing				Marking systems			Order code	Pkg qty	
		5.2 mm 0.205 in	6 mm 0.236 in	8 mm 0.315 in	> 8 mm > 0.315 in	HTP500-V2	MG3	AMS 250 AMS 500		cards	markers
Blank markers (white)											
MC512	45	●	○	○	○	●			1SNK140000R0000	22	
MC512PA	100	●	○	○	○			●	1SNK149999R0000	20	
MG-CPM-13 41790	56	●	○	○	○		●		1SNB041790R0512		1960
MC612	39		●	○	○	●			1SNK150000R0000	22	
MC612PA	100		●	○	○			●	1SNK159999R0000	20	
MG-CPM-13 41791	48		●	○	○		●		1SNB041791R0612		1680
MC812	30			●	●	●			1SNK160000R0000	22	
MC812PA	100			●	●			●	1SNK169999R0000	20	
Pre-marked marker cards (white)						Marking type					
MC512PA	100	●	○	○	○	1->10 (x10) 1->100			1SNK140011R0000 1SNK145011R0000	1	
MC612PA	100		●	○	○	1->10 (x10) 1->100			1SNK150011R0000 1SNK155011R0000	1	
MC812PA	100			●	●	1->10 (x10) 1->100			1SNK160011R0000 1SNK165011R0000	1	

● Recommended ○ Compatible

Universal marker holder for wire markers

Type	Nb of markers per card	Wire external diameter		Wire section		Spacing	Order code	Pkg qty	
		mm	in	mm²	AWG			strips	markers
UMH	Strip of 10 universal wire marker holders for terminal blocks					5.2 mm 0.205 in	1SNK900611R0000	10	
4 x 12 mm (0.157 in x 0.472 in) wire marker									
MG2-TDMO-01 40390	40	2...2.9	0.079...0.114	0.5...1.5	20...16		1SNB040390R0412		880
MG2-TDMO-02 40490	40	2.9...3.5	0.114...0.138	1.5...2.5	16...14		1SNB040490R0412		640
MG2-TDMO-03 40590	40	4...4.6	0.157...0.181	4...6	12...10		1SNB040590R0412		560
4 x 16 mm (0.157 in x 0.630 in) wire marker									
MG2-TDMO-01 40391	40	2...2.9	0.079...0.114	0.5...1.5	18...16		1SNB040391R0416		880
MG2-TDMO-02 40491	40	2.9...3.5	0.114...0.138	1.5...2.5	16...14		1SNB040491R0416		640
MG2-TDMO-03 40591	40	4...4.6	0.157...0.181	4...6	12...10		1SNB040591R0416		560

Label for end stops

Type	Nb of markers per card	Color	Compatible with label holder		Marking systems			Order code	Pkg qty	
			LH	LH-R1	HTP500-V2	MG3	AMS 250 AMS 500		cards	markers
Blank marker cards (white)										
MCLH	36	White	●		●		●	1SNK900630R0000	25	
MCLH-R1	15			●	●		●	1SNK900631R0000	25	
MG-TAA 49198	18			●		●		1SNB049198R1735	25	
MG-TAA 49498	33	Yellow	●					1SNB049498R8530	25	
MCLH-YL	36		●		●		●	1SNK900633R0000	25	
MCLH-R1-YL	15			●	●		●	1SNK900634R0000	25	

● Recommended ○ Compatible

Marking systems



HTP500-V2, Thermal transfer printer



MG3, Thermal transfer printer



AMS 500 and AMS 250 plotter



UMH is compatible with most of the wire markers available on the market.



MG2-TDMO...



LH + MCLH




LH-R1 + MCLH-R1

Index

Additional technical data

Terminal block dimensions
(add rail height to obtain mounted dimensions)
e.g. TH 35-7.5 rail = product height + 7.5 mm



Other products (not mounted on rail)

Order code	Type	Description	Rated voltage (IEC) V	Rated voltage (UL/CSA) V	Length mm	Height mm	Units per box	Units per carton	Page
1SNB040390R0412	MG2-TDMO-01 40390	Terminal block markers	-	-	12	4	880	-	15
1SNB040391R0416	MG2-TDMO-01 40391	Terminal block markers	-	-	16	4	880	-	15
1SNB040490R0412	MG2-TDMO-01 40490	Terminal block markers	-	-	12	4	640	-	15
1SNB040491R0416	MG2-TDMO-01 40491	Terminal block markers	-	-	16	4	640	-	15
1SNB040590R0412	MG2-TDMO-01 40590	Terminal block markers	-	-	12	4	560	-	15
1SNB040591R0416	MG2-TDMO-01 40591	Terminal block markers	-	-	16	4	560	-	15
1SNB041790R0512	MG-CPM-13 41790	Terminal block markers	-	-	12	5	1960	-	15
1SNB041791R0612	MG-CPM-13 41791	Terminal block markers	-	-	12	6	1680	-	15
1SNB049198R1735	MG-TAA 49198	Terminal block markers	-	-	35	17	450	-	15
1SNB049498R8530	MG-TAA 49498	Terminal block markers	-	-	30	8.5	825	-	15
1SNK140000R0000	MC512	Terminal block markers	-	-	12	5	22	990	15
1SNK140011R0000	MC512PA	Terminal block markers	-	-	12	5	1	600	15
1SNK145011R0000	MC512PA	Terminal block markers	-	-	12	5	1	600	15
1SNK149999R0000	MC512PA	Terminal block markers	-	-	12	5	1	600	15
1SNK150000R0000	MC612	Terminal block markers	-	-	12	6	22	858	15
1SNK150011R0000	MC612PA	Terminal block markers	-	-	12	6	1	600	15
1SNK155011R0000	MC612PA	Terminal block markers	-	-	12	6	1	600	15
1SNK159999R0000	MC612PA	Terminal block markers	-	-	12	6	1	600	15
1SNK160000R0000	MC812	Terminal block markers	-	-	12	8	22	660	15
1SNK160011R0000	MC812PA	Terminal block markers	-	-	12	8	1	600	15
1SNK165011R0000	MC812PA	Terminal block markers	-	-	12	8	1	600	15
1SNK169999R0000	MC812PA	Terminal block markers	-	-	12	8	1	600	15
1SNK505010R0000	ZS4	Screw clamp terminal blocks	1000	600	53	41.3	50	900	8
1SNK505020R0000	ZS4-BL	Screw clamp terminal blocks	1000	600	53	41.3	50	900	8
1SNK505150R0000	ZS4-PE	Screw clamp terminal blocks			59.5	41.4	20	420	8
1SNK505210R0000	ZS4-D2	Screw clamp terminal blocks	800	300	70.4	59.5	50	400	10
1SNK505211R0000	ZS4-D1	Screw clamp terminal blocks	800	300	70.4	59.5	50	400	10
1SNK505212R0000	ZS4-T3	Screw clamp terminal blocks	800	300	100.1	72.4	25	350	11
1SNK505310R0000	ZS4-S	Screw clamp terminal blocks	400	150	53	45.4	50	900	11
1SNK505311R0000	ZS4-S-T2	Screw clamp terminal blocks	400	150	53	45.4	50	900	11
1SNK505313R0000	ZS4-SP	Screw clamp terminal blocks	400	150	53	41.3	50	900	12
1SNK505314R0000	ZS4-SP-T2	Screw clamp terminal blocks	400	150	53	41.3	50	900	12
1SNK505315R0000	ZS4-D2-S	Screw clamp terminal blocks	630	300	70.4	63.6	50	400	10
1SNK505316R0000	ZS4-D2-S-T2	Screw clamp terminal blocks	630	300	70.4	63.6	50	400	10
1SNK505320R0000	ZS4-S-BL	Screw clamp terminal blocks	400	150	53	45.4	50	900	11
1SNK505330R0000	ZS4-S-OR	Screw clamp terminal blocks	400	150	53	45.4	50	900	11
1SNK505910R0000	ES4	End sections	-	-	50.9	33.7	20	-	8
1SNK505911R0000	ES6-4S	End sections	-	-	70.6	33.7	20	-	9
1SNK505912R0000	ES6-3S	End sections	-	-	59.9	33.7	20	-	9
1SNK505960R0000	ES4-D2	End sections	-	-	70.2	59.2	20	-	10
1SNK505961R0000	ES4-T3	End sections	-	-	97	81.2	20	-	11
1SNK506010R0000	ZS6	Screw clamp terminal blocks	1000	600	53	41.3	50	750	8
1SNK506011R0000	ZS6-3S	Screw clamp terminal blocks	800	600	62	42.2	50	400	9
1SNK506012R0000	ZS6-4S	Screw clamp terminal blocks	800	600	72.7	42.2	50	300	9
1SNK506013R0000	ZS4-R2	Screw clamp terminal blocks	800	300	70.5	41.3	50	600	13
1SNK506020R0000	ZS6-BL	Screw clamp terminal blocks	1000	600	53	41.3	50	750	8
1SNK506021R0000	ZS6-3S-BL	Screw clamp terminal blocks	800	600	62	42.2	50	400	9
1SNK506022R0000	ZS6-4S-BL	Screw clamp terminal blocks	800	600	72.7	42.2	50	300	9
1SNK506150R0000	ZS6-PE	Screw clamp terminal blocks			59.5	41.4	20	360	8
1SNK506151R0000	ZS6-3S-PE	Screw clamp terminal blocks			68.5	42.2	25	450	9
1SNK506152R0000	ZS6-4S-PE	Screw clamp terminal blocks			79.2	42.2	25	450	9
1SNK506153R0000	ZS4-PE-R2	Screw clamp terminal blocks			77	41.3	25	450	13
1SNK506210R0000	ZS6-D2	Screw clamp terminal blocks	800	300	70.4	59.5	50	400	10
1SNK506211R0000	ZS6-D1	Screw clamp terminal blocks	800	300	70.4	59.5	50	400	10
1SNK506212R0000	ZS6-D2-PE	Screw clamp terminal blocks	800	300	70.4	59.5	50	300	10
1SNK506213R0000	ZS4-T3-R1	Screw clamp terminal blocks	800	300	100.1	72.4	25	350	11

Index

Additional technical data

Order code	Type	Description	Rated voltage (IEC) V	Rated voltage (UL/CSA) V	Length mm	Height mm	Units per box	Units per carton	Page
1SNK506250R0000	ZS6-D1-PE	Screw clamp terminal blocks			70.4	59.5	50	180	10
1SNK506310R0000	ZS4-S-R1	Screw clamp terminal blocks	400	150	70.5	45.4	50	600	11
1SNK506311R0000	ZS4-S-T2-R1	Screw clamp terminal blocks	400	150	70.5	45.4	50	600	11
1SNK506313R0000	ZS4-SP-R1	Screw clamp terminal blocks	400	150	70.5	41.3	50	600	12
1SNK506314R0000	ZS4-SP-T2-R1	Screw clamp terminal blocks	400	150	70.5	41.3	50	600	12
1SNK506315R0000	ZS6-S	Screw clamp terminal blocks	500	150	53	45.4	50	750	11
1SNK506316R0000	ZS6-S-4S-T2	Screw clamp terminal blocks	500	300	80.7	45.4	50	300	11
1SNK506320R0000	ZS4-S-R1-BL	Screw clamp terminal blocks	400	150	70.5	45.4	50	600	11
1SNK506322R0000	ZS6-S-BL	Screw clamp terminal blocks	500	150	53	45.4	50	750	11
1SNK506330R0000	ZS4-S-R1-OR	Screw clamp terminal blocks	400	150	70.5	45.4	50	600	11
1SNK506410R0000	ZS4-SF	Screw clamp terminal blocks	500	150	70.5	70.8	50	400	13
1SNK506411R0000	ZS4-SF-T2	Screw clamp terminal blocks	500	150	70.5	70.8	50	400	13
1SNK506412R0000	ZS4-SF-R1	Screw clamp terminal blocks	500	150	70.5	70.8	50	400	13
1SNK506413R0000	ZS4-SF-R2	Screw clamp terminal blocks	500	150	70.5	70.8	50	400	13
1SNK506414R0000	ZS4-S-R2	Screw clamp terminal blocks	400	150	70.5	70.8	50	400	12
1SNK506415R0000	ZS4-SF-R3	Screw clamp terminal blocks	500	150	70.5	70.8	50	400	13
1SNK506416R0000	ZS4-SF-R4	Screw clamp terminal blocks	500	150	70.5	70.8	50	400	13
1SNK508010R0000	ZS10	Screw clamp terminal blocks	1000	600	53	41.3	50	600	8
1SNK508011R0000	ZS10-R1	Screw clamp terminal blocks	630	300	80.7	46	25	250	13
1SNK508020R0000	ZS10-BL	Screw clamp terminal blocks	1000	600	53	41.3	50	600	8
1SNK508150R0000	ZS10-PE	Screw clamp terminal blocks			59.5	41.3	20	240	8
1SNK508151R0000	ZS10-PE-R1	Screw clamp terminal blocks			80.7	46	25	250	13
1SNK508310R0000	ZS10-ST	Screw clamp terminal blocks	630	300	80.7	46	25	250	13
1SNK508311R0000	ZS10-ST-T4	Screw clamp terminal blocks	630	300	80.7	55.1	25	250	13
1SNK508312R0000	ZS10-ST-1	Screw clamp terminal blocks	630	300	80.7	46	25	250	13
1SNK508315R0000	ZS10-S	Screw clamp terminal blocks	630	150	53	45.4	50	600	11
1SNK508316R0000	ZS10-SP	Screw clamp terminal blocks	630	150	53	41.3	50	600	12
1SNK508320R0000	ZS10-S-BL	Screw clamp terminal blocks	630	150	53	45.4	50	600	11
1SNK508410R0000	ZS4-SF1	Screw clamp terminal blocks	630	300	59.7	39.6	50	450	12
1SNK508411R0000	ZS4-SF1-T2	Screw clamp terminal blocks	630	300	59.7	39.6	50	450	12
1SNK508412R0000	ZS4-SF1-R1	Screw clamp terminal blocks	630	300	59.7	39.6	50	450	12
1SNK508413R0000	ZS4-SF1-R2	Screw clamp terminal blocks	630	300	59.7	39.6	50	450	12
1SNK508414R0000	ZS4-SF1-R3	Screw clamp terminal blocks	630	300	59.7	39.6	50	450	12
1SNK508415R0000	ZS4-SF1-R4	Screw clamp terminal blocks	630	300	59.7	39.6	50	450	12
1SNK508416R0000	ZS4-S-R3	Screw clamp terminal blocks	500	300	59.7	39.6	50	450	12
1SNK508417R0000	ZS10-S-R2	Screw clamp terminal blocks	630	600	74.3	70.3	50	450	12
1SNK508418R0000	ZS10-SF	Screw clamp terminal blocks	630	600	74.3	70.3	50	450	13
1SNK508421R0000	ZS10-SF-R1	Screw clamp terminal blocks	630	600	74.3	70.3	50	450	13
1SNK508422R0000	ZS10-SF-R3	Screw clamp terminal blocks	630	600	74.3	70.3	50	450	13
1SNK508423R0000	ZS4-D2-SF1-R1	Screw clamp terminal blocks	800	300	89.2	60.5	50	200	10
1SNK508424R0000	ZS4-D2-SF1-R3	Screw clamp terminal blocks	800	300	89.2	60.5	50	200	10
1SNK508425R0000	ZS4-D2-SF1	Screw clamp terminal blocks	800	300	89.2	60.5	50	200	10
1SNK508910R0000	ES10-ST	End sections	-	-	79	38.7	20	-	13
1SNK508911R0000	ES4-D2-SF1	End sections	-	-	84.5	63.1	20	-	10
1SNK508960R0000	ES4-SF	End sections	-	-	59	31.9	20	-	12
1SNK510010R0000	ZS16	Screw clamp terminal blocks	1000	600	56.1	42.8	25	450	8
1SNK510020R0000	ZS16-BL	Screw clamp terminal blocks	1000	600	56.1	42.8	25	450	8
1SNK510150R0000	ZS16-PE	Screw clamp terminal blocks			60.6	42.8	20	160	8
1SNK512010R0000	ZS25	Screw clamp terminal blocks	1000	600	56.1	42.8	25	200	8
1SNK512020R0000	ZS25-BL	Screw clamp terminal blocks	1000	600	56.1	42.8	25	200	8
1SNK512150R0000	ZS25-PE	Screw clamp terminal blocks			63.6	42.8	20	300	8
1SNK516010R0000	ZS35	Screw clamp terminal blocks	1000	600	59	48.3	20	80	9
1SNK516020R0000	ZS35-BL	Screw clamp terminal blocks	1000	600	59	48.3	20	80	9
1SNK516150R0000	ZS35-PE	Screw clamp terminal blocks			59	48.3	20	80	9
1SNK522010R0000	ZS70	Screw clamp terminal blocks	1000	600	74	67.5	10	30	9
1SNK522020R0000	ZS70-BL	Screw clamp terminal blocks	1000	600	74	67.5	10	30	9
1SNK522150R0000	ZS70-PE	Screw clamp terminal blocks			74	67.6	10	30	9
1SNK526010R0000	ZS95	Screw clamp terminal blocks	1000	600	87	74.1	10	30	9
1SNK526020R0000	ZS95-BL	Screw clamp terminal blocks	1000	600	87	74.1	10	30	9
1SNK526150R0000	ZS95-PE	Screw clamp terminal blocks			87	79.2	10	30	9
1SNK900001R0000	BAM3	End stops	-	-	53.5	35	50	1000	14
1SNK900002R0000	BAZ1	End stops	-	-	54.4	34.2	50	750	14
1SNK900101R0000	CS	Circuit separators	-	-	-	-	20	-	14
1SNK900102R0000	BAZH1	End stops	-	-	74.4	30.2	20	360	14
1SNK900103R0000	CS-R1	Circuit separators	-	-	71	54	20	-	14
1SNK900200R0000	TC5	Test connectors	1000	-	34.1	71.7	10	1000	14
1SNK900201R0000	TC5-R1	Test connectors	1000	-	34.1	71.7	10	700	14

Index

Additional technical data


Order code	Type	Description	Rated voltage (IEC) V	Rated voltage (UL/CSA) V	Length mm	Height mm	Units per box	Units per carton	Page
1SNK900203R0000	TP2	Test adaptaters	1000	600	7.6	52.2	20	2000	14
1SNK900205R0000	TP4	Test adaptaters	1000	600	7.6	56.6	20	2000	14
1SNK900401R0000	PG5	Component plugs	400	150	31	39	20	1000	12
1SNK900402R0000	PG5-R1	Component plugs	400	150	31	39	20	2000	12
1SNK900403R0000	PG5-R2	Component plugs	250	-	37.7	48.9	20	160	14
1SNK900600R0000	SHBS	Shield connectors	-	-	-	-	20	-	14
1SNK900602R0000	SHB	Shield connectors	-	-	-	-	20	-	14
1SNK900604R0000	CO	Protecting covers	-	-	77	30.2	1	-	14
1SNK900605R0000	LH	Label holders	-	-	31.8	29.5	50	2500	14
1SNK900607R0000	LH-R1	Label holders	-	-	37.25	29.5	50	1000	14
1SNK900611R0000	UMH	Universal wire markers holder	-	-	-	-	10	-	15
1SNK900618R0000	PL5	Protecting covers	-	-	-	-	10	-	14
1SNK900619R0000	PL6	Protecting covers	-	-	-	-	10	-	14
1SNK900620R0000	PL8	Protecting covers	-	-	-	-	10	-	14
1SNK900621R0000	PL10	Protecting covers	-	-	-	-	10	-	14
1SNK900622R0000	PL16	Protecting covers	-	-	-	-	10	-	14
1SNK900630R0000	MCLH	Label for end stops	-	-	30	8.8	25	-	15
1SNK900631R0000	MCLH-R1	Label for end stops	-	-	35.4	17.7	25	-	15
1SNK900633R0000	MCLH-YL	Label for end stops	-	-	30	8.8	25	-	15
1SNK900634R0000	MCLH-R1-YL	Label for end stops	-	-	35.4	17.7	25	-	15
1SNK905302R0000	JB5-2	Jumper bars	1000	600	8.2	26.8	50	1500	8
1SNK905303R0000	JB5-3	Jumper bars	1000	600	13.4	26.8	50	1500	8
1SNK905304R0000	JB5-4	Jumper bars	1000	600	18.6	26.8	50	1500	8
1SNK905305R0000	JB5-5	Jumper bars	1000	600	23.8	26.8	50	1500	8
1SNK905310R0000	JB5-10	Jumper bars	1000	600	49.8	26.8	30	900	8
1SNK905350R0000	JB5-50	Jumper bars	1000	600	258	26.8	10	150	8
1SNK906302R0000	JB6-2	Jumper bars	1000	600	9	26.8	50	1500	8
1SNK906303R0000	JB6-3	Jumper bars	1000	600	15	26.8	50	1500	8
1SNK906304R0000	JB6-4	Jumper bars	1000	600	21	26.8	50	1500	8
1SNK906305R0000	JB6-5	Jumper bars	1000	600	27	26.8	50	1500	8
1SNK906310R0000	JB6-10	Jumper bars	1000	600	57	26.8	20	600	8
1SNK906350R0000	JB6-50	Jumper bars	1000	600	297	26.8	10	150	8
1SNK908302R0000	JB8-2	Jumper bars	1000	600	13.6	27.8	50	1500	8
1SNK908303R0000	JB8-3	Jumper bars	1000	600	21.6	27.8	50	1500	8
1SNK908304R0000	JB8-4	Jumper bars	1000	600	29.6	27.8	50	1500	8
1SNK908305R0000	JB8-5	Jumper bars	1000	600	37.6	27.8	40	1200	8
1SNK908310R0000	JB8-10	Jumper bars	1000	600	77.6	27.8	20	600	8
1SNK908902R0000	JB8-10-R1	Jumper bars	-	-	-	-	10	-	13
1SNK908903R0000	JB8-3-R1	Jumper bars	-	-	-	-	10	-	13
1SNK908904R0000	JB8-4-R1	Jumper bars	-	-	-	-	10	-	13
1SNK908905R0000	JB8-5-R1	Jumper bars	-	-	-	-	10	-	13
1SNK908910R0000	JB8-2-R1	Jumper bars	-	-	-	-	10	-	13
1SNK910302R0000	JB10-2	Jumper bars	1000	600	18.5	31.5	50	1500	8
1SNK910303R0000	JB10-3	Jumper bars	1000	600	28	31.5	50	1500	8
1SNK910304R0000	JB10-4	Jumper bars	1000	600	30.8	31.5	40	1200	8
1SNK910305R0000	JB10-5	Jumper bars	1000	600	48	31.5	30	900	8
1SNK910310R0000	JB10-10	Jumper bars	1000	600	98	31.5	20	600	8
1SNK912302R0000	JB12-2	Jumper bars	1000	600	20	31.5	50	-	8
1SNK912303R0000	JB12-3	Jumper bars	1000	600	32	31.5	50	-	8
1SNK912305R0000	JB12-5	Jumper bars	1000	600	56	31.5	20	-	8
1SNK916302R0000	JB16-2	Jumper bars	1000	600	-	-	10	-	9
1SNK916303R0000	JB16-3	Jumper bars	1000	600	-	-	10	-	9
1SNK916304R0000	JB16-4	Jumper bars	1000	600	-	-	10	-	9
1SNK916305R0000	JB16-5	Jumper bars	1000	600	-	-	10	-	9
1SNK916310R0000	JB16-10	Jumper bars	1000	600	-	-	10	-	9
1SNK922302R0000	JB22-2	Jumper bars	1000	600	-	-	5	-	9
1SNK922303R0000	JB22-3	Jumper bars	1000	600	-	-	5	-	9
1SNK922305R0000	JB22-5	Jumper bars	1000	600	-	-	5	-	9
1SNK922310R0000	JB22-10	Jumper bars	1000	600	-	-	5	-	9
1SNK926302R0000	JB26-2	Jumper bars	1000	600	-	-	5	-	9
1SNK926303R0000	JB26-3	Jumper bars	1000	600	-	-	5	-	9
1SNK926305R0000	JB26-5	Jumper bars	1000	600	-	-	5	-	9
1SNK926310R0000	JB26-10	Jumper bars	1000	600	-	-	5	-	9

SNK series, terminal blocks


Marketing material

www.abb.com/connecttocontrol
www.abb.com


Products → Low Voltage Products and Systems → Connection Devices



Tools



For product detailed information,
 use product type or order code, ex:
www.abb.com/productdetails/ZS4 or
www.abb.com/productdetails/1SNK505010R0000



Cadenas portal: Download 2D or 3D files
 according to your needs (STEP, IGES...)

Catalogs



New

SNK series terminal blocks in your pocket



The eBinder gives you
 all the information
 you need.

Always updated
 Always available
 Stay connected!

Contact us

ABB France

Low Voltage Products Division

3, rue Jean Perrin

F-69687 Chassieu cedex / France

You can find the address of your local sales organisation
on the ABB home page



www.abb.com/connecttocontrol



www.abb.com/lowvoltage

Note

We reserve the right to make technical changes or modify the contents of this document without prior notice.

ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB.

Copyright© 2013 ABB - All rights reserved