


# **Honeywell Sensing and Control**

Home> Products > Power-duty Rocker Switches > TP > Product Page

### Order Product and **Get Support**

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

#### 1TP7-7-BK



TP Series Rocker Switch, 1 pole, 3 position, Screw terminal, Above Panel Mounting

Actual product appearance may vary.

## **Features**

Environmentally sealed Two and three-position pushbutton action Various button colors 1, 2, and 4-pole circuitry Flush panel and above panel mountings Temperature range: -54 ? C to +71? C [-65 ? F to +160 ? F]

UL recognized, CSA certified

Industrial machinery and equipment Military and commercial aviation Marine applications Construction equipment Test instruments Agricultural machinery Process control

#### **Potential Applications**

Medical instrumentation

# Description

CE approved

MICRO SWITCH™ TP Rocker switches may be mounted flush with panel for a lowbutton profile or above panel for a distinct button appearance. Buttons measure 22,1 mm x 37,1 mm [.87 in x 1.46 in]. They are removable and interchangeable, anc come in transparent plastic, translucent plastic, and six colors of opaque plastic. Switches without buttons are also available, as well as separate buttons.

# **Supporting Documentation**

Accessory: Rocker **Operator** 

Product Specifications		
Circuitry/Operating action	Keyway Momentary Center Position Position 1 2 3 1 2 3 ON OFF	Opposite Keyway Momentary Position 1 2 3 ON
Product Type	MICRO SWITCH™ Rocker	
Ampere/Voltage Range (Resistive Load)	0.75 A at 115 Vdc,0.5 A at 250 Vdc,0.5 A to 10 A at 0.5 Vac to 277 Vac,0.5 A to 15 A at 0.5 Vdc to 28 Vdc	
Circuitry	SPDT	
Action	3 position	
Mounting	Above Panel	
Termination	Screw	
Button Type	No button	
UL/CSA Rating Code	L192: 10 A -125, 250, 277 Vac; 1/4 Hp Hp -250, 277 Vac; 3 A -125 Vac "L"	-125 Vac; 1/2
Comment	Silver cadmium oxide contacts	
Availability	Global	
UNSPSC Code	302119	
UNSPSC Commodity	302119 Switches and controls and relays	
Series Name	TP	

# My Links

Login to iCOM Login as Rep/AD Login as Guest **Login to Digital** University

# Keyword Search

Search for product and support information.

All Sensing and Contro

#### **Product Search**

Part number search:

Use (\*) to expand search

**Specification Search**