



RECTANGULAR POWER CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE) 12 PC. BLOCK AMP

205042-1
TE Internal Number: 205042-1

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Cable-to-Cable, Cable-to-Panel**

Applies To **Panel, Wire/Cable**

Number of Positions **12**

Product Drawings

BLOCK, MALE, 12 PLACE FOR TYPE XII CONTACTS, M SERIES
PDF **(TIFF AVAILABLE)**
English

BLOCK, MALE, 12 PLACE FOR TYPE XII CONTACTS, M SERIES
PDF **(TIFF AVAILABLE)**
English

CAD Files

Customer View Model
2D_DXF.ZIP
English

Customer View Model
3D_IGS.ZIP
English

Customer View Model
3D_STP.ZIP
English

3D PDF
PDF
English

Catalog Pages/Data Sheets

M_SERIES_PIN_AND_SOCKET_CONNECTORS
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Product Type	Housing
Housing Type	Plug
Contact Type	Pin

Configuration Features	Number of Positions	12
Mechanical Attachment	Panel Mount Retention Type	Screw Mount
	Panel Mount Retention	With
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Black
	Housing Material	Phenolic GF
Dimensions	Width	28.19 mm [1.1098 in]
	Height	65.91 mm [2.595 in]
	Length	27.69 mm [1.0902 in]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Cable-to-Cable, Cable-to-Panel
	Applies To	Panel, Wire/Cable
	Operating Temperature	-55 – 150 °C [-67 – 302 °F]
Packaging Features	Packaging Method	Carton
	Packaging Quantity	88
Other	For Use With	Receptacle Block 205043, Standard 75 Position Hardware
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

TOGGLE SWITCHES



7320K13=TOGGLE SWI
1520135-2



SERIES M 75 POS, 2 PC.
SHIELD
202713-1



12 PL. BLOCK FEM.
205043-1



JACKSCREW KIT
201911-1



 Save to List

