

4

3

2

1

THIS DRAWING IS UNPUBLISHED.
COPYRIGHT 20 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

REVISED FOR PUBLICATION
20

LOC
CE

DIST
00

REVISIONS

P	LYN	DESCRIPTION	DATE	OWN	APPRO
1		NPR 09-0129	31MAR2009	BB	SM
2		ADD 2064938-4 AND 2-2064938-4	18MAR2010	BB	SM

⚠ MATERIAL

PROTECTIVE COVER: TPE, COLOR: BLACK, UL94 HB*

FERRULE SUBASSEMBLY: ZIRCONIA/METAL

COMPRESSION SPRING: STAINLESS STEEL

FRONT HOUSING: PEI, COLOR: BEIGE, UL94 V-0*

INNER TUBING: PTFE, COLOR: CLEAR, UL VW-I

REAR BODY: METAL

BEND LIMITING BOOT: PP, COLOR: BEIGE, UL94 V-0*

BOOT AND SHORT BUFFER BOOT: TPE, COLOR: BEIGE, UL94 V-0*

CRIMP EYELET/HEAT SHRINK ASSY: ALUM. ALLOY, HEAT SHRINK: POLYOLEFIN, UL VW-I

DUPLEX CLIP: PP, COLOR: BEIGE, UL94 V-0*

3.0mm CRIMP EYELET: NICKEL PLATED BRASS

*RATED AT QUALIFYING THICKNESS.

2. INSTRUCTION SHEET: 408-8675 AVAILABLE FOR DOWNLOAD AT
www.tycoelectronics.com/documents OR
www.ampnetconnect.com/foguide.

3. BULK PACKAGE.

900um SHORT BUFFER BOOT

1.6-2.0mm AND 2.4mm BEND LIMITING BOOT

1.6-2.0mm OR 2.4mm CRIMP EYELET/ HEAT SHRINK ASSEMBLY

CONNECTOR SUBASSEMBLY

PROTECTIVE COVER

DUPLEX CLIP

3.0mm BOOT

3.0mm CRIMP EYELET

12.65 MAX

6.1 MAX

6.25

30.2 MAX

49.55 MAX

50.55 MAX

DESCRIPTION	PART NUMBER
DUPLEX, 2.4mm JACKETED	2-2064938-4
DUPLEX, 3.0mm JACKETED	2-2064938-3
DUPLEX, 1.6-2.0mm JACKETED	2-2064938-2
DUPLEX, 900um BUFFERED	2-2064938-1
SIMPLEX, 2.4mm JACKETED	2064938-4
SIMPLEX, 3.0mm JACKETED	2064938-3
SIMPLEX, 1.6-2.0mm JACKETED	2064938-2
SIMPLEX, 900um BUFFERED	2064938-1

DESCRIPTION

PART NUMBER

OWN B. BRIGGS 31MAR2009	TYCO ELECTRONICS Harrisburg, PA 17105-3608
CHK S. MILLER 31MAR2009	
APPRO D. BAICHTLE 31MAR2009	NAME KIT, CONNECTOR, LC, MM, BULK PACK
PRODUCT SPEC	
APPLICATION SPEC	
WEIGHT	
CUSTOMER DRAWING	

SIZE CASE CODE DRAWING NO

A200779C-2064938

RESTRICTED TO

SCALE 3:1 SHEET 1 OF 2 REV 2

Downloaded from Elcodis.com electronic components distributor