

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Thermofit Heat-Shrinkable Polymeric Products (excluding solder Sleeves see separate SDS)

PART NUMBERS TUBING: AP-2000, ATUM. BSTS, BSTS-FR, CCUV, CGPE-105, CRN, DCPT, DR-25, Duraseal, DWP-125, DWUL, ES1000, ES2000. FTS, HCTE (Convolex), HF, HRHF, HRNF, HRSR, HRHT, MTZH, HT-TMS, HT-200, NT, NT-MIL, NT-FR, Nylon, PolyCrimp, PolyGP, RAYSEAL, RT-555, QS-1500, RNF-100, RNF-150, RNF-3000, RP-4800, RT-3, RT-14, RT-21, RT-218, RT-375, RT-555, RT-876, RW-175, RW-200, S-1260, SCE, SCL, SFR, SST, SST-FR, TAK, TAT-125, TMS, TMS-SCE, TW-TMS, URHR, URHT, Versafit, VPB, XFFR, ZH, ZH2 and related parts.

MOLDED PARTS: RAY-3, -4, -5, -6, -8, -12, -15, -25, -50, -51, -55, -71, -125, -146, -152, -770, -780, -790, ES Caps, PD Caps, ZH Caps and related parts.

MANUFACTURER:	TE Connectivity
DIVISION:	All Divisions
ADDRESS:	300 Constitution Drive
	Menlo Park, CA 94025-1164 USA

 EMERGENCY TELEPHONE NUMBERS:
 US: CHEMTREC 1-800-424-9300

 CN: CHEMTREC 1-800-424-9300
 Outside North America: 1-703-527-3887

 (Collect calls accepted)
 (Collect calls accepted)

 NON-EMERGENCY HEALTH/SAFETY INFORMATION:
 (US) 1-800-522-6752

 (CAN) 1-905-475-6222
 (CAN) 1-905-475-6222

 CHEMICAL FAMILY:
 Not Applicable

 PRODUCT USE:
 Typical uses of heat-shrinkable polymeric products include primary electrical insulation,

Typical uses of heat-shrinkable polymeric products include primary electrical insulation, EMI/RFI shielding, cable jacketing and repair, strain relief, waterproofing, cable/pipe identification, corrosion protection, environmental/mechanical protection, and cable joining, splicing, and termination in commercial and military/aerospace electronic applications.

This product is not hazardous when used as recommended or intended. If this product is overheated, charred, or burned the health and safety information presented in this SDS may apply.

Thermal decomposition and combustion byproducts may be regulated under US-OSHA; CAN-WHMIS; IOSH; ISO; UK-CHIP; or EU Directives (67/548/EEC-Dangerous Substance Labelling, 98/24/EC-Chemical Agents at Work, 99/45/EC-Preparation Labeling, 2001/58/EC-SDS Content, and 1907/2006/EC-REACH).

SECTION 2: HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW:					
OSHA HAZARDS:	None Applicable	e			
GHS CLASSIFICATION:	Not classified as	s hazardou	is under any GH	IS haza	rd class.
GHS LABEL ELEMENTS, IN	CLUDING PRECAUT	IONARY	STATEMENTS		
PICTOGRAM:					
SIGNAL WORD:	CAUTION!				
HAZARD STATEMENT(S)	Molten material will produce thermal burns				
PRECAUTIONARY STATEMENT(S):	Products may emit hazardous thermal decomposition byproducts if overheated or burnt. Thermal degradation is not significant at temperatures achieved during proper installation, as directed by product installation guides.				
HMIS HAZARD CLASSIFICA		•		U	
HEALTH: 1	FLAMMABILITY: 1	1	REACTIVITY:	0	PROTECTION: See PPE section.
NFPA HAZARD CLASSIFICA	• •				
HEALTH: 1	FLAMMABILITY: 1	1 1	REACTIVITY:	0	

POTENTIAL HEALTH EFFECTS:

Proper installation of this product creates no known acute or chronic health hazards.

ACUTE HEALTH HAZARDS:

- EYES: Contact with molten material may cause thermal burns.
- **SKIN:** This product is not expected to be a skin irritant. Contact with the molten material may cause thermal burns. Hydrogen fluoride fumes emitted during a fire can react with water to form hydrofluoric acid. Have calcium gluconate available for hydrofluoric acid exposure.
- **INGESTION:** Ingestion of this product is highly unlikely. There is insufficient information available on this material to predict the effects from ingestion.
- **INHALATION:** Thermal degradation and combustion byproducts may be toxic and should not be inhaled. (See Comments below and the Thermal Degradation and Combustion Byproducts Section for more specific information.)

CHRONIC HEALTH HAZARDS:

None of the ingredients to which users may be exposed and which are present at equal to or greater than 0.1% of the product, are listed by OSHA, NTP, or IARC as suspected carcinogens.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Overheating the product to charring or burning may produce vapors that may cause eye, skin, nose and throat irritation. Persons with pre-existing eye, skin, or respiratory disorders (e.g., asthma conditions) may be more susceptible to the effects of these vapors.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS				
		0/ 1		
INGREDIENTS (Chemical/Common Names):	CAS No.:	% by Wt:	EC No.:	

Not applicable – This product is a manufactured article with no reportable hazardous substance(s) or complex substance(s).

Heat-Shrinkable Polymeric Products are not hazardous during proper installation, but heat-shrinkable tubing may emit hazardous thermal decomposition and combustion byproducts if overheated to degradation. See "Hazardous Combustion Products" section of this SDS for more specific information. Base polymer materials include polyethylene and olefin copolymers. Heat-shrinkable products may be coated with or used in conjunction with adhesives/mastics, which are based on olefin copolymers or polyamides.

NA – Not applicable/NE – Not Established/ND – Not determined

SECTION 4: FIRST AID	MEASURES	



- **EYE CONTACT:** If eye irritation occurs, flush with clean water for 15 minutes while holding eyelids apart. Seek medical attention.
- **SKIN CONTACT:** First aid is normally not required. After handling product, it is good work practice to wash your hands. If molten material contacts skin, cool area immediately in water. <u>DO NOT</u> attempt to remove material from the skin. Treat as a burn. Apply calcium gluconate to area for potential hydrofluoric acid exposure and seek immediate medical attention.
 - **INGESTION:** Not a normal route of exposure. However, if swallowed and symptoms develop seek medical attention.
 - **INHALATION:** If respiratory symptoms or other symptoms of exposure develop, move victim to fresh air. If symptoms persist, seek medical attention. If breathing difficulties develop, qualified personnel should administer oxygen. Seek immediate medical attention. If victim is not breathing, immediately begin artificial respiration. Keep victim warm and quiet; seek immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT:	Not applicable
METHOD USED:	Not applicable



FLAMMABLE LIMITS

UPPER FLAMMABILITY LIMIT (% BY VOLUME): LOWER FLAMMABILITY LIMIT (% BY VOLUME): Not applicable Not applicable

AUTOIGNITION TEMPERATURE: Not applicable

SUITABLE EXTINGUISHING MEDIA:

Use carbon dioxide, water, dry chemical or foam.

Selection of extinguishing media should be based upon the size of the fire, the firefighting training/experience of the individual attempting to extinguish or control the fire, and the packaging materials exposed to the fire.

SPECIAL FIRE FIGHTING PROCEDURES & PROTECTIVE EQUIPMENT:

Firefighters should wear self-contained breathing apparatus with a full-face piece operated in the positive pressure demand mode when fighting fires. Use water spray to keep fire-exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Toxic fumes may be given off in a fire. See sections on Thermal Degradation and Combustion Byproducts and Other Precautions.

SPECIFIC HAZARDS IN CASE OF FIRE:

Thermal degradation and combustion byproducts may be toxic and should not be inhaled. Fluoropolymers will degrade upon prolonged heating or in a fire, liberating hydrogen fluoride (HF). This gas is toxic if inhaled or it comes into contact with moist skin. Apply calcium gluconate to area for hydrofluoric acid exposure and seek immediate medical attention.

HAZARDOUS COMBUSTION PRODUCTS:

Thermal degradation and combustion byproducts may be toxic and should not be inhaled. Thermal degradation is not significant at temperatures achieved during proper installation, as directed by product installation guides. At temperatures higher than those recommended for proper installation, most significantly if the product burns, the thermal degradation and combustion byproducts will depend on the base polymer used and may include, but are not limited to; carbon monoxide, carbon dioxide, organic acids, aldehydes (including formaldehyde), acetic acid, low molecular weight hydrocarbons, silicon dioxide, hydrogen chloride, hydrogen fluoride, hydrogen bromide, fluoro-olefins, perfluoroisobutylene (PFIB), carbonyl fluoride and oxides of nitrogen, phosphorus and sulfur.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:

Wear appropriate personal protection when responding to a release, as specified under Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

ENVIRONMENTAL PRECATIONS:

Prevent spilled material from entering sewers and waterways.

SPILL CONTAINMENT & CLEANUP METHODS/MATERIALS:

Sweep up and collect in a suitable container for proper disposal or reuse.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING AND STORAGE:

Handling: Avoid any vapors given off if the product is heated to decomposition, as shown by a darkening and browning of the sleeve. Avoid contact with molten material. Heat-resistant gloves are required if hot products are handled after installation. Do not consume food, beverages or tobacco in the immediate work area. Wash hands thoroughly after handling compound.

Installation: Follow appropriate TE installation instructions and application guides to ensure installation is performed properly. Ensure that any local requirements/legislation concerning the use of hand-held electrical equipment are observed. When using IR (infrared) heating devices, observe specific instructions. Do not touch hot surfaces on installation equipment.

Storage: No special storage requirements.

OTHER PRECAUTIONS (e.g.; Incompatibilities):

Avoid heating products beyond temperatures required for normal installation. See installation instructions for proper installation procedures. If product chars or burns, immediately stop heating. Avoid inhaling any fumes which may be given off under such circumstances. Ventilate and allow any vapors to disperse before continuing work in the area.

TE Connectivity



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS/SYSTEM DESIGN INFORMATION:

None

VENTILATION:

Provide general or local exhaust ventilation systems

RESPIRATORY PROTECTION:

If installation occurs in a confined, unventilated area, NIOSH/MSHA-approved respirators are recommended.

EYE PROTECTION:

Use safety glasses with side shield or goggles to prevent contact with eyes, as appropriate to the given operation.

SKIN PROTECTION:

Avoid contact with skin. Use heat resistant rated gloves to prevent skin contact, as appropriate to the given operation. If it is necessary to handle grossly overheated or fire-damaged products, wear natural rubber gloves to prevent possible contact with potentially corrosive inorganic acid residues.

Fluoropolymers will degrade upon prolonged heating or in a fire, liberating hydrogen fluoride (HF). This gas is toxic if inhaled or it comes into contact with moist skin. If skin contact occurs, apply calcium gluconate to area for hydrofluoric acid exposure and seek immediate medical attention.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: If product chars or burns the surface may contain hydrogen fluoride condensate which may cause severe burns. In this case wear neoprene gloves.

EXPOSURE GUIDELINES & LIMITS:

There are no established exposure limits for polymer mixtures.

	1 1 2		
OSHA	Permissible Exposure Limit (PEL/	/TWA)	NE
ACGIH	Threshold Limit Value (TLV)		NE
Quebec	Permissible Exposure Value (PE)	√)	NE
Ontario	Occupational Exposure Level (OF	EL)	NE
Germany	Maximale Arbeitsplatzkonzentrati	onen (MAK)	NE
United Kingdom	Occupational Exposure Standard	(OES)	NE
		TWA – 8-Hour Time Weighted Average	NE – Not Established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE:	Plastic tubing and molded parts in a variety of shapes, sizes and colors.
ODOR:	No odor
ODOR THRESHOLD:	Not applicable
PHYSICAL STATE:	Solid
pH:	Not applicable
BOILING POINT:	Not applicable
MELTING POINT:	70° – 260° C (158° - 500° F)
FREEZING POINT:	Not applicable
VAPOR PRESSURE (mmHg @ 20°C):	Not applicable
VAPOR DENSITY (AIR = 1):	Not applicable
SPECIFIC GRAVITY (H2O = 1):	0.93 – 2.15
EVAPORATION RATE: (Butyl acetate=1)	Not applicable
SOLUBILITY IN WATER:	Insoluble
FLASH POINT:	Not applicable
AUTO-IGNITION TEMPERATURE:	Not applicable
LOWER EXPLOSIVE LIMIT (LEL):	Not applicable
UPPER EXPLOSIVE LIMIT (UEL):	Not applicable
PARTITION COEFFICIENT:	Not applicable
VISCOSITY (centipoise @ 25° C):	Not applicable
DECOMPOSITION TEMPERATURE:	Not Determined
SECTION 10: STABILITY AND REAC	ΤΙVΙΤΥ

STABILITY:	This product is stable under normal use.
INCOMPATIBILITY (MATERIAL TO AVOID):	None known.
HAZARDOUS DECOMPOSITION OR BY-	See Section 5: FIRE FIGHTING MEASURES (Hazardous Combustion
PRODUCTS:	Products).
HAZARDOUS POLYMERIZATION:	Will not occur. No known polymerization conditions to avoid.
CONDITIONS TO AVOID:	Avoid overheating of product.

SECTION 11: TOXICOLOGICAL INFORMATION



ACUTE TOXICITY (Test Results Basis and Comments):

LD50 (Oral, Rat): Not determined

LC₅₀ (Inhalation, Rat): Not determined ROUTES OF ENTRY/EFFECTS OF ACUTE OVEREXPOSURE:

Eye Contact: Contact with the molten material may cause thermal burns.

Skin Contact: This product is not expected to be a skin irritant. Contact with the molten material may cause thermal burns. No harmful effects are expected from skin contact with of this product.

Ingestion (Swallowing): Ingestion of this product is highly unlikely. There is insufficient information available on this material to predict the effects from ingestion.

Inhalation (Breathing): Thermal degradation and combustion byproducts may be toxic and should not be inhaled. (See the Thermal Degradation and Combustion Byproducts Section for more specific information.)

SUBCHRONIC/CHRONIC TOXICITY (Test Results and Comments):

IRRITANCY OF PRODUCT: See above

SENSITIZATION TO MATERIAL: Not known.

CARCINOGENICITY: None of the ingredients to which users may be exposed and which are present at equal to or greater than 0.1% of the product, are listed by OSHA, NTP, or IARC as carcinogens.

REPRODUCTIVE TOXICITY: None known.

TERATOGENICITY: None known.

MUTAGENICITY: None known.

TOXICOLOGICALLY SYNERGISTIC PRODUCTS: None known

SECTION 12: ECOLOGICAL INFORMATION

PERSISTENCE & DEGRADABILITY:

No data available on biodegradation.

BIO-ACCUMULATIVE POTENTIAL (Including Mobility):

No data available on bioaccumulation.

AQUATIC TOXICITY (Test Results & Comments):

No data available on aquatic toxicity.

Additional Information

- No known effects on stratospheric ozone depletion.
- Water Endangering Class (WGK): NA

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: HAZARDOUS WASTE	Treatment, storage, and disposal must be in accordance with applicable, federal, state, provincial, and local regulations. Waste resulting from this product as supplied is not known to be classified as hazardous.	
CLASS/CODE:	US - Not applicable to material as manufactured for distribution into commerce. CN – Not applicable to material as manufactured for distribution into commerce. EWC – Not applicable to material as manufactured for distribution into commerce.	

Additional Information

Not Included - Dispose/Recycle as allowed by local jurisdiction for the end-of-life characteristics as-disposed.

SECTION 14: TRANSPORT INFORMATION



GROUND - US-DOT/CAN-TDG/EU-ADR/APEC-ADR:

Proper Shipping Name Hazard Class Packing Group	Not Subject to HMR NA NA	ID Number Labels	NA NA
AIRCRAFT – ICAO-IATA: Proper Shipping Name Hazard Class Packing Group	Not Subject to DGR NA NA	ID Number Labels	NA NA
VESSEL – IMO-IMDG: Proper Shipping Name Hazard Class Packing Group	Not Subject to IMDG NA NA	ID Number Labels	NA NA

Additional Information

• Transportation must be in accordance with applicable, federal, state, provincial, and local regulations.

- Transport requires proper packaging and paperwork, including the Nature and Quantity of goods, per applicable origin/destination/customs points as-shipped. Statement of Jurisdictional/Modal Special Provision(s) required.
- Not restricted for any mode of international transport as finished goods.
- Not a Marine Pollutant as-shipped per IMO/IMDG.

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS:

All components are listed on the TSCA; EINECS/ELINCS; and DSL, unless noted otherwise below.

U.S. FEDERAL REGULATIONS:

TSCA Section 8b – Inventory Status: All chemicals comprising this product are either exempt or listed on the TSCA Inventory.

TSCA Section 12b – Export Notification: If the product contains chemicals subject to TSCA Section 12b export notification they are listed below:

<u>Chemical</u>		<u>CAS #</u>	<u>% wt</u>		
None		NA	NA		
CERCLA (COMPREHENSIVE RESPON	SE COMPENSATION, AND	LIABILITY ACT)			
Chemicals present in the product white	ch could require reporting ur	nder the statute:			
<u>Chemical</u>		CAS #	<u>% wt</u>		
None		NA	NA		
SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT) If the product contains chemicals subject to the reporting requirements of Section 313 of SARA Title III, they are listed below.					
Chemical CAS # % wt					
None		NA	NA		
CERCLA SECTION 311/312 HAZARD C	CATEGORIES: Note that thi	s product is exempt from	these regulations.		
	Fire Hazard No)			
	Pressure Hazard No)			
	Reactivity Hazard No.)			
	Immediate Hazard No)			

Immediate Hazard No Delayed Hazard No



STATE REGULATIONS (US):

California Proposition 65

The following chemicals identified to exist in the product as distributed into commerce are known to the State of California to cause cancer, birth defects, or other reproductive harm:

Chemical

None

<u>CAS #</u> NA <u>% Wt</u>

INTERNATIONAL REGULATIONS (Non-US): Canadian Domestic Substance List (DSL)

Not applicable.

WHMIS Classifications

Not applicable.

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the SDS contains all of the information required by the *Controlled Products Regulations*."

NPRI and Ontario Regulation 127/01

This product contains the following chemicals subject to the reporting requirements of Canada NPRI and/or Ont. Reg. 127/01:

Chemi	ical
None	

9	CAS	#	
Ī	NA		

<u>% Wt</u> NA

European Inventory of Existing Commercial Chemical Substances (EINECS)

All ingredients remaining in the product as distributed into commerce are exempt from, or included on, the European Inventory of Existing Commercial Chemical Substances.

European Communities (EC) Hazard Classification according to directives 67/548/EEC and 1999/45/EC.

R-Phrases	<u>S-Phrases</u>
None	None

Additional Information

This product may be regulated under additional regulations and laws not identified above, such as for uses other than described or as-designed/as-intended by the manufacturer, or for distribution into specific domestic destinations.

SECTION 16: OTHER INFORMATION

OTHER INFORMATION:

Distribution into Quebec to follow Canadian Controlled Product Regulations (CPR) 24(1) and 24(2).

Distribution into the EU to follow applicable Directives to the Use, Import/Export of the product as-sold.

SDS PREPARATION INFORMATION:

Department Issuing SDS: TE Connectivity, Menlo Park

DATE OF ISSUE: July 9, 2015 SUPERCEDES: December 30, 2014

DISCLAIMER:

Tyco Electronics makes no warranties as to the accuracy or completeness of this information and disclaims any liability in connection with its use. Tyco Electronics' obligation shall be only as set forth in Tyco Electronics' standard terms and conditions of sale for this product. In no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product.

The information presented herein was prepared at Tyco Electronics by qualified technical personnel, and to our knowledge it is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser/user will independently determine the suitability of the product for this purpose. The data do not constitute a warranty, expressed or implied, statutory or otherwise, nor are they a representation for which Tyco Electronics assumes legal responsibility. The data are submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with the applicable federal, State/Provincial, and local laws and regulations.

Users are advised that they may have additional disclosure obligations under other national and local laws. Users are advised to ensure that this information is brought to the attention of all employees, agents, and contractors handling this product. Users of Tyco Electronics products should make their own evaluation to determine the suitability of each such product for the specific application and to establish safe handling and installation procedures. Distributors of this product are advised to forward this document, or the information contained herein, to every purchaser of this product.