


Potential distributors - UMK- PVB 2/24/ZFKDS - 2302366

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE module, with two equipotential busbars (P1, P2) for potential distribution, for mounting on NS 32 or on NS 35/7.5


The illustration shows version UMK-PVB 2/16/ZFKDS

Why buy this product

- ☒ Consecutive numbering
- ☒ Separate supply
- ☒ Two potential levels



Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 880514
GTIN	4017918880514
Weight per Piece (excluding packing)	148.900 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Dimensions

Width	67.5 mm
Height	77 mm
Depth	52 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

Potential distributors - UMK- PVB 2/24/ZFKDS - 2302366

Technical data

Ambient conditions

Ambient temperature (storage/transport)	-20 °C ... 70 °C
---	------------------

General

Nominal voltage U_N	250 V AC/DC
Max. current carrying capacity per branch	17 A
Total current	32 A (per potential)
Mounting position	any
Designation	Air clearances and creepage distances in a circuit
Standards/regulations	DIN EN 50178
Rated surge voltage	2.3 kV
Rated insulation voltage	260 V AC
Degree of pollution	2
Overvoltage category	II

Connection data, supply

Connection method	Spring-cage connection
Stripping length	8 mm
Conductor cross section solid	0.2 mm ² ... 6 mm ²
Conductor cross section flexible	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 10
Number of connections	2

Connection data, distribution

Connection method	Spring-cage connection
Stripping length	8 mm
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12
Number of connections	24

Standards and Regulations

Connection in acc. with standard	CUL
Designation	Air clearances and creepage distances in a circuit
Standards/regulations	DIN EN 50178
Rated insulation voltage	260 V AC
Rated surge voltage	2.3 kV
Insulation	Basic insulation
Degree of pollution	2
Overvoltage category	II

Potential distributors - UMK- PVB 2/24/ZFKDS - 2302366

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals


Approvals


Approvals

UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal current I _N		10 A	
Nominal voltage U _N		250 V	

cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal current I _N		10 A	
Nominal voltage U _N		250 V	

EAC		EAC-Zulassung
-----	---	---------------

EAC		7500651.22.01.00246
-----	---	---------------------

Potential distributors - UMK- PVB 2/24/ZFKDS - 2302366

Approvals

cULus Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>