

Item no.:	232-372
Product description:	HEADERS FOR DOUBLE DECK ASSEMBLY RIGHT ANGLE SOLDER PIN, 1 X 1 MM / 0.039 X 0.039 IN 12 POLE PIN SPACING 5.08 MM / 0.2 IN WITH CLOSED END MATING DIRECTION PARALLEL TO PCB



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Weight	10.4 g
Color	orange
pole count	12
Height	26 mm
Height	1.024 in
Width	64.16 mm
Width	2.526 in
Depth	17 mm
Depth	0.669 in
Pin spacing from	5.08 mm
Pin spacing from	0.2 in
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	12 A
Pollution degree	2
Measured voltage EN	630 V

Measured shock voltage	4 kV
Current intensity EN	12 A
Material group	I
Contact material	Electrolytic copper (Ecu)
Contact surface	tin-plated



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
232-372	ABS	04-HG469925/1-PDA	250	12	0,08-2,5
232-372	BV	11915/A0	400	16	2,5
232-372	CCA	5764	250	12	1x1
232-372	CSA	154112-1466354	300	10	
232-372	GL	17296-00HH	250	12	0,08-2,5
232-372	KEMA	2083746.02	250	12	1x1
232-372	KR	HMB05880-EL003	250/400	12/16	2,5
232-372	LR	96/20035	250	12	0,08-2,5
232-372	RMR	11130002	250	12	0,08-2,5
232-372	UR	E45171	600	10	
232-372	UR	E45172	300	10	

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected